

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P250447

Luminaire Tested: **LD8B175D010 ER8B1759727 8LBN0B**

Issue Date: 03/03/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P250447  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P13948)  
Test Lab: INNOVATION CENTER-P1  
Issue Date: 03/03/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LD8B175D010 ER8B1759727 8LBN0B  
Description: PORTFOLIO 8 INCH NARROW DISTRIBUTION 50 DEGREE CUTOFF RECESSED  
DOWNLIGHT  
97 CRI 2700 CCT WITH SPECULAR BLACK TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 7266.0 lumens  
Efficiency: N/A  
Efficacy: 41.0 lumens/watt  
Spacing Criteria (0/90/45): 0.69 / 0.69 / 0.77  
Luminous Opening: Point Source (0' x 0' x 0')  
CIE Type: Direct


Input Watts (W): 177.2  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P250447

CATALOG NUMBER: LD8B175D010 ER8B1759727 8LBN0B

### Luminous Intensity Polar Plot





TEST NUMBER: P250447

CATALOG NUMBER: LD8B175D010 ER8B1759727 8LBN0B

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| RF  | 20  |     |     |     | 20  |     |     |     | 20  |     |     |     | 20  |     |     |     | 20  |     |
| RC  | 80  |     |     |     | 70  |     |     |     | 50  |     |     |     | 30  |     |     |     | 10  | 0   |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  | 50  | 30  | 10  | 50  | 30  | 10  | 0   |
| RCR |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |     |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 | 106 | 106 | 106 | 102 | 102 | 102 | 100 |
| 1   | 114 | 111 | 109 | 107 | 112 | 109 | 107 | 105 | 105 | 104 | 102 | 101 | 100 | 99  | 98  | 97  | 96  | 94  |
| 2   | 109 | 104 | 101 | 97  | 107 | 103 | 99  | 96  | 99  | 97  | 94  | 96  | 94  | 92  | 94  | 92  | 90  | 89  |
| 3   | 104 | 98  | 93  | 90  | 102 | 97  | 92  | 89  | 94  | 90  | 88  | 92  | 89  | 86  | 89  | 87  | 85  | 83  |
| 4   | 99  | 92  | 87  | 83  | 97  | 91  | 86  | 83  | 89  | 85  | 82  | 87  | 84  | 81  | 85  | 82  | 80  | 78  |
| 5   | 95  | 87  | 82  | 78  | 93  | 86  | 81  | 77  | 84  | 80  | 77  | 83  | 79  | 76  | 81  | 78  | 75  | 74  |
| 6   | 90  | 82  | 77  | 73  | 89  | 81  | 76  | 72  | 80  | 75  | 72  | 79  | 75  | 71  | 77  | 74  | 71  | 70  |
| 7   | 86  | 78  | 72  | 68  | 85  | 77  | 72  | 68  | 76  | 71  | 68  | 75  | 71  | 67  | 74  | 70  | 67  | 66  |
| 8   | 83  | 74  | 68  | 64  | 81  | 73  | 68  | 64  | 72  | 67  | 64  | 71  | 67  | 64  | 70  | 66  | 63  | 62  |
| 9   | 79  | 70  | 65  | 61  | 78  | 70  | 64  | 61  | 69  | 64  | 61  | 68  | 63  | 60  | 67  | 63  | 60  | 59  |
| 10  | 76  | 67  | 61  | 58  | 75  | 66  | 61  | 58  | 65  | 61  | 57  | 65  | 60  | 57  | 64  | 60  | 57  | 56  |

**AVERAGE LUMINANCE (cd/sqm):**





TEST NUMBER: P250447

CATALOG NUMBER: LD8B175D010 ER8B1759727 8LBN0B

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 1042.3 | 14.3      |
| 10°-20°   | 2265.3 | 31.2      |
| 20°-30°   | 2432.0 | 33.5      |
| 30°-40°   | 1314.4 | 18.1      |
| 40°-50°   | 205.1  | 2.8       |
| 50°-60°   | 5.6    | 0.1       |
| 60°-70°   | 1.4    | 0.0       |
| 70°-80°   | 0.0    | 0.0       |
| 80°-90°   | 0.0    | 0.0       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| 0°-30°    | 5739.5 | 79.0      |
| 0°-40°    | 7053.9 | 97.1      |
| 0°-60°    | 7264.6 | 100.0     |
| 0°-90°    | 7266.0 | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 7266.0 | 100.0     |

**CANDELA DISTRIBUTION:**

|     | 0°    | Flux |
|-----|-------|------|
| 0°  | 11610 |      |
| 5°  | 11381 | ###  |
| 15° | 8088  | 2265 |
| 25° | 5391  | 2432 |
| 35° | 2065  | 1314 |
| 45° | 189   | 205  |
| 55° | 0     | 6    |
| 65° | 0     | 1    |
| 75° | 0     | 0    |
| 85° | 0     | 0    |
| 90° | 0     |      |



TEST NUMBER: P250447

CATALOG NUMBER: LD8B175D010 ER8B1759727 8LBN0B

**CANDELA DISTRIBUTION (FULL):**

|       | 0°      |
|-------|---------|
| 0°    | 11610.4 |
| 1°    | 11632.4 |
| 2°    | 11621.5 |
| 3°    | 11581.7 |
| 4°    | 11505.2 |
| 5°    | 11381.4 |
| 6°    | 11210.9 |
| 7°    | 10981.5 |
| 8°    | 10694.4 |
| 9°    | 10364.0 |
| 10°   | 9996.5  |
| 11°   | 9611.1  |
| 12°   | 9211.2  |
| 13°   | 8811.8  |
| 14°   | 8440.6  |
| 15°   | 8088.1  |
| 16°   | 7764.5  |
| 17°   | 7451.9  |
| 18°   | 7161.1  |
| 19°   | 6888.8  |
| 20°   | 6626.8  |
| 21°   | 6372.3  |
| 22°   | 6132.2  |
| 23°   | 5892.6  |
| 24°   | 5641.8  |
| 25°   | 5390.8  |
| 26°   | 5136.3  |
| 27°   | 4845.6  |
| 28°   | 4525.6  |
| 29°   | 4198.8  |
| 30°   | 3856.9  |
| 31°   | 3489.8  |
| 32°   | 3122.4  |
| 33°   | 2759.0  |
| 34°   | 2391.9  |
| 35°   | 2064.6  |
| 37.5° | 1319.5  |
| 40°   | 763.4   |
| 42.5° | 407.3   |
| 45°   | 189.2   |
| 47.5° | 102.0   |
| 50°   | 33.0    |
| 52.5° | 3.7     |
| 55°   | 0.0     |
| 57.5° | 3.7     |



TEST NUMBER: P250447

CATALOG NUMBER: LD8B175D010 ER8B1759727 8LBN0B

**CANDELA DISTRIBUTION (continued):**

|       | 0°  |
|-------|-----|
| 60°   | 3.7 |
| 62.5° | 0.0 |
| 65°   | 0.0 |
| 67.5° | 3.7 |
| 70°   | 0.0 |
| 72.5° | 0.0 |
| 75°   | 0.0 |
| 77.5° | 0.0 |
| 80°   | 0.0 |
| 82.5° | 0.0 |
| 85°   | 0.0 |
| 87.5° | 0.0 |
| 90°   | 0.0 |

(END OF REPORT)