

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P244364

Luminaire Tested: **LD8B20D010 ER8B20927 8LBN0H**

Issue Date: 03/03/2020

Test Information

Test Method: LM-79-08
Report Number: P244364
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P27944)
Test Lab: INNOVATION CENTER-P2
Issue Date: 03/03/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD8B20D010 ER8B20927 8LBN0H
Description: PORTFOLIO 8 INCH NARROW DISTRIBUTION 50 DEGREE CUTOFF RECESSED
DOWNLIGHT
97 CRI 2700 CCT WITH SEMI-SPECULAR CLEAR TRIM
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1575.0 lumens
Efficiency: N/A
Efficacy: 73.9 lumens/watt
Spacing Criteria (0/90/45): 0.69 / 0.69 / 0.79
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 21.3
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P244364

CATALOG NUMBER: LD8B20D010 ER8B20927 8LBN0H

Luminous Intensity Polar Plot





TEST NUMBER: P244364

CATALOG NUMBER: LD8B20D010 ER8B20927 8LBN0H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	114	111	109	106	111	109	107	105	105	103	101		101	100	98		98	97	96	94
2	108	104	100	96	106	102	98	95	99	96	93		96	93	91		93	91	89	88
3	103	97	92	88	101	95	91	87	93	89	86		90	87	85		88	86	83	82
4	98	91	85	81	96	90	85	81	87	83	80		85	82	79		84	80	78	76
5	93	85	79	75	92	84	79	75	82	78	74		81	77	74		79	76	73	72
6	89	80	74	70	87	79	74	70	78	73	69		76	72	69		75	71	69	67
7	85	76	70	66	83	75	69	65	74	69	65		72	68	65		71	67	64	63
8	81	71	66	62	79	71	65	61	70	65	61		69	64	61		68	64	61	59
9	77	68	62	58	76	67	62	58	66	61	58		65	61	58		64	60	57	56
10	74	64	59	55	73	64	58	55	63	58	55		62	58	54		61	57	54	53

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P244364

CATALOG NUMBER: LD8B20D010 ER8B20927 8LBN0H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	202.2	12.8
10°-20°	451.8	28.7
20°-30°	513.7	32.6
30°-40°	301.7	19.2
40°-50°	81.0	5.1
50°-60°	19.2	1.2
60°-70°	4.4	0.3
70°-80°	1.0	0.1
80°-90°	0.1	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1167.7	74.1
0°-40°	1469.4	93.3
0°-60°	1569.5	99.7
0°-90°	1575.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1575.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2404	
5°	2234	202
15°	1616	452
25°	1134	514
35°	470	302
45°	97	81
55°	19	19
65°	4	4
75°	1	1
85°	0	0
90°	0	



TEST NUMBER: P244364

CATALOG NUMBER: LD8B20D010 ER8B20927 8LBN0H

CANDELA DISTRIBUTION (FULL):

0°	
0°	2404.2
1°	2391.0
2°	2366.4
3°	2331.9
4°	2287.2
5°	2234.0
6°	2174.0
7°	2105.9
8°	2037.7
9°	1969.2
10°	1903.7
11°	1839.9
12°	1779.8
13°	1724.0
14°	1668.0
15°	1616.0
16°	1564.9
17°	1514.4
18°	1465.4
19°	1415.9
20°	1367.6
21°	1319.2
22°	1272.8
23°	1227.1
24°	1180.4
25°	1133.6
26°	1085.1
27°	1032.4
28°	977.2
29°	916.5
30°	851.1
32.5°	667.6
35°	469.7
37.5°	309.6
40°	202.6
42.5°	139.8
45°	96.9
47.5°	66.5
50°	44.1
52.5°	28.7
55°	19.1
57.5°	12.7
60°	8.5
62.5°	5.9
65°	4.3



TEST NUMBER: P244364

CATALOG NUMBER: LD8B20D010 ER8B20927 8LBN0H

CANDELA DISTRIBUTION (continued):

	0°
67.5°	2.7
70°	1.6
72.5°	1.0
75°	1.0
77.5°	0.6
80°	0.6
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)