

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P246656

Luminaire Tested: **LD8B20D010 ER8B20940 8LBN0MW**

Issue Date: 03/03/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P246656  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P201839)  
Test Lab: INNOVATION CENTER-P1  
Issue Date: 03/03/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LD8B20D010 ER8B20940 8LBN0MW  
Description: PORTFOLIO 8 INCH NARROW DISTRIBUTION 50 DEGREE CUTOFF RECESSED  
DOWNLIGHT  
90 CRI 4000 CCT WITH MATTE WHITE TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 1828.0 lumens  
Efficiency: N/A  
Efficacy: 85.8 lumens/watt  
Spacing Criteria (0/90/45): 0.79 / 0.79 / 0.85  
Luminous Opening: Circular (Dia: 0.67' x H: 0')  
CIE Type: Direct


Input Watts (W): 21.3  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P246656

CATALOG NUMBER: LD8B20D010 ER8B20940 8LBN0MW

### Luminous Intensity Polar Plot





TEST NUMBER: P246656

CATALOG NUMBER: LD8B20D010 ER8B20940 8LBN0MW

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	112	109	106	103	109	106	104	101	102	100	98		98	97	95		95	94	92	90
2	105	99	94	90	103	97	93	89	94	90	87		91	88	85		88	86	83	82
3	99	91	85	80	96	89	84	79	87	82	78		84	80	77		82	78	76	74
4	93	84	77	72	91	83	76	72	80	75	71		78	74	70		76	72	69	67
5	87	78	71	66	85	77	70	65	75	69	65		73	68	64		71	67	64	62
6	82	72	65	60	81	71	65	60	70	64	60		68	63	59		67	62	59	57
7	78	67	60	56	76	67	60	55	65	59	55		64	59	55		63	58	54	53
8	74	63	56	52	72	62	56	51	61	55	51		60	55	51		59	54	51	49
9	70	59	53	48	69	59	52	48	58	52	48		57	51	48		56	51	47	46
10	66	56	49	45	65	55	49	45	54	49	45		54	48	45		53	48	45	43

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	59113
5°	58689
10°	53484
15°	45843
20°	40629
25°	36253
30°	29279
35°	20313
40°	12889
45°	9577
50°	8175
55°	7166
60°	6414
65°	5728
70°	4941
75°	4539
80°	4226
85°	3750



TEST NUMBER: P246656

CATALOG NUMBER: LD8B20D010 ER8B20940 8LBN0MW

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	174.9	9.6
10°-20°	404.5	22.1
20°-30°	481.0	26.3
30°-40°	340.1	18.6
40°-50°	175.5	9.6
50°-60°	120.4	6.6
60°-70°	78.1	4.3
70°-80°	41.0	2.2
80°-90°	12.6	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1060.4	58.0
0°-40°	1400.5	76.6
0°-60°	1696.4	92.8
0°-90°	1828.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1828.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	1917	
5°	1896	175
15°	1436	405
25°	1066	481
35°	540	340
45°	220	176
55°	133	120
65°	78	78
75°	38	41
85°	11	12
90°	0	1
95°	0	0
105°	0	0
115°	0	0
125°	0	0
135°	0	0
145°	0	0
155°	0	0
165°	0	0
175°	0	0
180°	0	0



TEST NUMBER: P246656

CATALOG NUMBER: LD8B20D010 ER8B20940 8LBN0MW

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	1917.0
2.5°	1917.0
5°	1896.0
7.5°	1826.3
10°	1708.1
12.5°	1567.0
15°	1436.0
17.5°	1328.2
20°	1238.1
22.5°	1152.9
25°	1065.5
27.5°	956.0
30°	822.3
32.5°	678.5
35°	539.6
37.5°	415.8
40°	320.2
42.5°	257.7
45°	219.6
47.5°	191.9
50°	170.4
52.5°	151.5
55°	133.3
57.5°	117.2
60°	104.0
62.5°	90.1
65°	78.5
67.5°	68.0
70°	54.8
72.5°	47.0
75°	38.1
77.5°	30.9
80°	23.8
82.5°	17.7
85°	10.6
87.5°	6.1
90°	0.0
92.5°	0.0
95°	0.0
97.5°	0.0
100°	0.0
102.5°	0.0
105°	0.0
107.5°	0.0
110°	0.0



TEST NUMBER: P246656

CATALOG NUMBER: LD8B20D010 ER8B20940 8LBN0MW

**CANDELA DISTRIBUTION (continued):**

	0°
112.5°	0.0
115°	0.0
117.5°	0.0
120°	0.0
122.5°	0.0
125°	0.0
127.5°	0.0
130°	0.0
132.5°	0.0
135°	0.0
137.5°	0.0
140°	0.0
142.5°	0.0
145°	0.0
147.5°	0.0
150°	0.0
152.5°	0.0
155°	0.0
157.5°	0.0
160°	0.0
162.5°	0.0
165°	0.0
167.5°	0.0
170°	0.0
172.5°	0.0
175°	0.0
177.5°	0.0
180°	0.0

(END OF REPORT)