

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P243860

Luminaire Tested: **LD8B20D010 ER8B209727 8LBW0LI**

Issue Date: 03/03/2020

Test Information

Test Method: LM-79-08
Report Number: P243860
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P27941)
Test Lab: INNOVATION CENTER-P2
Issue Date: 03/03/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD8B20D010 ER8B209727 8LBW0LI
Description: PORTFOLIO 8 INCH WIDE DISTRIBUTION 60 DEGREE CUTOFF RECESSED
DOWNLIGHT
97 CRI 2700 CCT WITH SPECULAR CLEAR TRIM
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 1609.0 lumens
Efficiency: N/A
Efficacy: 75.5 lumens/watt
Spacing Criteria (0/90/45): 1.34 / 1.34 / 1.17
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 21.3
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P243860

CATALOG NUMBER: LD8B20D010 ER8B209727 8LBW0LI

Luminous Intensity Polar Plot





TEST NUMBER: P243860

CATALOG NUMBER: LD8B20D010 ER8B209727 8LBW0LI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	113	110	107	105	110	108	105	103	104	102	100		100	98	97		96	95	94	92
2	106	101	97	93	104	99	95	92	96	93	90		93	90	88		90	88	86	84
3	100	93	87	83	98	92	86	82	89	85	81		86	83	80		84	81	78	77
4	94	86	79	75	92	84	79	74	82	77	73		80	76	72		78	75	72	70
5	88	79	72	68	87	78	72	67	76	71	67		74	70	66		73	69	65	64
6	83	73	66	62	82	72	66	61	71	65	61		69	64	60		68	63	60	58
7	78	68	61	56	77	67	61	56	66	60	56		64	59	55		63	59	55	54
8	74	63	56	52	72	62	56	52	61	55	51		60	55	51		59	54	51	49
9	70	59	52	48	68	58	52	47	57	51	47		56	51	47		55	50	47	45
10	66	55	48	44	65	54	48	44	53	48	44		53	47	44		52	47	43	42

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P243860

CATALOG NUMBER: LD8B20D010 ER8B209727 8LBW0LI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	92.8	5.8
10°-20°	307.6	19.1
20°-30°	483.9	30.1
30°-40°	460.3	28.6
40°-50°	212.2	13.2
50°-60°	48.2	3.0
60°-70°	3.2	0.2
70°-80°	0.6	0.0
80°-90°	0.1	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	884.3	55.0
0°-40°	1344.7	83.6
0°-60°	1605.1	99.8
0°-90°	1609.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1609.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	926	
5°	950	93
15°	1091	308
25°	1061	484
35°	754	460
45°	260	212
55°	47	48
65°	2	3
75°	0	1
85°	0	0
90°	0	



TEST NUMBER: P243860

CATALOG NUMBER: LD8B20D010 ER8B209727 8LBW0LI

CANDELA DISTRIBUTION (FULL):

0°	
0°	925.8
1°	925.3
2°	927.1
3°	932.4
4°	940.3
5°	949.5
6°	961.0
7°	973.3
8°	986.1
9°	1001.0
10°	1016.9
11°	1032.7
12°	1049.5
13°	1065.3
14°	1079.8
15°	1091.3
16°	1099.7
17°	1105.4
18°	1108.0
19°	1107.6
20°	1104.5
21°	1099.2
22°	1092.6
23°	1083.8
24°	1073.7
25°	1061.4
26°	1046.8
27°	1028.3
28°	1006.3
29°	980.8
30°	951.3
32.5°	862.8
35°	754.5
37.5°	628.6
40°	491.3
42.5°	363.2
45°	259.7
47.5°	184.0
50°	126.8
52.5°	81.0
55°	46.7
57.5°	23.3
60°	10.1
62.5°	4.0
65°	2.2



TEST NUMBER: P243860

CATALOG NUMBER: LD8B20D010 ER8B209727 8LBW0LI

CANDELA DISTRIBUTION (continued):

	0°
67.5°	1.3
70°	0.9
72.5°	0.9
75°	0.4
77.5°	0.4
80°	0.4
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)