

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P247849

Luminaire Tested: **LD8B200D010 ER8B200840 8LBMOLI**

Issue Date: 03/03/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P247849  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1801-521-90)  
Test Lab: INNOVATION CENTER(G1)  
Issue Date: 03/03/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LD8B200D010 ER8B200840 8LBM0LI  
Description: PORTFOLIO 8 INCH MEDIUM DISTRIBUTION 55 DEG CUTOFF RECESSED  
DOWNLIGHT  
80 CRI 4000 CCT WITH SPECULAR CLEAR TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 21947.0 lumens  
Efficiency: N/A  
Efficacy: 98.3 lumens/watt  
Spacing Criteria (0/90/45): 0.7 / 0.7 / 0.76  
Luminous Opening: Circular (Dia: 0.67' x H: 0')  
CIE Type: Direct


Input Watts (W): 223.3  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P247849

CATALOG NUMBER: LD8B200D010 ER8B200840 8LBM0LI

### Luminous Intensity Polar Plot





TEST NUMBER: P247849

CATALOG NUMBER: LD8B200D010 ER8B200840 8LBM0LI

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	114	111	109	107	111	109	107	105	105	103	102		101	100	99		98	97	96	94
2	109	104	100	97	106	102	99	96	99	96	94		96	94	92		93	91	90	88
3	103	97	93	89	102	96	92	88	93	90	87		91	88	85		89	86	84	83
4	99	91	86	82	97	90	86	82	88	84	81		86	83	80		84	81	79	78
5	94	86	81	77	92	85	80	76	83	79	76		82	78	75		80	77	74	73
6	90	81	76	72	88	80	75	71	79	74	71		78	73	70		76	73	70	68
7	86	77	71	67	84	76	71	67	75	70	67		74	69	66		73	69	66	65
8	82	73	67	63	80	72	67	63	71	66	63		70	66	62		69	65	62	61
9	78	69	63	60	77	68	63	59	68	63	59		67	62	59		66	62	59	58
10	75	66	60	56	74	65	60	56	64	59	56		64	59	56		63	59	56	55

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	1057411
5°	1027073
10°	908960
15°	772592
20°	643266
25°	520229
30°	386628
35°	241329
40°	118838
45°	50277
50°	18201
55°	5613
60°	3016
65°	1255
70°	1307
75°	310
80°	462
85°	0



TEST NUMBER: P247849

CATALOG NUMBER: LD8B200D010 ER8B200840 8LBM0LI

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	3034.6	13.8
10°-20°	6731.4	30.7
20°-30°	6953.7	31.7
30°-40°	4053.8	18.5
40°-50°	1015.9	4.6
50°-60°	123.1	0.6
60°-70°	25.7	0.1
70°-80°	3.3	0.0
80°-90°	5.4	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	16719.7	76.2
0°-40°	20773.6	94.7
0°-60°	21912.6	99.8
0°-90°	21947.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	21947.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	34291	
5°	33180	###
15°	24201	6731
25°	15290	6954
35°	6411	4054
45°	1153	1016
55°	104	123
65°	17	26
75°	3	3
85°	0	5
90°	0	



TEST NUMBER: P247849

CATALOG NUMBER: LD8B200D010 ER8B200840 8LBM0LI

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	34291.1
2.5°	34025.3
5°	33180.5
7.5°	31517.3
10°	29029.1
12.5°	26564.8
15°	24200.9
17.5°	21829.0
20°	19602.6
22.5°	17463.5
25°	15290.0
27.5°	13128.4
30°	10858.3
32.5°	8618.7
35°	6410.8
37.5°	4504.4
40°	2952.2
42.5°	1860.2
45°	1152.9
47.5°	703.4
50°	379.4
52.5°	185.1
55°	104.4
57.5°	56.8
60°	48.9
62.5°	34.4
65°	17.2
67.5°	21.2
70°	14.5
72.5°	0.0
75°	2.6
77.5°	1.3
80°	2.6
82.5°	4.0
85°	0.0
87.5°	14.5
90°	0.0

(END OF REPORT)