

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P248017

Luminaire Tested: **LD8B200D010 ER8B2009730 8LBW0WMH**

Issue Date: 03/03/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P248017  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1801-521-71)  
Test Lab: INNOVATION CENTER(G1)  
Issue Date: 03/03/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LD8B200D010 ER8B2009730 8LBW0WMH  
Description: PORTFOLIO 8 INCH WIDE DISTRIBUTION 60 DEGREE CUTOFF RECESSED  
DOWNLIGHT  
97 CRI 3000 CCT WITH WARM HAZE TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 15536.1 lumens  
Efficiency: N/A  
Efficacy: 69.6 lumens/watt  
Spacing Criteria (0/90/45): 1.12 / 1.12 / 1.06  
Luminous Opening: Point Source (0' x 0' x 0')  
CIE Type: Direct


Input Watts (W): 223.3  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P248017

CATALOG NUMBER: LD8B200D010 ER8B2009730 8LBW0WMH

### Luminous Intensity Polar Plot





TEST NUMBER: P248017

CATALOG NUMBER: LD8B200D010 ER8B2009730 8LBW0WMH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	112	109	106	104	110	107	104	102	103	101	99	99	97	96	96	94	93	91
2	106	100	95	91	103	98	94	90	95	91	88	92	89	86	89	86	84	82
3	99	91	85	81	97	90	84	80	87	82	79	85	81	77	82	79	76	74
4	93	84	77	72	91	82	76	72	80	75	71	78	74	70	76	72	69	67
5	87	77	70	65	85	76	70	65	74	68	64	72	67	64	71	66	63	61
6	82	71	64	59	80	70	64	59	69	63	58	67	62	58	66	61	58	56
7	77	66	59	54	75	65	58	54	64	58	53	62	57	53	61	56	53	51
8	72	61	54	49	71	61	54	49	59	53	49	58	53	49	57	52	49	47
9	68	57	50	46	67	56	50	46	55	49	45	54	49	45	54	49	45	43
10	64	53	47	42	63	53	46	42	52	46	42	51	46	42	50	45	42	40

**AVERAGE LUMINANCE (cd/sqm):**





TEST NUMBER: P248017

CATALOG NUMBER: LD8B200D010 ER8B2009730 8LBW0WMH

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	1027.3	6.6
10°-20°	2893.0	18.6
20°-30°	4224.8	27.2
30°-40°	3799.6	24.5
40°-50°	2078.0	13.4
50°-60°	1030.2	6.6
60°-70°	406.9	2.6
70°-80°	65.6	0.4
80°-90°	10.7	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	8145.1	52.4
0°-40°	11944.8	76.9
0°-60°	15053.0	96.9
0°-90°	15536.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	15536.1	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	10963	
5°	10847	###
15°	10250	2893
25°	9324	4225
35°	6132	3800
45°	2587	2078
55°	1118	1030
65°	407	407
75°	50	66
85°	14	11
90°	0	



TEST NUMBER: P248017

CATALOG NUMBER: LD8B200D010 ER8B2009730 8LBW0WMH

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	10962.9
2.5°	10932.5
5°	10847.2
7.5°	10736.4
10°	10580.5
12.5°	10414.8
15°	10250.1
17.5°	10073.7
20°	9873.7
22.5°	9645.2
25°	9323.6
27.5°	8782.5
30°	8059.9
32.5°	7149.1
35°	6132.4
37.5°	5117.7
40°	4148.1
42.5°	3274.6
45°	2587.3
47.5°	2073.6
50°	1711.8
52.5°	1393.2
55°	1117.7
57.5°	903.0
60°	722.6
62.5°	571.6
65°	406.9
67.5°	242.2
70°	146.1
72.5°	82.4
75°	50.0
77.5°	32.4
80°	23.5
82.5°	7.8
85°	13.7
87.5°	5.9
90°	0.0

(END OF REPORT)