

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P244449

Luminaire Tested: **LD8B30D010 ER8B30827 8LBS0H**

Issue Date: 03/03/2020

Test Information

Test Method: LM-79-08
Report Number: P244449
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1801-521-13)
Test Lab: INNOVATION CENTER(G1)
Issue Date: 03/03/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD8B30D010 ER8B30827 8LBS0H
Description: PORTFOLIO 8 INCH WIDE SHALLOW DISTRIBUTION 75 DEGREE CUTOFF RECESSED
DOWNLIGHT
80 CRI 2700 CCT WITH SEMI-SPECULAR CLEAR TRIM
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3181.0 lumens
Efficiency: N/A
Efficacy: 117.4 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 1.2 / 1.23
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct


Input Watts (W): 27.1
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P244449

CATALOG NUMBER: LD8B30D010 ER8B30827 8LBS0H

Luminous Intensity Polar Plot





TEST NUMBER: P244449

CATALOG NUMBER: LD8B30D010 ER8B30827 8LBSOH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	112	109	106	103	110	107	104	102	103	100	98		99	97	95		95	94	93	91
2	105	99	94	90	103	97	93	89	94	90	87		91	88	85		88	85	83	81
3	98	90	84	79	96	89	83	78	86	81	77		83	79	76		81	78	75	73
4	91	82	75	70	89	81	75	70	79	73	69		76	72	68		74	70	67	65
5	85	75	68	63	83	74	67	62	72	66	62		70	65	61		69	64	60	59
6	80	69	61	56	78	68	61	56	66	60	56		65	59	55		63	58	55	53
7	75	63	56	51	73	63	56	51	61	55	50		60	54	50		59	54	50	48
8	70	58	51	46	68	58	51	46	57	50	46		55	50	46		54	49	45	44
9	66	54	47	42	64	53	47	42	52	46	42		51	46	42		51	45	42	40
10	62	50	43	39	61	50	43	39	49	43	38		48	42	38		47	42	38	37

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	56924
5°	56736
10°	56305
15°	55909
20°	55530
25°	54799
30°	53104
35°	50104
40°	45539
45°	37469
50°	24975
55°	13010
60°	6130
65°	3218
70°	1605
75°	1120
80°	835
85°	672



TEST NUMBER: P244449

CATALOG NUMBER: LD8B30D010 ER8B30827 8LBSOH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	173.9	5.5
10°-20°	494.3	15.5
20°-30°	739.4	23.2
30°-40°	827.0	26.0
40°-50°	648.8	20.4
50°-60°	236.8	7.4
60°-70°	48.3	1.5
70°-80°	10.4	0.3
80°-90°	2.2	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1407.6	44.2
0°-40°	2234.6	70.2
0°-60°	3120.2	98.1
0°-90°	3181.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3181.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1846	
5°	1833	174
15°	1751	494
25°	1611	739
35°	1331	827
45°	859	649
55°	242	237
65°	44	48
75°	9	10
85°	2	2
90°	0	



TEST NUMBER: P244449

CATALOG NUMBER: LD8B30D010 ER8B30827 8LBS0H

CANDELA DISTRIBUTION (FULL):

	0°
0°	1846.0
2.5°	1843.2
5°	1832.9
7.5°	1817.9
10°	1798.2
12.5°	1775.7
15°	1751.3
17.5°	1724.1
20°	1692.2
22.5°	1654.7
25°	1610.6
27.5°	1556.2
30°	1491.4
32.5°	1415.5
35°	1331.0
37.5°	1236.3
40°	1131.3
42.5°	1006.5
45°	859.2
47.5°	693.2
50°	520.6
52.5°	364.9
55°	242.0
57.5°	154.8
60°	99.4
62.5°	65.7
65°	44.1
67.5°	28.1
70°	17.8
72.5°	12.2
75°	9.4
77.5°	6.6
80°	4.7
82.5°	2.8
85°	1.9
87.5°	0.9
90°	0.0

(END OF REPORT)