

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P246471

Luminaire Tested: **LD8B30D010 ER8B30830 8LBS0B**

Issue Date: 03/03/2020

Test Information

Test Method: LM-79-08
Report Number: P246471
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1801-521-17)
Test Lab: INNOVATION CENTER(G1)
Issue Date: 03/03/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD8B30D010 ER8B30830 8LBS0B
Description: PORTFOLIO 8 INCH WIDE SHALLOW DISTRIBUTION 75 DEGREE CUTOFF RECESSED
DOWNLIGHT
80 CRI 3000 CCT WITH SPECULAR BLACK TRIM
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 2711.0 lumens
Efficiency: N/A
Efficacy: 100.0 lumens/watt
Spacing Criteria (0/90/45): 1.2 / 1.2 / 1.25
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct


Input Watts (W): 27.1
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P246471

CATALOG NUMBER: LD8B30D010 ER8B30830 8LBS0B

Luminous Intensity Polar Plot





TEST NUMBER: P246471

CATALOG NUMBER: LD8B30D010 ER8B30830 8LBS0B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	112	109	106	103	110	107	104	102	103	101	99		99	97	96		96	94	93	91
2	105	99	94	90	103	98	93	89	94	90	87		91	88	85		88	86	84	82
3	98	90	84	79	96	89	83	79	86	81	77		84	80	76		81	78	75	73
4	92	82	76	70	90	81	75	70	79	73	69		77	72	68		75	71	67	66
5	86	75	68	63	84	74	68	63	72	66	62		71	65	61		69	64	61	59
6	80	69	62	56	78	68	61	56	67	60	56		65	60	55		64	59	55	53
7	75	63	56	51	73	63	56	51	61	55	51		60	54	50		59	54	50	48
8	70	59	51	46	69	58	51	46	57	50	46		56	50	46		54	49	46	44
9	66	54	47	42	65	54	47	42	53	46	42		52	46	42		51	45	42	40
10	62	50	43	39	61	50	43	39	49	43	39		48	42	38		47	42	38	37

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	48428
5°	48375
10°	48120
15°	47771
20°	47244
25°	46497
30°	45132
35°	43008
40°	39835
45°	33426
50°	22101
55°	10908
60°	4329
65°	1685
70°	261
75°	0
80°	0
85°	0



TEST NUMBER: P246471

CATALOG NUMBER: LD8B30D010 ER8B30830 8LBS0B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	148.3	5.5
10°-20°	421.8	15.6
20°-30°	627.8	23.2
30°-40°	711.1	26.2
40°-50°	574.9	21.2
50°-60°	199.4	7.4
60°-70°	27.3	1.0
70°-80°	0.4	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1198.0	44.2
0°-40°	1909.0	70.4
0°-60°	2683.3	99.0
0°-90°	2711.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2711.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1570	
5°	1563	148
15°	1496	422
25°	1367	628
35°	1142	711
45°	766	575
55°	203	199
65°	23	27
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P246471

CATALOG NUMBER: LD8B30D010 ER8B30830 8LBS0B

CANDELA DISTRIBUTION (FULL):

	0°
0°	1570.5
2.5°	1568.6
5°	1562.8
7.5°	1551.2
10°	1536.8
12.5°	1517.6
15°	1496.4
17.5°	1469.5
20°	1439.7
22.5°	1405.1
25°	1366.6
27.5°	1320.4
30°	1267.5
32.5°	1207.9
35°	1142.5
37.5°	1070.4
40°	989.6
42.5°	890.5
45°	766.5
47.5°	616.5
50°	460.7
52.5°	315.4
55°	202.9
57.5°	120.2
60°	70.2
62.5°	41.4
65°	23.1
67.5°	10.6
70°	2.9
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)