

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P245728

Luminaire Tested: **LD8B40D010 ER8B40950 8LBM0GPH**

Issue Date: 03/03/2020

Test Information

Test Method: LM-79-08
Report Number: P245728
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P201629)
Test Lab: INNOVATION CENTER-P1
Issue Date: 03/03/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD8B40D010 ER8B40950 8LBM0GPH
Description: PORTFOLIO 8 INCH MEDIUM DISTRIBUTION 55 DEG CUTOFF RECESSED
DOWNLIGHT
90 CRI 5000 CCT WITH GRAPHITE TRIM
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3572.0 lumens
Efficiency: N/A
Efficacy: 87.3 lumens/watt
Spacing Criteria (0/90/45): 0.82 / 0.82 / 0.87
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct


Input Watts (W): 40.9
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P245728

CATALOG NUMBER: LD8B40D010 ER8B40950 8LBM0GPH

Luminous Intensity Polar Plot





TEST NUMBER: P245728

CATALOG NUMBER: LD8B40D010 ER8B40950 8LBM0GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	114	111	108	106	111	109	107	105	105	103	101		101	100	98		98	96	95	94
2	108	103	99	96	106	102	98	95	98	95	93		95	93	91		93	91	89	87
3	103	96	92	88	101	95	91	87	92	89	86		90	87	84		88	85	83	81
4	98	90	85	81	96	89	84	80	87	83	79		85	81	78		83	80	77	76
5	93	85	79	75	91	84	78	74	82	77	74		80	76	73		79	75	72	71
6	88	79	73	69	87	79	73	69	77	72	69		76	71	68		74	71	68	66
7	84	75	69	65	82	74	68	64	73	68	64		72	67	64		70	66	63	62
8	80	70	64	60	79	70	64	60	69	64	60		68	63	60		67	63	59	58
9	76	66	61	57	75	66	60	57	65	60	56		64	59	56		63	59	56	55
10	72	63	57	53	71	62	57	53	62	57	53		61	56	53		60	56	53	51

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	139719
5°	136173
10°	122101
15°	108724
20°	99204
25°	90089
30°	73884
35°	48651
40°	24245
45°	9014
50°	2744
55°	312
60°	185
65°	0
70°	126
75°	536
80°	0
85°	495



TEST NUMBER: P245728

CATALOG NUMBER: LD8B40D010 ER8B40950 8LBM0GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	403.4	11.3
10°-20°	959.0	26.8
20°-30°	1194.6	33.4
30°-40°	806.1	22.6
40°-50°	190.5	5.3
50°-60°	13.8	0.4
60°-70°	2.4	0.1
70°-80°	1.7	0.0
80°-90°	0.4	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2557.0	71.6
0°-40°	3363.1	94.2
0°-60°	3567.5	99.9
0°-90°	3572.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3572.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	4531	
5°	4399	403
15°	3406	959
25°	2648	1195
35°	1292	806
45°	207	191
55°	6	14
65°	0	2
75°	4	2
85°	1	0
90°	0	0
95°	0	0
105°	0	0
115°	0	0
125°	0	0
135°	0	0
145°	0	0
155°	0	0
165°	0	0
175°	0	0
180°	0	0



TEST NUMBER: P245728

CATALOG NUMBER: LD8B40D010 ER8B40950 8LBM0GPH

CANDELA DISTRIBUTION (FULL):

0°	
0°	4531.0
2.5°	4523.8
5°	4399.2
7.5°	4174.9
10°	3899.5
12.5°	3637.2
15°	3405.7
17.5°	3206.2
20°	3023.1
22.5°	2845.8
25°	2647.8
27.5°	2390.0
30°	2075.0
32.5°	1694.0
35°	1292.4
37.5°	924.8
40°	602.3
42.5°	360.4
45°	206.7
47.5°	115.8
50°	57.2
52.5°	26.4
55°	5.8
57.5°	1.4
60°	3.0
62.5°	4.5
65°	0.0
67.5°	3.0
70°	1.4
72.5°	1.4
75°	4.5
77.5°	0.0
80°	0.0
82.5°	0.0
85°	1.4
87.5°	0.0
90°	0.0
92.5°	0.0
95°	0.0
97.5°	0.0
100°	0.0
102.5°	0.0
105°	0.0
107.5°	0.0
110°	0.0



TEST NUMBER: P245728

CATALOG NUMBER: LD8B40D010 ER8B40950 8LBM0GPH

CANDELA DISTRIBUTION (continued):

	0°
112.5°	0.0
115°	0.0
117.5°	0.0
120°	0.0
122.5°	0.0
125°	0.0
127.5°	0.0
130°	0.0
132.5°	0.0
135°	0.0
137.5°	0.0
140°	0.0
142.5°	0.0
145°	0.0
147.5°	0.0
150°	0.0
152.5°	0.0
155°	0.0
157.5°	0.0
160°	0.0
162.5°	0.0
165°	0.0
167.5°	0.0
170°	0.0
172.5°	0.0
175°	0.0
177.5°	0.0
180°	0.0

(END OF REPORT)