

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P245315

Luminaire Tested: **LD8B50D010 ER8B50827 8LBS0WH**

Issue Date: 03/03/2020

Test Information

Test Method: LM-79-08
Report Number: P245315
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1801-521-15)
Test Lab: INNOVATION CENTER(G1)
Issue Date: 03/03/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD8B50D010 ER8B50827 8LBS0WH
Description: PORTFOLIO 8 INCH WIDE SHALLOW DISTRIBUTION 75 DEGREE CUTOFF RECESSED
DOWNLIGHT
80 CRI 2700 CCT WITH WHEAT TRIM
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 5769.0 lumens
Efficiency: N/A
Efficacy: 108.8 lumens/watt
Spacing Criteria (0/90/45): 1.27 / 1.27 / 1.23
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct


Input Watts (W): 53
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P245315

CATALOG NUMBER: LD8B50D010 ER8B50827 8LBS0WH

Luminous Intensity Polar Plot





TEST NUMBER: P245315

CATALOG NUMBER: LD8B50D010 ER8B50827 8LBS0WH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	112	109	106	104	110	107	104	102	103	101	99		99	97	96		96	94	93	91
2	105	100	95	91	103	98	93	90	94	91	88		91	88	86		89	86	84	82
3	99	91	85	80	96	89	84	79	87	82	78		84	80	77		82	78	76	74
4	92	83	76	71	90	82	76	71	79	74	70		77	73	69		75	71	68	66
5	86	76	69	64	84	75	68	63	73	67	63		71	66	62		70	65	62	60
6	80	70	63	57	79	69	62	57	67	61	57		66	60	56		64	60	56	54
7	75	64	57	52	74	63	57	52	62	56	51		61	55	51		60	55	51	49
8	71	59	52	47	69	59	52	47	57	51	47		56	51	47		55	50	46	45
9	66	55	48	43	65	54	48	43	53	47	43		52	47	43		51	46	43	41
10	63	51	44	40	61	51	44	40	50	44	39		49	43	39		48	43	39	38

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	100761
5°	101146
10°	102422
15°	104424
20°	105915
25°	106349
30°	103092
35°	94095
40°	81393
45°	64079
50°	41333
55°	20290
60°	8338
65°	3656
70°	1055
75°	393
80°	302
85°	0



TEST NUMBER: P245315

CATALOG NUMBER: LD8B50D010 ER8B50827 8LBS0WH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	312.0	5.4
10°-20°	924.4	16.0
20°-30°	1431.2	24.8
30°-40°	1550.5	26.9
40°-50°	1115.7	19.3
50°-60°	373.3	6.5
60°-70°	56.4	1.0
70°-80°	4.8	0.1
80°-90°	0.7	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2667.6	46.2
0°-40°	4218.1	73.1
0°-60°	5707.1	98.9
0°-90°	5769.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5769.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3268	
5°	3268	312
15°	3271	924
25°	3126	1431
35°	2500	1550
45°	1469	1116
55°	377	373
65°	50	56
75°	3	5
85°	0	1
90°	0	



TEST NUMBER: P245315

CATALOG NUMBER: LD8B50D010 ER8B50827 8LBS0WH

CANDELA DISTRIBUTION (FULL):

0°	
0°	3267.6
2.5°	3267.6
5°	3267.6
7.5°	3269.3
10°	3271.0
12.5°	3274.3
15°	3271.0
17.5°	3257.6
20°	3227.6
22.5°	3182.5
25°	3125.7
27.5°	3035.5
30°	2895.3
32.5°	2711.6
35°	2499.6
37.5°	2270.8
40°	2022.0
42.5°	1754.9
45°	1469.4
47.5°	1160.5
50°	861.6
52.5°	591.1
55°	377.4
57.5°	225.4
60°	135.2
62.5°	81.8
65°	50.1
67.5°	25.0
70°	11.7
72.5°	5.0
75°	3.3
77.5°	3.3
80°	1.7
82.5°	1.7
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)