

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P244805

Luminaire Tested: **LD8B50D010 ER8B50930 8LBN0WMH**

Issue Date: 03/03/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P244805  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P201884)  
Test Lab: INNOVATION CENTER-P1  
Issue Date: 03/03/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LD8B50D010 ER8B50930 8LBN0WMH  
Description: PORTFOLIO 8 INCH NARROW DISTRIBUTION 50 DEGREE CUTOFF RECESSED  
DOWNLIGHT  
97 CRI 3000 CCT WITH WARM HAZE TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 3995.3 lumens  
Efficiency: N/A  
Efficacy: 75.4 lumens/watt  
Spacing Criteria (0/90/45): 0.74 / 0.74 / 0.79  
Luminous Opening: Point Source (0' x 0' x 0')  
CIE Type: Direct


Input Watts (W): 53  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P244805

CATALOG NUMBER: LD8B50D010 ER8B50930 8LBN0WMH

### Luminous Intensity Polar Plot





TEST NUMBER: P244805

CATALOG NUMBER: LD8B50D010 ER8B50930 8LBN0WMH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

|     |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |     |     |     |
|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|--|-----|-----|-----|--|-----|-----|-----|-----|
| RF  | 20  |     |     |     | 20  |     |     |     | 20  |     |     |  | 20  |     |     |  | 20  |     |     |     |
| RC  | 80  |     |     |     | 70  |     |     |     | 50  |     |     |  | 30  |     |     |  | 10  | 0   |     |     |
| RW  | 70  | 50  | 30  | 10  | 70  | 50  | 30  | 10  | 50  | 30  | 10  |  | 50  | 30  | 10  |  | 50  | 30  | 10  | 0   |
| RCR |     |     |     |     |     |     |     |     |     |     |     |  |     |     |     |  |     |     |     |     |
| 0   | 119 | 119 | 119 | 119 | 116 | 116 | 116 | 116 | 111 | 111 | 111 |  | 106 | 106 | 106 |  | 102 | 102 | 102 | 100 |
| 1   | 114 | 111 | 109 | 107 | 111 | 109 | 107 | 105 | 105 | 103 | 102 |  | 101 | 100 | 99  |  | 98  | 97  | 96  | 94  |
| 2   | 108 | 104 | 100 | 97  | 106 | 102 | 99  | 96  | 99  | 96  | 93  |  | 96  | 94  | 91  |  | 93  | 91  | 90  | 88  |
| 3   | 103 | 97  | 92  | 89  | 101 | 96  | 91  | 88  | 93  | 89  | 86  |  | 91  | 88  | 85  |  | 89  | 86  | 84  | 82  |
| 4   | 98  | 91  | 86  | 82  | 97  | 90  | 85  | 81  | 88  | 84  | 80  |  | 86  | 82  | 79  |  | 84  | 81  | 79  | 77  |
| 5   | 94  | 86  | 80  | 76  | 92  | 85  | 80  | 76  | 83  | 78  | 75  |  | 81  | 77  | 74  |  | 80  | 76  | 74  | 72  |
| 6   | 89  | 81  | 75  | 71  | 88  | 80  | 75  | 71  | 79  | 74  | 70  |  | 77  | 73  | 70  |  | 76  | 72  | 69  | 68  |
| 7   | 85  | 76  | 71  | 67  | 84  | 76  | 70  | 66  | 74  | 70  | 66  |  | 73  | 69  | 66  |  | 72  | 68  | 65  | 64  |
| 8   | 81  | 72  | 66  | 63  | 80  | 72  | 66  | 62  | 71  | 66  | 62  |  | 70  | 65  | 62  |  | 69  | 65  | 62  | 60  |
| 9   | 78  | 68  | 63  | 59  | 77  | 68  | 63  | 59  | 67  | 62  | 59  |  | 66  | 62  | 58  |  | 65  | 61  | 58  | 57  |
| 10  | 74  | 65  | 59  | 56  | 73  | 65  | 59  | 56  | 64  | 59  | 56  |  | 63  | 59  | 55  |  | 62  | 58  | 55  | 54  |

**AVERAGE LUMINANCE (cd/sqm):**





TEST NUMBER: P244805

CATALOG NUMBER: LD8B50D010 ER8B50930 8LBN0WMH

**ZONAL LUMENS:**

| Zone      | Lumens | % Fixture |
|-----------|--------|-----------|
| 0°-10°    | 527.8  | 13.2      |
| 10°-20°   | 1213.1 | 30.4      |
| 20°-30°   | 1287.1 | 32.2      |
| 30°-40°   | 734.4  | 18.4      |
| 40°-50°   | 182.0  | 4.6       |
| 50°-60°   | 35.7   | 0.9       |
| 60°-70°   | 10.8   | 0.3       |
| 70°-80°   | 2.4    | 0.1       |
| 80°-90°   | 2.0    | 0.1       |
| 90°-100°  | 0.0    | 0.0       |
| 100°-110° | 0.0    | 0.0       |
| 110°-120° | 0.0    | 0.0       |
| 120°-130° | 0.0    | 0.0       |
| 130°-140° | 0.0    | 0.0       |
| 140°-150° | 0.0    | 0.0       |
| 150°-160° | 0.0    | 0.0       |
| 160°-170° | 0.0    | 0.0       |
| 170°-180° | 0.0    | 0.0       |
| 0°-30°    | 3028.0 | 75.8      |
| 0°-40°    | 3762.4 | 94.2      |
| 0°-60°    | 3980.1 | 99.6      |
| 0°-90°    | 3995.3 | 100.0     |
| 90°-120°  | 0.0    | 0.0       |
| 90°-150°  | 0.0    | 0.0       |
| 90°-180°  | 0.0    | 0.0       |
| 0°-180°   | 3995.3 | 100.0     |

**CANDELA DISTRIBUTION:**

|      | 0°   | Flux |
|------|------|------|
| 0°   | 5818 |      |
| 5°   | 5715 | 528  |
| 15°  | 4354 | 1213 |
| 25°  | 2841 | 1287 |
| 35°  | 1148 | 734  |
| 45°  | 206  | 182  |
| 55°  | 33   | 36   |
| 65°  | 8    | 11   |
| 75°  | 0    | 2    |
| 85°  | 3    | 2    |
| 90°  | 0    | 0    |
| 95°  | 0    | 0    |
| 105° | 0    | 0    |
| 115° | 0    | 0    |
| 125° | 0    | 0    |
| 135° | 0    | 0    |
| 145° | 0    | 0    |
| 155° | 0    | 0    |
| 165° | 0    | 0    |
| 175° | 0    | 0    |
| 180° | 0    | 0    |



TEST NUMBER: P244805

CATALOG NUMBER: LD8B50D010 ER8B50930 8LBN0WMH

**CANDELA DISTRIBUTION (FULL):**

| 0°     |        |
|--------|--------|
| 0°     | 5818.4 |
| 2.5°   | 5815.6 |
| 5°     | 5715.4 |
| 7.5°   | 5495.3 |
| 10°    | 5169.7 |
| 12.5°  | 4776.7 |
| 15°    | 4353.5 |
| 17.5°  | 3950.1 |
| 20°    | 3566.3 |
| 22.5°  | 3197.3 |
| 25°    | 2841.3 |
| 27.5°  | 2458.9 |
| 30°    | 2037.0 |
| 32.5°  | 1583.4 |
| 35°    | 1148.4 |
| 37.5°  | 791.1  |
| 40°    | 511.5  |
| 42.5°  | 324.3  |
| 45°    | 205.7  |
| 47.5°  | 134.5  |
| 50°    | 84.4   |
| 52.5°  | 51.3   |
| 55°    | 33.1   |
| 57.5°  | 26.5   |
| 60°    | 17.2   |
| 62.5°  | 15.8   |
| 65°    | 8.0    |
| 67.5°  | 8.0    |
| 70°    | 6.6    |
| 72.5°  | 3.9    |
| 75°    | 0.0    |
| 77.5°  | 1.3    |
| 80°    | 1.3    |
| 82.5°  | 2.7    |
| 85°    | 2.7    |
| 87.5°  | 1.3    |
| 90°    | 0.0    |
| 92.5°  | 0.0    |
| 95°    | 0.0    |
| 97.5°  | 0.0    |
| 100°   | 0.0    |
| 102.5° | 0.0    |
| 105°   | 0.0    |
| 107.5° | 0.0    |
| 110°   | 0.0    |



TEST NUMBER: P244805

CATALOG NUMBER: LD8B50D010 ER8B50930 8LBN0WMH

**CANDELA DISTRIBUTION (continued):**

|        | 0°  |
|--------|-----|
| 112.5° | 0.0 |
| 115°   | 0.0 |
| 117.5° | 0.0 |
| 120°   | 0.0 |
| 122.5° | 0.0 |
| 125°   | 0.0 |
| 127.5° | 0.0 |
| 130°   | 0.0 |
| 132.5° | 0.0 |
| 135°   | 0.0 |
| 137.5° | 0.0 |
| 140°   | 0.0 |
| 142.5° | 0.0 |
| 145°   | 0.0 |
| 147.5° | 0.0 |
| 150°   | 0.0 |
| 152.5° | 0.0 |
| 155°   | 0.0 |
| 157.5° | 0.0 |
| 160°   | 0.0 |
| 162.5° | 0.0 |
| 165°   | 0.0 |
| 167.5° | 0.0 |
| 170°   | 0.0 |
| 172.5° | 0.0 |
| 175°   | 0.0 |
| 177.5° | 0.0 |
| 180°   | 0.0 |

(END OF REPORT)