

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P245717

Luminaire Tested: **LD8B50D010 ER8B50935 8LBM0GPH**

Issue Date: 03/03/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P245717  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P201629)  
Test Lab: INNOVATION CENTER-P1  
Issue Date: 03/03/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LD8B50D010 ER8B50935 8LBM0GPH  
Description: PORTFOLIO 8 INCH MEDIUM DISTRIBUTION 55 DEG CUTOFF RECESSED  
DOWNLIGHT  
90 CRI 3500 CCT WITH GRAPHITE TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 4133.1 lumens  
Efficiency: N/A  
Efficacy: 78.0 lumens/watt  
Spacing Criteria (0/90/45): 0.82 / 0.82 / 0.87  
Luminous Opening: Circular (Dia: 0.67' x H: 0')  
CIE Type: Direct


Input Watts (W): 53  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P245717

CATALOG NUMBER: LD8B50D010 ER8B50935 8LBM0GPH

### Luminous Intensity Polar Plot





TEST NUMBER: P245717

CATALOG NUMBER: LD8B50D010 ER8B50935 8LBM0GPH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	114	111	108	106	111	109	107	105	105	103	101		101	100	98		98	96	95	94
2	108	103	99	96	106	102	98	95	98	95	93		95	93	91		93	91	89	87
3	103	96	92	88	101	95	91	87	92	89	86		90	87	84		88	85	83	81
4	98	90	85	81	96	89	84	80	87	83	79		85	81	78		83	80	77	76
5	93	85	79	75	91	84	78	74	82	77	74		80	76	73		79	75	72	71
6	88	79	73	69	87	79	73	69	77	72	69		76	71	68		74	71	68	66
7	84	75	69	65	82	74	68	64	73	68	64		72	67	64		70	66	63	62
8	80	70	64	60	79	70	64	60	69	64	60		68	63	60		67	63	59	58
9	76	66	61	57	75	66	60	57	65	60	56		64	59	56		63	59	56	55
10	72	63	57	53	71	62	57	53	62	57	53		61	56	53		60	56	53	51

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	161662
5°	157559
10°	141277
15°	125800
20°	114785
25°	104240
30°	85488
35°	56289
40°	28049
45°	10431
50°	3176
55°	360
60°	216
65°	0
70°	153
75°	620
80°	0
85°	601



TEST NUMBER: P245717

CATALOG NUMBER: LD8B50D010 ER8B50935 8LBM0GPH

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	466.7	11.3
10°-20°	1109.7	26.8
20°-30°	1382.2	33.4
30°-40°	932.7	22.6
40°-50°	220.4	5.3
50°-60°	16.0	0.4
60°-70°	2.8	0.1
70°-80°	2.0	0.0
80°-90°	0.5	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2958.6	71.6
0°-40°	3891.3	94.2
0°-60°	4127.8	99.9
0°-90°	4133.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4133.1	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	5243	
5°	5090	467
15°	3941	1110
25°	3064	1382
35°	1495	933
45°	239	220
55°	7	16
65°	0	3
75°	5	2
85°	2	0
90°	0	0
95°	0	0
105°	0	0
115°	0	0
125°	0	0
135°	0	0
145°	0	0
155°	0	0
165°	0	0
175°	0	0
180°	0	0



TEST NUMBER: P245717

CATALOG NUMBER: LD8B50D010 ER8B50935 8LBM0GPH

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	5242.6
2.5°	5234.3
5°	5090.1
7.5°	4830.6
10°	4511.9
12.5°	4208.4
15°	3940.6
17.5°	3709.7
20°	3497.9
22.5°	3292.7
25°	3063.7
27.5°	2765.4
30°	2400.9
32.5°	1960.0
35°	1495.3
37.5°	1070.0
40°	696.8
42.5°	417.0
45°	239.2
47.5°	134.0
50°	66.2
52.5°	30.5
55°	6.7
57.5°	1.7
60°	3.5
62.5°	5.2
65°	0.0
67.5°	3.5
70°	1.7
72.5°	1.7
75°	5.2
77.5°	0.0
80°	0.0
82.5°	0.0
85°	1.7
87.5°	0.0
90°	0.0
92.5°	0.0
95°	0.0
97.5°	0.0
100°	0.0
102.5°	0.0
105°	0.0
107.5°	0.0
110°	0.0



TEST NUMBER: P245717

CATALOG NUMBER: LD8B50D010 ER8B50935 8LBM0GPH

**CANDELA DISTRIBUTION (continued):**

	0°
112.5°	0.0
115°	0.0
117.5°	0.0
120°	0.0
122.5°	0.0
125°	0.0
127.5°	0.0
130°	0.0
132.5°	0.0
135°	0.0
137.5°	0.0
140°	0.0
142.5°	0.0
145°	0.0
147.5°	0.0
150°	0.0
152.5°	0.0
155°	0.0
157.5°	0.0
160°	0.0
162.5°	0.0
165°	0.0
167.5°	0.0
170°	0.0
172.5°	0.0
175°	0.0
177.5°	0.0
180°	0.0

(END OF REPORT)