

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P251284

Luminaire Tested: **LD8B60D010 ER8B60827 8LBS0GPH**

Issue Date: 03/03/2020

Test Information

Test Method: LM-79-08
Report Number: P251284
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1801-521-16)
Test Lab: INNOVATION CENTER(G1)
Issue Date: 03/03/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD8B60D010 ER8B60827 8LBS0GPH
Description: PORTFOLIO 8 INCH WIDE SHALLOW DISTRIBUTION 75 DEGREE CUTOFF RECESSED
DOWNLIGHT
80 CRI 2700 CCT WITH GRAPHITE TRIM
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 5796.0 lumens
Efficiency: N/A
Efficacy: 97.4 lumens/watt
Spacing Criteria (0/90/45): 1.19 / 1.19 / 1.25
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct


Input Watts (W): 59.5
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P251284

CATALOG NUMBER: LD8B60D010 ER8B60827 8LBS0GPH

Luminous Intensity Polar Plot





TEST NUMBER: P251284

CATALOG NUMBER: LD8B60D010 ER8B60827 8LBS0GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	112	109	106	103	110	107	104	102	103	100	98		99	97	95		95	94	93	91
2	105	99	94	90	103	97	93	89	94	90	87		91	88	85		88	85	83	81
3	98	90	84	79	96	88	83	78	86	81	77		83	79	76		81	77	74	73
4	91	82	75	70	89	81	74	69	78	73	69		76	72	68		74	70	67	65
5	85	75	68	62	83	74	67	62	72	66	61		70	65	61		68	64	60	58
6	79	69	61	56	78	68	61	56	66	60	55		64	59	55		63	58	54	53
7	74	63	56	50	73	62	55	50	61	55	50		59	54	50		58	53	49	48
8	70	58	51	46	68	57	50	46	56	50	45		55	49	45		54	49	45	43
9	65	54	47	42	64	53	46	42	52	46	41		51	45	41		50	45	41	40
10	62	50	43	38	60	49	43	38	48	42	38		48	42	38		47	42	38	36

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	102589
5°	102279
10°	101269
15°	100229
20°	99181
25°	97557
30°	94888
35°	90564
40°	84203
45°	71096
50°	48270
55°	25220
60°	11317
65°	5523
70°	2218
75°	1346
80°	1012
85°	672



TEST NUMBER: P251284

CATALOG NUMBER: LD8B60D010 ER8B60827 8LBS0GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	313.1	5.4
10°-20°	885.6	15.3
20°-30°	1318.3	22.7
30°-40°	1498.6	25.9
40°-50°	1225.4	21.1
50°-60°	456.8	7.9
60°-70°	83.5	1.4
70°-80°	12.9	0.2
80°-90°	1.8	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2517.0	43.4
0°-40°	4015.6	69.3
0°-60°	5697.8	98.3
0°-90°	5796.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5796.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3327	
5°	3304	313
15°	3140	886
25°	2867	1318
35°	2406	1499
45°	1630	1225
55°	469	457
65°	76	84
75°	11	13
85°	2	2
90°	0	



TEST NUMBER: P251284

CATALOG NUMBER: LD8B60D010 ER8B60827 8LBS0GPH

CANDELA DISTRIBUTION (FULL):

	0°
0°	3326.9
2.5°	3321.2
5°	3304.2
7.5°	3273.9
10°	3234.2
12.5°	3188.8
15°	3139.6
17.5°	3082.9
20°	3022.4
22.5°	2950.5
25°	2867.3
27.5°	2772.7
30°	2664.9
32.5°	2542.0
35°	2405.8
37.5°	2260.2
40°	2091.8
42.5°	1883.8
45°	1630.3
47.5°	1325.8
50°	1006.2
52.5°	709.3
55°	469.1
57.5°	295.1
60°	183.5
62.5°	117.3
65°	75.7
67.5°	43.5
70°	24.6
72.5°	15.1
75°	11.3
77.5°	7.6
80°	5.7
82.5°	1.9
85°	1.9
87.5°	0.0
90°	0.0

(END OF REPORT)