

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P251264

Luminaire Tested: **LD8B60D010 ER8B60830 8LBM0GPH**

Issue Date: 03/03/2020

Test Information

Test Method: LM-79-08
Report Number: P251264
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P201629)
Test Lab: INNOVATION CENTER-P1
Issue Date: 03/03/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD8B60D010 ER8B60830 8LBM0GPH
Description: PORTFOLIO 8 INCH MEDIUM DISTRIBUTION 55 DEG CUTOFF RECESSED
DOWNLIGHT
80 CRI 3000 CCT WITH GRAPHITE TRIM
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 5280.0 lumens
Efficiency: N/A
Efficacy: 88.7 lumens/watt
Spacing Criteria (0/90/45): 0.82 / 0.82 / 0.87
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct


Input Watts (W): 59.5
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P251264

CATALOG NUMBER: LD8B60D010 ER8B60830 8LBM0GPH

Luminous Intensity Polar Plot





TEST NUMBER: P251264

CATALOG NUMBER: LD8B60D010 ER8B60830 8LBM0GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	114	111	108	106	111	109	107	105	105	103	101		101	100	98		98	96	95	94
2	108	103	99	96	106	102	98	95	98	95	93		95	93	91		93	91	89	87
3	103	96	92	88	101	95	91	87	92	89	86		90	87	84		88	85	83	81
4	98	90	85	81	96	89	84	80	87	83	79		85	81	78		83	80	77	76
5	93	85	79	75	91	84	78	74	82	77	74		80	76	73		79	75	72	71
6	88	79	73	69	87	79	73	69	77	72	69		76	71	68		74	71	68	66
7	84	75	69	65	82	74	68	64	73	68	64		72	67	64		70	66	63	62
8	80	70	64	60	79	70	64	60	69	64	60		68	63	60		67	63	59	58
9	76	66	61	57	75	66	60	57	65	60	56		64	59	56		63	59	56	55
10	72	63	57	53	71	62	57	53	62	57	53		61	56	53		60	56	53	51

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	206526
5°	201285
10°	180486
15°	160712
20°	146639
25°	133167
30°	109213
35°	71912
40°	35834
45°	13327
50°	4054
55°	457
60°	278
65°	0
70°	189
75°	786
80°	0
85°	743



TEST NUMBER: P251264

CATALOG NUMBER: LD8B60D010 ER8B60830 8LBM0GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	596.2	11.3
10°-20°	1417.6	26.8
20°-30°	1765.8	33.4
30°-40°	1191.6	22.6
40°-50°	281.6	5.3
50°-60°	20.4	0.4
60°-70°	3.6	0.1
70°-80°	2.6	0.0
80°-90°	0.6	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3779.7	71.6
0°-40°	4971.2	94.2
0°-60°	5273.3	99.9
0°-90°	5280.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5280.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	6698	
5°	6503	596
15°	5034	1418
25°	3914	1766
35°	1910	1192
45°	306	282
55°	8	20
65°	0	4
75°	7	3
85°	2	1
90°	0	0
95°	0	0
105°	0	0
115°	0	0
125°	0	0
135°	0	0
145°	0	0
155°	0	0
165°	0	0
175°	0	0
180°	0	0



TEST NUMBER: P251264

CATALOG NUMBER: LD8B60D010 ER8B60830 8LBM0GPH

CANDELA DISTRIBUTION (FULL):

0°	
0°	6697.5
2.5°	6686.9
5°	6502.7
7.5°	6171.2
10°	5764.1
12.5°	5376.3
15°	5034.2
17.5°	4739.2
20°	4468.6
22.5°	4206.5
25°	3913.9
27.5°	3532.8
30°	3067.2
32.5°	2504.0
35°	1910.3
37.5°	1367.0
40°	890.2
42.5°	532.7
45°	305.6
47.5°	171.2
50°	84.5
52.5°	39.0
55°	8.5
57.5°	2.1
60°	4.5
62.5°	6.6
65°	0.0
67.5°	4.5
70°	2.1
72.5°	2.1
75°	6.6
77.5°	0.0
80°	0.0
82.5°	0.0
85°	2.1
87.5°	0.0
90°	0.0
92.5°	0.0
95°	0.0
97.5°	0.0
100°	0.0
102.5°	0.0
105°	0.0
107.5°	0.0
110°	0.0



TEST NUMBER: P251264

CATALOG NUMBER: LD8B60D010 ER8B60830 8LBM0GPH

CANDELA DISTRIBUTION (continued):

	0°
112.5°	0.0
115°	0.0
117.5°	0.0
120°	0.0
122.5°	0.0
125°	0.0
127.5°	0.0
130°	0.0
132.5°	0.0
135°	0.0
137.5°	0.0
140°	0.0
142.5°	0.0
145°	0.0
147.5°	0.0
150°	0.0
152.5°	0.0
155°	0.0
157.5°	0.0
160°	0.0
162.5°	0.0
165°	0.0
167.5°	0.0
170°	0.0
172.5°	0.0
175°	0.0
177.5°	0.0
180°	0.0

(END OF REPORT)