

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P251230

Luminaire Tested: **LD8B60D010 ER8B60930 8LBW0GPH**

Issue Date: 03/03/2020

Test Information

Test Method: LM-79-08
Report Number: P251230
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1801-521-46)
Test Lab: INNOVATION CENTER(G1)
Issue Date: 03/03/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD8B60D010 ER8B60930 8LBW0GPH
Description: PORTFOLIO 8 INCH WIDE DISTRIBUTION 60 DEGREE CUTOFF RECESSED
DOWNLIGHT
90 CRI 3000 CCT WITH GRAPHITE TRIM
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 5172.3 lumens
Efficiency: N/A
Efficacy: 86.9 lumens/watt
Spacing Criteria (0/90/45): 1.11 / 1.11 / 1.05
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct


Input Watts (W): 59.5
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P251230

CATALOG NUMBER: LD8B60D010 ER8B60930 8LBW0GPH

Luminous Intensity Polar Plot





TEST NUMBER: P251230

CATALOG NUMBER: LD8B60D010 ER8B60930 8LBW0GPH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	113	110	107	104	110	108	105	103	103	101	100		100	98	97		96	95	94	92
2	106	101	96	92	104	99	95	91	96	92	89		93	90	87		90	88	86	84
3	100	93	87	83	98	91	86	82	89	84	81		86	82	79		84	81	78	76
4	94	85	79	74	92	84	78	74	82	77	73		80	76	72		78	74	71	70
5	88	79	72	67	87	78	72	67	76	71	66		74	70	66		73	69	65	64
6	83	73	66	61	82	72	66	61	71	65	61		69	64	60		68	63	60	58
7	78	68	61	56	77	67	61	56	66	60	56		65	59	56		63	59	55	54
8	74	63	56	52	73	63	56	52	61	56	51		60	55	51		59	55	51	49
9	70	59	52	48	69	58	52	48	57	52	48		57	51	47		56	51	47	46
10	66	55	49	44	65	55	49	44	54	48	44		53	48	44		52	47	44	43

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	124190
5°	121253
10°	117454
15°	115757
20°	114394
25°	111936
30°	104840
35°	85610
40°	51106
45°	30696
50°	22125
55°	15053
60°	9442
65°	4626
70°	1181
75°	441
80°	337
85°	0



TEST NUMBER: P251230

CATALOG NUMBER: LD8B60D010 ER8B60930 8LBW0GPH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	368.5	7.1
10°-20°	1023.3	19.8
20°-30°	1502.7	29.1
30°-40°	1362.2	26.3
40°-50°	583.1	11.3
50°-60°	258.0	5.0
60°-70°	68.8	1.3
70°-80°	5.4	0.1
80°-90°	0.3	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2894.5	56.0
0°-40°	4256.7	82.3
0°-60°	5097.8	98.6
0°-90°	5172.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5172.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	4027	
5°	3917	369
15°	3626	1023
25°	3290	1503
35°	2274	1362
45°	704	583
55°	280	258
65°	63	69
75°	4	5
85°	0	0
90°	0	



TEST NUMBER: P251230

CATALOG NUMBER: LD8B60D010 ER8B60930 8LBW0GPH

CANDELA DISTRIBUTION (FULL):

	0°
0°	4027.4
2.5°	3995.7
5°	3917.2
7.5°	3827.7
10°	3751.1
12.5°	3687.6
15°	3626.0
17.5°	3560.6
20°	3486.0
22.5°	3398.2
25°	3289.9
27.5°	3144.3
30°	2944.4
32.5°	2664.4
35°	2274.2
37.5°	1762.5
40°	1269.6
42.5°	916.8
45°	703.9
47.5°	567.6
50°	461.2
52.5°	366.0
55°	280.0
57.5°	209.1
60°	153.1
62.5°	106.4
65°	63.4
67.5°	28.0
70°	13.1
72.5°	7.5
75°	3.7
77.5°	1.9
80°	1.9
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)