

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P250982

Luminaire Tested: **LD8B60D010 ER8B609730 8LBM0H**

Issue Date: 03/03/2020

Test Information

Test Method: LM-79-08
Report Number: P250982
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P27951)
Test Lab: INNOVATION CENTER-P2
Issue Date: 03/03/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD8B60D010 ER8B609730 8LBM0H
Description: PORTFOLIO 8 INCH MEDIUM DISTRIBUTION 55 DEG CUTOFF RECESSED
DOWNLIGHT
97 CRI 3000 CCT WITH SEMI-SPECULAR CLEAR TRIM
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4528.0 lumens
Efficiency: N/A
Efficacy: 76.1 lumens/watt
Spacing Criteria (0/90/45): 0.91 / 0.91 / 0.93
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 59.5
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P250982

CATALOG NUMBER: LD8B60D010 ER8B609730 8LBM0H

Luminous Intensity Polar Plot





TEST NUMBER: P250982

CATALOG NUMBER: LD8B60D010 ER8B609730 8LBM0H

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	113	110	108	105	111	108	106	104	104	102	100		100	99	97		97	96	95	93
2	107	102	98	94	105	100	96	93	97	94	91		94	91	89		91	89	87	85
3	101	94	89	85	99	93	88	84	90	86	83		88	84	82		86	83	80	79
4	96	88	82	77	94	86	81	77	84	80	76		82	78	75		80	77	74	73
5	90	82	75	71	89	81	75	70	79	74	70		77	73	69		75	72	69	67
6	85	76	70	65	84	75	69	65	74	68	64		72	68	64		71	67	64	62
7	81	71	65	60	80	70	64	60	69	64	60		68	63	59		67	62	59	58
8	77	67	60	56	75	66	60	56	65	59	56		64	59	55		63	58	55	54
9	73	63	56	52	72	62	56	52	61	56	52		60	55	52		59	55	51	50
10	69	59	53	49	68	58	53	49	58	52	48		57	52	48		56	51	48	47

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P250982

CATALOG NUMBER: LD8B60D010 ER8B609730 8LBM0H

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	417.9	9.2
10°-20°	1051.9	23.2
20°-30°	1403.6	31.0
30°-40°	1081.9	23.9
40°-50°	403.4	8.9
50°-60°	131.9	2.9
60°-70°	30.4	0.7
70°-80°	6.1	0.1
80°-90°	0.9	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2873.4	63.5
0°-40°	3955.3	87.4
0°-60°	4490.6	99.2
0°-90°	4528.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4528.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	4745	
5°	4526	418
15°	3742	1052
25°	3090	1404
35°	1760	1082
45°	490	403
55°	138	132
65°	27	30
75°	5	6
85°	1	1
90°	0	



TEST NUMBER: P250982

CATALOG NUMBER: LD8B60D010 ER8B609730 8LBM0H

CANDELA DISTRIBUTION (FULL):

0°	
0°	4744.7
1°	4724.2
2°	4689.6
3°	4645.2
4°	4591.1
5°	4526.2
6°	4452.7
7°	4368.3
8°	4278.5
9°	4185.5
10°	4100.0
11°	4017.8
12°	3941.0
13°	3870.7
14°	3805.7
15°	3741.9
16°	3677.0
17°	3614.3
18°	3549.4
19°	3485.5
20°	3423.9
21°	3360.0
22°	3298.4
23°	3233.5
24°	3165.3
25°	3089.6
26°	3006.3
27°	2914.3
28°	2812.7
29°	2699.1
30°	2574.7
32.5°	2210.1
35°	1760.1
37.5°	1303.6
40°	922.8
42.5°	661.0
45°	490.1
47.5°	368.9
50°	272.6
52.5°	194.7
55°	138.5
57.5°	95.2
60°	62.7
62.5°	41.1
65°	27.0



TEST NUMBER: P250982

CATALOG NUMBER: LD8B60D010 ER8B609730 8LBM0H

CANDELA DISTRIBUTION (continued):

	0°
67.5°	18.4
70°	11.9
72.5°	7.6
75°	5.4
77.5°	3.2
80°	2.2
82.5°	1.1
85°	1.1
87.5°	0.0
90°	0.0

(END OF REPORT)