

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P250869

Luminaire Tested: **LD8B70D010 ER8B70835 8LBSOLI**

Issue Date: 03/03/2020

Test Information

Test Method: LM-79-08
Report Number: P250869
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1801-521-12)
Test Lab: INNOVATION CENTER(G1)
Issue Date: 03/03/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD8B70D010 ER8B70835 8LBSOLI
Description: PORTFOLIO 8 INCH WIDE SHALLOW DISTRIBUTION 75 DEGREE CUTOFF RECESSED
DOWNLIGHT
80 CRI 3500 CCT WITH SPECULAR CLEAR TRIM
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 8487.0 lumens
Efficiency: N/A
Efficacy: 111.8 lumens/watt
Spacing Criteria (0/90/45): 1.28 / 1.28 / 1.24
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct


Input Watts (W): 75.9
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P250869

CATALOG NUMBER: LD8B70D010 ER8B70835 8LBSOLI

Luminous Intensity Polar Plot





TEST NUMBER: P250869

CATALOG NUMBER: LD8B70D010 ER8B70835 8LBSOLI

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	112	109	106	104	110	107	104	102	103	101	99	99	97	96	96	94	93	91
2	105	99	95	91	103	98	93	90	94	91	88	91	88	86	88	86	84	82
3	98	91	85	80	96	89	84	79	86	82	78	84	80	77	82	78	75	74
4	92	83	76	71	90	82	75	71	79	74	70	77	73	69	75	71	68	66
5	86	76	69	63	84	75	68	63	73	67	63	71	66	62	69	65	61	60
6	80	70	62	57	79	69	62	57	67	61	56	66	60	56	64	59	56	54
7	75	64	57	52	74	63	56	52	62	56	51	61	55	51	59	54	51	49
8	71	59	52	47	69	58	52	47	57	51	47	56	51	46	55	50	46	45
9	66	55	48	43	65	54	48	43	53	47	43	52	47	43	51	46	42	41
10	62	51	44	39	61	50	44	39	50	43	39	49	43	39	48	43	39	37

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	145917
5°	146549
10°	148929
15°	152696
20°	155361
25°	155534
30°	150723
35°	137996
40°	119933
45°	94898
50°	61539
55°	30752
60°	12908
65°	5684
70°	1758
75°	870
80°	870
85°	849



TEST NUMBER: P250869

CATALOG NUMBER: LD8B70D010 ER8B70835 8LBSOLI

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	452.6	5.3
10°-20°	1351.6	15.9
20°-30°	2093.8	24.7
30°-40°	2273.9	26.8
40°-50°	1652.4	19.5
50°-60°	561.6	6.6
60°-70°	89.4	1.1
70°-80°	9.6	0.1
80°-90°	2.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3898.1	45.9
0°-40°	6172.0	72.7
0°-60°	8386.0	98.8
0°-90°	8487.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	8487.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	4732	
5°	4734	453
15°	4783	1352
25°	4571	2094
35°	3666	2274
45°	2176	1652
55°	572	562
65°	78	89
75°	7	10
85°	2	2
90°	0	



TEST NUMBER: P250869

CATALOG NUMBER: LD8B70D010 ER8B70835 8LBSOLI

CANDELA DISTRIBUTION (FULL):

	0°
0°	4732.0
2.5°	4732.0
5°	4734.4
7.5°	4741.7
10°	4756.3
12.5°	4773.4
15°	4783.1
17.5°	4773.4
20°	4734.4
22.5°	4663.8
25°	4571.3
27.5°	4432.6
30°	4233.0
32.5°	3967.7
35°	3665.8
37.5°	3337.2
40°	2979.4
42.5°	2592.4
45°	2176.1
47.5°	1728.2
50°	1282.8
52.5°	878.7
55°	572.0
57.5°	348.1
60°	209.3
62.5°	129.0
65°	77.9
67.5°	43.8
70°	19.5
72.5°	12.2
75°	7.3
77.5°	4.9
80°	4.9
82.5°	2.4
85°	2.4
87.5°	0.0
90°	0.0

(END OF REPORT)