

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P251447

Luminaire Tested: **LD8B70D010 ER8B70850 8LBN0MW**

Issue Date: 03/03/2020

Test Information

Test Method: LM-79-08
Report Number: P251447
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P201839)
Test Lab: INNOVATION CENTER-P1
Issue Date: 03/03/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD8B70D010 ER8B70850 8LBN0MW
Description: PORTFOLIO 8 INCH NARROW DISTRIBUTION 50 DEGREE CUTOFF RECESSED
DOWNLIGHT
80 CRI 5000 CCT WITH MATTE WHITE TRIM
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 7023.0 lumens
Efficiency: N/A
Efficacy: 92.5 lumens/watt
Spacing Criteria (0/90/45): 0.79 / 0.79 / 0.85
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct


Input Watts (W): 75.9
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P251447

CATALOG NUMBER: LD8B70D010 ER8B70850 8LBN0MW

Luminous Intensity Polar Plot





TEST NUMBER: P251447

CATALOG NUMBER: LD8B70D010 ER8B70850 8LBN0MW

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	112	109	106	103	109	106	104	101	102	100	98		98	97	95		95	94	92	90
2	105	99	94	90	103	97	93	89	94	90	87		91	88	85		88	86	83	82
3	99	91	85	80	96	89	84	79	87	82	78		84	80	77		82	78	76	74
4	93	84	77	72	91	83	76	72	80	75	71		78	74	70		76	72	69	67
5	87	78	71	66	85	77	70	65	75	69	65		73	68	64		71	67	64	62
6	82	72	65	60	81	71	65	60	70	64	60		68	63	59		67	62	59	57
7	78	67	60	56	76	67	60	55	65	59	55		64	59	55		63	58	54	53
8	74	63	56	52	72	62	56	51	61	55	51		60	55	51		59	54	51	49
9	70	59	53	48	69	59	52	48	58	52	48		57	51	48		56	51	47	46
10	66	56	49	45	65	55	49	45	54	49	45		54	48	45		53	48	45	43

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	227106
5°	225479
10°	205476
15°	176122
20°	156086
25°	139284
30°	112485
35°	78048
40°	49520
45°	36784
50°	31398
55°	27526
60°	24632
65°	22006
70°	18970
75°	17442
80°	16249
85°	14329



TEST NUMBER: P251447

CATALOG NUMBER: LD8B70D010 ER8B70850 8LBN0MW

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	671.9	9.6
10°-20°	1554.0	22.1
20°-30°	1848.1	26.3
30°-40°	1306.5	18.6
40°-50°	674.3	9.6
50°-60°	462.4	6.6
60°-70°	300.1	4.3
70°-80°	157.4	2.2
80°-90°	48.4	0.7
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	4074.0	58.0
0°-40°	5380.4	76.6
0°-60°	6517.1	92.8
0°-90°	7023.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	7023.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	7365	
5°	7284	672
15°	5517	1554
25°	4094	1848
35°	2073	1306
45°	844	674
55°	512	462
65°	302	300
75°	146	157
85°	40	45
90°	0	3
95°	0	0
105°	0	0
115°	0	0
125°	0	0
135°	0	0
145°	0	0
155°	0	0
165°	0	0
175°	0	0
180°	0	0



TEST NUMBER: P251447

CATALOG NUMBER: LD8B70D010 ER8B70850 8LBN0MW

CANDELA DISTRIBUTION (FULL):

0°	
0°	7364.9
2.5°	7364.9
5°	7284.3
7.5°	7016.5
10°	6562.2
12.5°	6020.3
15°	5516.9
17.5°	5102.6
20°	4756.5
22.5°	4429.2
25°	4093.7
27.5°	3672.7
30°	3159.1
32.5°	2606.6
35°	2073.3
37.5°	1597.4
40°	1230.2
42.5°	989.9
45°	843.5
47.5°	737.2
50°	654.5
52.5°	582.0
55°	512.0
57.5°	450.4
60°	399.4
62.5°	346.1
65°	301.6
67.5°	261.3
70°	210.4
72.5°	180.7
75°	146.4
77.5°	118.8
80°	91.5
82.5°	68.1
85°	40.5
87.5°	23.4
90°	0.0
92.5°	0.0
95°	0.0
97.5°	0.0
100°	0.0
102.5°	0.0
105°	0.0
107.5°	0.0
110°	0.0



TEST NUMBER: P251447

CATALOG NUMBER: LD8B70D010 ER8B70850 8LBN0MW

CANDELA DISTRIBUTION (continued):

	0°
112.5°	0.0
115°	0.0
117.5°	0.0
120°	0.0
122.5°	0.0
125°	0.0
127.5°	0.0
130°	0.0
132.5°	0.0
135°	0.0
137.5°	0.0
140°	0.0
142.5°	0.0
145°	0.0
147.5°	0.0
150°	0.0
152.5°	0.0
155°	0.0
157.5°	0.0
160°	0.0
162.5°	0.0
165°	0.0
167.5°	0.0
170°	0.0
172.5°	0.0
175°	0.0
177.5°	0.0
180°	0.0

(END OF REPORT)