

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P251029

Luminaire Tested: **LD8B70D010 ER8B70927 8LBW0WMH**

Issue Date: 03/03/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P251029  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1801-521-44)  
Test Lab: INNOVATION CENTER(G1)  
Issue Date: 03/03/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LD8B70D010 ER8B70927 8LBW0WMH  
Description: PORTFOLIO 8 INCH WIDE DISTRIBUTION 60 DEGREE CUTOFF RECESSED  
DOWNLIGHT  
97 CRI 2700 CCT WITH WARM HAZE TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 5736.4 lumens  
Efficiency: N/A  
Efficacy: 75.6 lumens/watt  
Spacing Criteria (0/90/45): 1.14 / 1.14 / 1.06  
Luminous Opening: Point Source (0' x 0' x 0')  
CIE Type: Direct


Input Watts (W): 75.9  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P251029

CATALOG NUMBER: LD8B70D010 ER8B70927 8LBW0WMH

### Luminous Intensity Polar Plot





TEST NUMBER: P251029

CATALOG NUMBER: LD8B70D010 ER8B70927 8LBW0WMH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	112	109	106	104	110	107	104	102	103	101	99		99	98	96		96	94	93	91
2	106	100	95	91	103	98	94	90	95	91	88		92	89	86		89	87	84	83
3	99	91	86	81	97	90	85	80	87	83	79		85	81	78		82	79	76	75
4	93	84	77	72	91	83	77	72	80	75	71		78	74	70		76	73	69	68
5	87	77	70	65	85	76	70	65	74	69	64		73	68	64		71	67	63	62
6	82	71	64	59	80	70	64	59	69	63	59		67	62	58		66	61	58	56
7	77	66	59	54	75	65	59	54	64	58	54		63	57	53		61	57	53	51
8	72	61	54	50	71	61	54	50	60	54	49		58	53	49		57	53	49	47
9	68	57	50	46	67	57	50	46	56	50	46		55	49	45		54	49	45	44
10	65	54	47	42	63	53	47	42	52	46	42		51	46	42		51	46	42	41

**AVERAGE LUMINANCE (cd/sqm):**





TEST NUMBER: P251029

CATALOG NUMBER: LD8B70D010 ER8B70927 8LBW0WMH

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	381.7	6.7
10°-20°	1061.9	18.5
20°-30°	1581.7	27.6
30°-40°	1468.9	25.6
40°-50°	693.8	12.1
50°-60°	372.8	6.5
60°-70°	149.7	2.6
70°-80°	23.5	0.4
80°-90°	2.3	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3025.3	52.7
0°-40°	4494.3	78.3
0°-60°	5560.9	96.9
0°-90°	5736.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5736.4	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	4157	
5°	4058	382
15°	3759	1062
25°	3462	1582
35°	2442	1469
45°	846	694
55°	410	373
65°	149	150
75°	19	24
85°	2	2
90°	0	



TEST NUMBER: P251029

CATALOG NUMBER: LD8B70D010 ER8B70927 8LBW0WMH

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	4157.2
2.5°	4128.6
5°	4058.1
7.5°	3968.4
10°	3884.6
12.5°	3816.0
15°	3758.8
17.5°	3699.7
20°	3634.9
22.5°	3560.6
25°	3461.5
27.5°	3322.4
30°	3129.8
32.5°	2847.7
35°	2441.7
37.5°	1923.3
40°	1425.7
42.5°	1061.7
45°	846.3
47.5°	707.2
50°	596.6
52.5°	497.5
55°	409.8
57.5°	333.6
60°	270.7
62.5°	211.6
65°	148.7
67.5°	87.6
70°	51.4
72.5°	30.5
75°	19.0
77.5°	11.5
80°	5.7
82.5°	3.8
85°	1.9
87.5°	0.0
90°	0.0

(END OF REPORT)