

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P251231

Luminaire Tested: **LD8B70D010 ER8B70930 8LBW0GPH**

Issue Date: 03/03/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P251231  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1801-521-46)  
Test Lab: INNOVATION CENTER(G1)  
Issue Date: 03/03/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LD8B70D010 ER8B70930 8LBW0GPH  
Description: PORTFOLIO 8 INCH WIDE DISTRIBUTION 60 DEGREE CUTOFF RECESSED  
DOWNLIGHT  
90 CRI 3000 CCT WITH GRAPHITE TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 6244.0 lumens  
Efficiency: N/A  
Efficacy: 82.3 lumens/watt  
Spacing Criteria (0/90/45): 1.11 / 1.11 / 1.05  
Luminous Opening: Circular (Dia: 0.67' x H: 0')  
CIE Type: Direct


Input Watts (W): 75.9  
Input Voltage (V): NR  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P251231

CATALOG NUMBER: LD8B70D010 ER8B70930 8LBW0GPH

### Luminous Intensity Polar Plot





TEST NUMBER: P251231

CATALOG NUMBER: LD8B70D010 ER8B70930 8LBW0GPH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	113	110	107	104	110	108	105	103	103	101	100	100	98	97	96	95	94	92
2	106	101	96	92	104	99	95	91	96	92	89	93	90	87	90	88	86	84
3	100	93	87	83	98	91	86	82	89	84	81	86	82	79	84	81	78	76
4	94	85	79	74	92	84	78	74	82	77	73	80	76	72	78	74	71	70
5	88	79	72	67	87	78	72	67	76	71	66	74	70	66	73	69	65	64
6	83	73	66	61	82	72	66	61	71	65	61	69	64	60	68	63	60	58
7	78	68	61	56	77	67	61	56	66	60	56	65	59	56	63	59	55	54
8	74	63	56	52	73	63	56	52	61	56	51	60	55	51	59	55	51	49
9	70	59	52	48	69	58	52	48	57	52	48	57	51	47	56	51	47	46
10	66	55	49	44	65	55	49	44	54	48	44	53	48	44	52	47	44	43

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	149923
5°	146379
10°	141790
15°	139741
20°	138093
25°	135130
30°	126568
35°	103345
40°	61697
45°	37055
50°	26706
55°	18177
60°	11403
65°	5596
70°	1425
75°	536
80°	391
85°	0



TEST NUMBER: P251231

CATALOG NUMBER: LD8B70D010 ER8B70930 8LBW0GPH

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	444.9	7.1
10°-20°	1235.3	19.8
20°-30°	1814.0	29.1
30°-40°	1644.5	26.3
40°-50°	704.0	11.3
50°-60°	311.5	5.0
60°-70°	83.1	1.3
70°-80°	6.5	0.1
80°-90°	0.3	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	3494.2	56.0
0°-40°	5138.7	82.3
0°-60°	6154.1	98.6
0°-90°	6244.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6244.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	4862	
5°	4729	445
15°	4377	1235
25°	3972	1814
35°	2745	1644
45°	850	704
55°	338	311
65°	77	83
75°	4	6
85°	0	0
90°	0	



TEST NUMBER: P251231

CATALOG NUMBER: LD8B70D010 ER8B70930 8LBW0GPH

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	4861.9
2.5°	4823.6
5°	4728.9
7.5°	4620.6
10°	4528.3
12.5°	4451.6
15°	4377.3
17.5°	4298.4
20°	4208.2
22.5°	4102.3
25°	3971.6
27.5°	3795.7
30°	3554.6
32.5°	3216.5
35°	2745.3
37.5°	2127.8
40°	1532.7
42.5°	1106.8
45°	849.7
47.5°	685.3
50°	556.7
52.5°	441.8
55°	338.1
57.5°	252.4
60°	184.9
62.5°	128.5
65°	76.7
67.5°	33.9
70°	15.8
72.5°	9.0
75°	4.5
77.5°	2.2
80°	2.2
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)