

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P251413

Luminaire Tested: **LD8B70D010 ER8B70950 8LBS0B**

Issue Date: 03/03/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P251413  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1801-521-17)  
Test Lab: INNOVATION CENTER(G1)  
Issue Date: 03/03/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LD8B70D010 ER8B70950 8LBS0B  
Description: PORTFOLIO 8 INCH WIDE SHALLOW DISTRIBUTION 75 DEGREE CUTOFF RECESSED  
DOWNLIGHT  
90 CRI 5000 CCT WITH SPECULAR BLACK TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 6327.0 lumens  
Efficiency: N/A  
Efficacy: 83.4 lumens/watt  
Spacing Criteria (0/90/45): 1.2 / 1.2 / 1.25  
Luminous Opening: Circular (Dia: 0.67' x H: 0')  
CIE Type: Direct


Input Watts (W): 75.9  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P251413

CATALOG NUMBER: LD8B70D010 ER8B70950 8LBS0B

### Luminous Intensity Polar Plot





TEST NUMBER: P251413

CATALOG NUMBER: LD8B70D010 ER8B70950 8LBS0B

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	112	109	106	103	110	107	104	102	103	101	99		99	97	96		96	94	93	91
2	105	99	94	90	103	98	93	89	94	90	87		91	88	85		88	86	84	82
3	98	90	84	79	96	89	83	79	86	81	77		84	80	76		81	78	75	73
4	92	82	76	70	90	81	75	70	79	73	69		77	72	68		75	71	67	66
5	86	75	68	63	84	74	68	63	72	66	62		71	65	61		69	64	61	59
6	80	69	62	56	78	68	61	56	67	60	56		65	60	55		64	59	55	53
7	75	63	56	51	73	63	56	51	61	55	51		60	54	50		59	54	50	48
8	70	59	51	46	69	58	51	46	57	50	46		56	50	46		54	49	46	44
9	66	54	47	42	65	54	47	42	53	46	42		52	46	42		51	45	42	40
10	62	50	43	39	61	50	43	39	49	43	39		48	42	38		47	42	38	37

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	113021
5°	112899
10°	112307
15°	111492
20°	110259
25°	108516
30°	105332
35°	100374
40°	92971
45°	78008
50°	51576
55°	25461
60°	10102
65°	3933
70°	604
75°	0
80°	0
85°	0



TEST NUMBER: P251413

CATALOG NUMBER: LD8B70D010 ER8B70950 8LBS0B

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	346.1	5.5
10°-20°	984.4	15.6
20°-30°	1465.3	23.2
30°-40°	1659.6	26.2
40°-50°	1341.7	21.2
50°-60°	465.4	7.4
60°-70°	63.6	1.0
70°-80°	0.9	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2795.8	44.2
0°-40°	4455.4	70.4
0°-60°	6262.5	99.0
0°-90°	6327.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6327.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	3665	
5°	3647	346
15°	3492	984
25°	3189	1465
35°	2666	1660
45°	1789	1342
55°	474	465
65°	54	64
75°	0	1
85°	0	0
90°	0	



TEST NUMBER: P251413

CATALOG NUMBER: LD8B70D010 ER8B70950 8LBS0B

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	3665.2
2.5°	3660.7
5°	3647.3
7.5°	3620.3
10°	3586.7
12.5°	3541.8
15°	3492.4
17.5°	3429.5
20°	3360.0
22.5°	3279.2
25°	3189.4
27.5°	3081.7
30°	2958.2
32.5°	2819.1
35°	2666.4
37.5°	2498.1
40°	2309.6
42.5°	2078.4
45°	1788.8
47.5°	1438.7
50°	1075.1
52.5°	736.2
55°	473.6
57.5°	280.6
60°	163.8
62.5°	96.5
65°	53.9
67.5°	24.7
70°	6.7
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)