

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P251385

Luminaire Tested: **LD8B70D010 ER8B709730 8LBM0B**

Issue Date: 03/03/2020

Test Information

Test Method: LM-79-08
Report Number: P251385
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P201569)
Test Lab: INNOVATION CENTER-P1
Issue Date: 03/03/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD8B70D010 ER8B709730 8LBM0B
Description: PORTFOLIO 8 INCH MEDIUM DISTRIBUTION 55 DEG CUTOFF RECESSED
DOWNLIGHT
90 CRI 3000 CCT WITH SPECULAR BLACK TRIM
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 3893.1 lumens
Efficiency: N/A
Efficacy: 51.3 lumens/watt
Spacing Criteria (0/90/45): 0.79 / 0.79 / 0.87
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct


Input Watts (W): 75.9
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P251385

CATALOG NUMBER: LD8B70D010 ER8B709730 8LBM0B

Luminous Intensity Polar Plot





TEST NUMBER: P251385

CATALOG NUMBER: LD8B70D010 ER8B709730 8LBM0B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	114	111	108	106	111	109	107	105	105	103	101		101	100	98		98	97	96	94
2	108	103	99	96	106	102	98	95	98	95	93		95	93	91		93	91	89	87
3	103	96	92	88	101	95	91	87	93	89	86		90	87	84		88	85	83	81
4	98	90	85	81	96	89	84	80	87	83	79		85	81	78		83	80	77	76
5	93	85	79	75	91	84	78	74	82	77	74		80	76	73		79	75	72	71
6	88	79	74	69	87	79	73	69	77	72	69		76	71	68		74	71	68	66
7	84	75	69	65	83	74	68	64	73	68	64		72	67	64		70	66	63	62
8	80	70	64	60	79	70	64	60	69	64	60		68	63	60		67	63	60	58
9	76	66	61	57	75	66	60	57	65	60	56		64	60	56		63	59	56	55
10	72	63	57	53	71	62	57	53	62	57	53		61	56	53		60	56	53	52

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	155730
5°	150966
10°	132218
15°	116746
20°	106958
25°	98517
30°	82002
35°	54464
40°	26495
45°	9568
50°	2902
55°	199
60°	0
65°	131
70°	0
75°	0
80°	320
85°	0



TEST NUMBER: P251385

CATALOG NUMBER: LD8B70D010 ER8B709730 8LBM0B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	443.8	11.4
10°-20°	1031.8	26.5
20°-30°	1305.9	33.5
30°-40°	895.9	23.0
40°-50°	203.7	5.2
50°-60°	10.0	0.3
60°-70°	0.4	0.0
70°-80°	0.7	0.0
80°-90°	0.7	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2781.5	71.4
0°-40°	3677.4	94.5
0°-60°	3891.2	100.0
0°-90°	3893.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3893.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	5050	
5°	4877	444
15°	3657	1032
25°	2896	1306
35°	1447	896
45°	219	204
55°	4	10
65°	2	0
75°	0	1
85°	0	0
90°	0	0
95°	0	0
105°	0	0
115°	0	0
125°	0	0
135°	0	0
145°	0	0
155°	0	0
165°	0	0
175°	0	0
180°	0	0



TEST NUMBER: P251385

CATALOG NUMBER: LD8B70D010 ER8B709730 8LBM0B

CANDELA DISTRIBUTION (FULL):

0°	
0°	5050.2
2.5°	5050.2
5°	4877.1
7.5°	4579.5
10°	4222.6
12.5°	3908.6
15°	3657.0
17.5°	3446.5
20°	3259.4
22.5°	3082.6
25°	2895.5
27.5°	2634.8
30°	2303.0
32.5°	1885.8
35°	1446.8
37.5°	1022.1
40°	658.2
42.5°	387.3
45°	219.4
47.5°	117.7
50°	60.5
52.5°	10.7
55°	3.7
57.5°	1.8
60°	0.0
62.5°	0.0
65°	1.8
67.5°	0.0
70°	0.0
72.5°	1.8
75°	0.0
77.5°	0.0
80°	1.8
82.5°	0.0
85°	0.0
87.5°	1.8
90°	0.0
92.5°	0.0
95°	0.0
97.5°	0.0
100°	0.0
102.5°	0.0
105°	0.0
107.5°	0.0
110°	0.0



TEST NUMBER: P251385

CATALOG NUMBER: LD8B70D010 ER8B709730 8LBM0B

CANDELA DISTRIBUTION (continued):

	0°
112.5°	0.0
115°	0.0
117.5°	0.0
120°	0.0
122.5°	0.0
125°	0.0
127.5°	0.0
130°	0.0
132.5°	0.0
135°	0.0
137.5°	0.0
140°	0.0
142.5°	0.0
145°	0.0
147.5°	0.0
150°	0.0
152.5°	0.0
155°	0.0
157.5°	0.0
160°	0.0
162.5°	0.0
165°	0.0
167.5°	0.0
170°	0.0
172.5°	0.0
175°	0.0
177.5°	0.0
180°	0.0

(END OF REPORT)