

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P250309

Luminaire Tested: **LD8B80D010 ER8B80840 8LBN0GPH**

Issue Date: 03/03/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P250309  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P13948)  
Test Lab: INNOVATION CENTER-P1  
Issue Date: 03/03/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: PORTFOLIO  
Catalog Number: LD8B80D010 ER8B80840 8LBN0GPH  
Description: PORTFOLIO 8 INCH NARROW DISTRIBUTION 50 DEGREE CUTOFF RECESSED  
DOWNLIGHT  
80 CRI 4000 CCT WITH GRAPHITE TRIM  
Light Source: -  
Ballast/Driver: -

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 6740.0 lumens  
Efficiency: N/A  
Efficacy: 90.6 lumens/watt  
Spacing Criteria (0/90/45): 0.69 / 0.69 / 0.77  
Luminous Opening: Circular (Dia: 0.67' x H: 0')  
CIE Type: Direct


Input Watts (W): 74.4  
Input Voltage (V): NR  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P250309

CATALOG NUMBER: LD8B80D010 ER8B80840 8LBN0GPH

### Luminous Intensity Polar Plot





TEST NUMBER: P250309

CATALOG NUMBER: LD8B80D010 ER8B80840 8LBN0GPH

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	114	111	109	107	112	109	107	105	105	104	102		101	100	99		98	97	96	94
2	109	104	101	97	107	103	99	96	99	97	94		96	94	92		94	92	90	89
3	104	98	93	90	102	97	92	89	94	90	88		92	89	86		89	87	85	83
4	99	92	87	83	97	91	86	83	89	85	82		87	84	81		85	82	80	78
5	95	87	82	78	93	86	81	77	84	80	77		83	79	76		81	78	75	74
6	90	82	77	73	89	81	76	72	80	75	72		79	75	71		77	74	71	70
7	86	78	72	68	85	77	72	68	76	71	68		75	71	67		74	70	67	66
8	83	74	68	64	81	73	68	64	72	67	64		71	67	64		70	66	63	62
9	79	70	65	61	78	70	64	61	69	64	61		68	63	60		67	63	60	59
10	76	67	61	58	75	66	61	58	65	61	57		65	60	57		64	60	57	56

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	332104
5°	326795
10°	290350
15°	239514
20°	201719
25°	170138
30°	127390
35°	72092
40°	28508
45°	7653
50°	1468
55°	0
60°	210
65°	0
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P250309

CATALOG NUMBER: LD8B80D010 ER8B80840 8LBN0GPH

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	966.8	14.3
10°-20°	2101.3	31.2
20°-30°	2255.9	33.5
30°-40°	1219.3	18.1
40°-50°	190.2	2.8
50°-60°	5.2	0.1
60°-70°	1.3	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	5324.0	79.0
0°-40°	6543.3	97.1
0°-60°	6738.7	100.0
0°-90°	6740.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6740.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	10770	
5°	10557	967
15°	7503	2101
25°	5000	2256
35°	1915	1219
45°	176	190
55°	0	5
65°	0	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P250309

CATALOG NUMBER: LD8B80D010 ER8B80840 8LBN0GPH

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	10769.9
1°	10790.3
2°	10780.2
3°	10743.2
4°	10672.3
5°	10557.4
6°	10399.3
7°	10186.5
8°	9920.2
9°	9613.7
10°	9272.8
11°	8915.3
12°	8544.4
13°	8173.9
14°	7829.6
15°	7502.6
16°	7202.5
17°	6912.4
18°	6642.7
19°	6390.1
20°	6147.1
21°	5911.0
22°	5688.3
23°	5466.1
24°	5233.4
25°	5000.5
26°	4764.4
27°	4494.8
28°	4197.9
29°	3894.9
30°	3577.7
31°	3237.2
32°	2896.3
33°	2559.3
34°	2218.7
35°	1915.1
37.5°	1224.0
40°	708.2
42.5°	377.8
45°	175.5
47.5°	94.6
50°	30.6
52.5°	3.4
55°	0.0
57.5°	3.4



TEST NUMBER: P250309

CATALOG NUMBER: LD8B80D010 ER8B80840 8LBN0GPH

**CANDELA DISTRIBUTION (continued):**

	0°
60°	3.4
62.5°	0.0
65°	0.0
67.5°	3.4
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)