

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P250610

Luminaire Tested: **LD8B80D010 ER8B80927 8LBM0B**

Issue Date: 03/03/2020

Test Information

Test Method: LM-79-08
Report Number: P250610
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P13928)
Test Lab: INNOVATION CENTER-P1
Issue Date: 03/03/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD8B80D010 ER8B80927 8LBM0B
Description: PORTFOLIO 8 INCH MEDIUM DISTRIBUTION 55 DEG CUTOFF RECESSED
DOWNLIGHT
97 CRI 2700 CCT WITH SPECULAR BLACK TRIM
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 4179.3 lumens
Efficiency: N/A
Efficacy: 56.2 lumens/watt
Spacing Criteria (0/90/45): 0.79 / 0.79 / 0.87
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 74.4
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P250610

CATALOG NUMBER: LD8B80D010 ER8B80927 8LBM0B

Luminous Intensity Polar Plot





TEST NUMBER: P250610

CATALOG NUMBER: LD8B80D010 ER8B80927 8LBM0B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	114	111	108	106	111	109	107	105	105	103	101		101	100	98		98	97	96	94
2	108	103	99	96	106	102	98	95	98	95	93		95	93	91		93	91	89	87
3	103	96	92	88	101	95	91	87	92	89	86		90	87	84		88	85	83	81
4	98	90	85	81	96	89	84	80	87	83	79		85	81	78		83	80	77	76
5	93	85	79	75	91	84	78	74	82	77	74		80	76	73		79	75	72	71
6	88	79	74	69	87	79	73	69	77	72	69		76	71	68		74	71	68	66
7	84	75	69	65	83	74	68	64	73	68	64		72	67	64		70	66	63	62
8	80	70	64	60	79	70	64	60	69	64	60		68	63	60		67	63	60	58
9	76	66	61	57	75	66	60	57	65	60	56		64	60	56		63	59	56	55
10	72	63	57	53	71	62	57	53	62	57	53		61	56	53		60	56	53	51

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P250610

CATALOG NUMBER: LD8B80D010 ER8B80927 8LBM0B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	476.3	11.4
10°-20°	1106.2	26.5
20°-30°	1403.4	33.6
30°-40°	961.4	23.0
40°-50°	219.1	5.2
50°-60°	10.9	0.3
60°-70°	0.5	0.0
70°-80°	0.8	0.0
80°-90°	0.8	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2985.8	71.4
0°-40°	3947.2	94.4
0°-60°	4177.2	99.9
0°-90°	4179.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4179.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	5423	
5°	5237	476
15°	3926	1106
25°	3108	1403
35°	1553	961
45°	236	219
55°	4	11
65°	2	0
75°	0	1
85°	0	1
90°	0	



TEST NUMBER: P250610

CATALOG NUMBER: LD8B80D010 ER8B80927 8LBM0B

CANDELA DISTRIBUTION (FULL):

0°	
0°	5422.8
1°	5451.2
2°	5441.1
3°	5400.7
4°	5331.9
5°	5237.1
6°	5121.9
7°	4988.6
8°	4841.2
9°	4683.6
10°	4534.2
11°	4396.8
12°	4249.5
13°	4142.4
14°	4029.3
15°	3926.2
16°	3833.4
17°	3742.4
18°	3657.6
19°	3574.8
20°	3500.1
21°	3423.4
22°	3344.6
23°	3276.0
24°	3199.2
25°	3108.4
26°	3007.4
27°	2890.2
28°	2764.9
29°	2625.6
30°	2472.1
31°	2298.4
32°	2118.7
33°	1930.8
34°	1738.9
35°	1553.2
37.5°	1096.6
40°	706.8
42.5°	416.0
45°	236.4
47.5°	127.2
50°	64.7
52.5°	12.2
55°	4.0
57.5°	2.0



TEST NUMBER: P250610

CATALOG NUMBER: LD8B80D010 ER8B80927 8LBM0B

CANDELA DISTRIBUTION (continued):

	0°
60°	0.0
62.5°	0.0
65°	2.0
67.5°	0.0
70°	0.0
72.5°	2.0
75°	0.0
77.5°	0.0
80°	2.0
82.5°	0.0
85°	0.0
87.5°	2.0
90°	0.0

(END OF REPORT)