

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P250113

Luminaire Tested: **LD8B80D010 ER8B80930 8LBNOWH**

Issue Date: 03/03/2020

Test Information

Test Method: LM-79-08
Report Number: P250113
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P13946)
Test Lab: INNOVATION CENTER-P1
Issue Date: 03/03/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD8B80D010 ER8B80930 8LBN0WH
Description: PORTFOLIO 8 INCH NARROW DISTRIBUTION 50 DEGREE CUTOFF RECESSED
DOWNLIGHT
97 CRI 3000 CCT WITH WHEAT TRIM
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 6422.1 lumens
Efficiency: N/A
Efficacy: 86.3 lumens/watt
Spacing Criteria (0/90/45): 0.58 / 0.58 / 0.66
Luminous Opening: Point Source (0' x 0' x 0')
CIE Type: Direct


Input Watts (W): 74.4
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P250113

CATALOG NUMBER: LD8B80D010 ER8B80930 8LBN0WH

Luminous Intensity Polar Plot





TEST NUMBER: P250113

CATALOG NUMBER: LD8B80D010 ER8B80930 8LBN0WH

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	114	112	109	107	112	109	107	106	105	104	102		102	100	99		98	97	96	95
2	109	105	101	98	107	103	100	97	100	97	95		97	95	93		94	93	91	89
3	105	99	94	91	103	97	93	90	95	91	89		92	90	87		90	88	86	85
4	100	93	88	85	98	92	88	84	90	86	83		88	85	82		86	84	81	80
5	96	88	83	79	94	87	83	79	86	82	78		84	81	78		83	80	77	76
6	92	84	79	75	90	83	78	74	82	77	74		80	76	74		79	76	73	72
7	88	80	74	71	87	79	74	70	78	73	70		77	73	70		76	72	69	68
8	84	76	71	67	83	75	70	67	74	70	67		73	69	66		72	69	66	65
9	81	72	67	64	80	72	67	64	71	67	63		70	66	63		69	66	63	62
10	78	69	64	61	77	69	64	61	68	63	60		67	63	60		67	63	60	59

AVERAGE LUMINANCE (cd/sqm):





TEST NUMBER: P250113

CATALOG NUMBER: LD8B80D010 ER8B80930 8LBN0WH

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	1127.5	17.6
10°-20°	2184.9	34.0
20°-30°	1967.1	30.6
30°-40°	973.2	15.2
40°-50°	148.0	2.3
50°-60°	6.1	0.1
60°-70°	7.8	0.1
70°-80°	2.9	0.0
80°-90°	4.6	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	5279.5	82.2
0°-40°	6252.7	97.4
0°-60°	6406.8	99.8
0°-90°	6422.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6422.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	12910	
5°	12437	###
15°	7828	2185
25°	4350	1967
35°	1575	973
45°	164	148
55°	2	6
65°	4	8
75°	4	3
85°	7	5
90°	0	



TEST NUMBER: P250113

CATALOG NUMBER: LD8B80D010 ER8B80930 8LBN0WH

CANDELA DISTRIBUTION (FULL):

	0°
0°	12910.2
1°	12883.3
2°	12889.9
3°	12825.0
4°	12706.3
5°	12437.4
6°	12231.2
7°	11904.0
8°	11464.8
9°	11007.5
10°	10456.2
11°	9963.3
12°	9434.4
13°	8849.5
14°	8345.4
15°	7827.6
16°	7386.2
17°	6996.3
18°	6516.7
19°	6164.8
20°	5819.8
21°	5461.2
22°	5199.0
23°	4894.3
24°	4614.1
25°	4349.7
26°	4038.2
27°	3758.2
28°	3507.0
29°	3231.4
30°	2834.8
31°	2610.7
32°	2328.3
33°	2019.0
34°	1783.7
35°	1575.3
37.5°	997.1
40°	450.4
42.5°	307.0
45°	163.6
47.5°	91.8
50°	2.2
52.5°	9.0
55°	2.2
57.5°	13.5



TEST NUMBER: P250113

CATALOG NUMBER: LD8B80D010 ER8B80930 8LBN0WH

CANDELA DISTRIBUTION (continued):

	0°
60°	2.2
62.5°	11.2
65°	4.5
67.5°	11.2
70°	6.7
72.5°	2.2
75°	4.5
77.5°	0.0
80°	2.2
82.5°	9.0
85°	6.7
87.5°	0.0
90°	0.0

(END OF REPORT)