

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for
Cooper Lighting Solutions
(formerly Eaton)

Brand: PORTFOLIO

Report Number: P250387

Luminaire Tested: **LD8B90D010 ER8B90835 8LBN0B**

Issue Date: 03/03/2020

Test Information

Test Method: LM-79-08
Report Number: P250387
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P13948)
Test Lab: INNOVATION CENTER-P1
Issue Date: 03/03/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD8B90D010 ER8B90835 8LBN0B
Description: PORTFOLIO 8 INCH NARROW DISTRIBUTION 50 DEGREE CUTOFF RECESSED
DOWNLIGHT
80 CRI 3500 CCT WITH SPECULAR BLACK TRIM
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 5567.0 lumens
Efficiency: N/A
Efficacy: 64.7 lumens/watt
Spacing Criteria (0/90/45): 0.69 / 0.69 / 0.77
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct


Input Watts (W): 86.1
Input Voltage (V): NR
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P250387

CATALOG NUMBER: LD8B90D010 ER8B90835 8LBN0B

Luminous Intensity Polar Plot





TEST NUMBER: P250387

CATALOG NUMBER: LD8B90D010 ER8B90835 8LBN0B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	114	111	109	107	112	109	107	105	105	104	102		101	100	99		98	97	96	94
2	109	104	101	97	107	103	99	96	99	97	94		96	94	92		94	92	90	89
3	104	98	93	90	102	97	92	89	94	90	88		92	89	86		89	87	85	83
4	99	92	87	83	97	91	86	83	89	85	82		87	84	81		85	82	80	78
5	95	87	82	78	93	86	81	77	84	80	77		83	79	76		81	78	75	74
6	90	82	77	73	89	81	76	72	80	75	72		79	75	71		77	74	71	70
7	86	78	72	68	85	77	72	68	76	71	68		75	71	67		74	70	67	66
8	83	74	68	64	81	73	68	64	72	67	64		71	67	64		70	66	63	62
9	79	70	65	61	78	70	64	61	69	64	61		68	63	60		67	63	60	59
10	76	67	61	58	75	66	61	58	65	61	57		65	60	57		64	60	57	56

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	274304
5°	269923
10°	239819
15°	197830
20°	166613
25°	140530
30°	105221
35°	59546
40°	23545
45°	6323
50°	1209
55°	0
60°	173
65°	0
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P250387

CATALOG NUMBER: LD8B90D010 ER8B90835 8LBN0B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	798.5	14.3
10°-20°	1735.6	31.2
20°-30°	1863.3	33.5
30°-40°	1007.1	18.1
40°-50°	157.1	2.8
50°-60°	4.3	0.1
60°-70°	1.0	0.0
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	4397.5	79.0
0°-40°	5404.5	97.1
0°-60°	5565.9	100.0
0°-90°	5567.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5567.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	8896	
5°	8720	799
15°	6197	1736
25°	4130	1863
35°	1582	1007
45°	145	157
55°	0	4
65°	0	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P250387

CATALOG NUMBER: LD8B90D010 ER8B90835 8LBN0B

CANDELA DISTRIBUTION (FULL):

0°	
0°	8895.5
1°	8912.4
2°	8904.0
3°	8873.5
4°	8815.0
5°	8720.1
6°	8589.4
7°	8413.7
8°	8193.7
9°	7940.6
10°	7659.0
11°	7363.7
12°	7057.4
13°	6751.3
14°	6466.9
15°	6196.9
16°	5949.0
17°	5709.4
18°	5486.6
19°	5278.0
20°	5077.3
21°	4882.3
22°	4698.3
23°	4514.8
24°	4322.6
25°	4130.3
26°	3935.3
27°	3712.6
28°	3467.3
29°	3217.0
30°	2955.1
31°	2673.8
32°	2392.3
33°	2113.9
34°	1832.6
35°	1581.8
37.5°	1011.0
40°	584.9
42.5°	312.0
45°	145.0
47.5°	78.1
50°	25.2
52.5°	2.8
55°	0.0
57.5°	2.8



TEST NUMBER: P250387

CATALOG NUMBER: LD8B90D010 ER8B90835 8LBN0B

CANDELA DISTRIBUTION (continued):

	0°
60°	2.8
62.5°	0.0
65°	0.0
67.5°	2.8
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)