

Scaled data based on original data using
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State
Lighting Products

Test Report Prepared for

Cooper Lighting Solutions

(formerly Eaton)

Brand: PORTFOLIO

Report Number: P246259

Luminaire Tested: **LD8B15D010 ER8B15835 8LBW0B**

Issue Date: 03/03/2020

Test Information

Test Method: LM-79-08
Report Number: P246259
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G1-1801-521-47)
Test Lab: INNOVATION CENTER(G1)
Issue Date: 03/03/2020
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)
Product Line: PORTFOLIO
Catalog Number: LD8B15D010 ER8B15835 8LBW0B
Description: PORTFOLIO 8 INCH WIDE DISTRIBUTION 60 DEGREE CUTOFF RECESSED
DOWNLIGHT
80 CRI 3500 CCT WITH SPECULAR BLACK TRIM
Light Source: -
Ballast/Driver: -

Summary

Lumens per Lamp: N/A
Luminaire Lumens: 993.0 lumens
Efficiency: N/A
Efficacy: 69.0 lumens/watt
Spacing Criteria (0/90/45): 1.08 / 1.08 / 1.02
Luminous Opening: Circular (Dia: 0.67' x H: 0')
CIE Type: Direct


Input Watts (W): 14.4
Input Voltage (V): NR
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: NR
Operation Time: NR
Ambient Temperature (°C): NR
Test Distance: 25 FT



TEST NUMBER: P246259

CATALOG NUMBER: LD8B15D010 ER8B15835 8LBW0B

Luminous Intensity Polar Plot





TEST NUMBER: P246259

CATALOG NUMBER: LD8B15D010 ER8B15835 8LBW0B

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20
RC	80				70				50				30				10
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50
RCR																	
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102
1	113	110	108	106	111	108	106	104	104	102	101		101	99	98		97
2	107	102	98	95	105	101	97	94	97	94	92		94	92	90		92
3	102	95	90	86	100	94	89	85	91	87	84		89	85	82		86
4	96	88	83	78	94	87	82	78	85	80	77		83	79	76		81
5	91	82	76	72	89	81	76	71	80	75	71		78	74	70		76
6	86	77	71	66	85	76	70	66	74	69	65		73	68	65		72
7	82	72	66	61	80	71	65	61	70	64	61		69	64	60		67
8	77	67	61	57	76	67	61	57	66	60	56		65	60	56		64
9	73	63	57	53	72	63	57	53	62	56	52		61	56	52		60
10	70	59	53	49	68	59	53	49	58	53	49		57	52	49		57

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	28002
5°	27295
10°	26571
15°	26076
20°	25396
25°	24497
30°	22479
35°	17234
40°	8200
45°	3122
50°	1526
55°	624
60°	154
65°	36
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P246259

CATALOG NUMBER: LD8B15D010 ER8B15835 8LBW0B

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	83.1	8.4
10°-20°	229.8	23.1
20°-30°	328.2	33.1
30°-40°	272.0	27.4
40°-50°	67.1	6.8
50°-60°	12.1	1.2
60°-70°	0.7	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	641.2	64.6
0°-40°	913.2	92.0
0°-60°	992.4	99.9
0°-90°	993.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	993.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	908	
5°	882	83
15°	817	230
25°	720	328
35°	458	272
45°	72	67
55°	12	12
65°	0	1
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P246259

CATALOG NUMBER: LD8B15D010 ER8B15835 8LBW0B

CANDELA DISTRIBUTION (FULL):

	0°
0°	908.1
2.5°	900.5
5°	881.8
7.5°	863.7
10°	848.6
12.5°	833.9
15°	816.8
17.5°	796.6
20°	773.9
22.5°	748.2
25°	720.0
27.5°	681.7
30°	631.3
32.5°	560.2
35°	457.8
37.5°	330.8
40°	203.7
42.5°	118.5
45°	71.6
47.5°	47.4
50°	31.8
52.5°	20.7
55°	11.6
57.5°	5.5
60°	2.5
62.5°	1.0
65°	0.5
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)