

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P865969

Luminaire Tested: PRLX-2001-M-930-15L-L-U-S-X-X-BRSS-X

Issue Date: 8/20/2024

Test Information

Test Method: LM-79-2019
Report Number: P865969
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2304-993-47)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 8/20/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: Prenalux
Catalog Number: PRLX-2001-M-930-15L-L-U-S-X-X-BRSS-X
Description: PRENTALUX 3D PRINTED PENDANT LED LUMINAIRE, MEDIUM LIGHT ENGINE, FLAT LENS,
TAPERED DRUM WITH BRASS INTERIOR SHADE.
LIGHT LEVEL 2
Light Source: 3000K CCT, 90 CRI LEDS
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1181.3 lumens
Efficiency: N/A
Efficacy: 84.4 lumens/watt
Spacing Criteria (0/90/45): 1.15 / 1.15 / 1.27
Luminous Opening: Circular (Dia: 1.27' x H: 0')
CIE Type: Direct

Input Watts (W): 14
Input Voltage (V): 120
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: 0.333 HR
Operation Time: 3 HR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P865969

CATALOG NUMBER: PRLX-2001-M-930-15L-L-U-S-X-X-BRSS-X

Luminous Intensity Polar Plot





TEST NUMBER: P865969

CATALOG NUMBER: PRLX-2001-M-930-15L-L-U-S-X-X-BRSS-X

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	112	108	105	102	109	106	103	100	102	99	97	98	96	94	94	93	92	90
2	104	97	92	88	101	96	91	87	92	88	85	89	86	83	86	83	81	79
3	96	88	81	76	94	86	80	75	83	78	74	81	76	73	78	75	72	70
4	89	79	72	66	87	78	71	66	76	70	65	74	68	64	71	67	64	62
5	83	72	64	59	81	71	64	58	69	63	58	67	61	57	65	60	57	55
6	77	65	58	52	75	65	57	52	63	56	51	61	56	51	60	55	51	49
7	72	60	52	47	70	59	52	47	58	51	46	56	50	46	55	50	46	44
8	67	55	47	42	66	54	47	42	53	46	42	52	46	42	51	45	41	40
9	63	51	43	38	62	50	43	38	49	42	38	48	42	38	47	42	38	36
10	59	47	40	35	58	46	39	35	45	39	35	45	39	35	44	38	34	33

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	5227
5°	5196
10°	5115
15°	5005
20°	4878
25°	4756
30°	4613
35°	4460
40°	4300
45°	4108
50°	3866
55°	2762
60°	1029
65°	273
70°	268
75°	289
80°	313
85°	312

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 4108 cd/sqm

TEST NUMBER: P865969

CATALOG NUMBER: PRLX-2001-M-930-15L-L-U-S-X-X-BRSS-X

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	57.7	4.9
10°-20°	160.5	13.6
20°-30°	233.7	19.8
30°-40°	269.1	22.8
40°-50°	263.7	22.3
50°-60°	161.9	13.7
60°-70°	22.0	1.9
70°-80°	9.2	0.8
80°-90°	3.5	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	451.9	38.3
0°-40°	721.0	61.0
0°-60°	1146.5	97.1
0°-90°	1181.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1181.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	616	
5°	610	58
15°	570	160
25°	508	234
35°	430	269
45°	342	264
55°	187	162
65°	14	22
75°	9	9
85°	3	3
90°	0	

TEST NUMBER: P865969

CATALOG NUMBER: PRLX-2001-M-930-15L-L-U-S-X-X-BRSS-X

CANDELA DISTRIBUTION (FULL):

	0°
0°	616.0
2.5°	614.8
5°	610.0
7.5°	602.8
10°	593.6
12.5°	582.9
15°	569.7
17.5°	556.1
20°	540.2
22.5°	524.6
25°	507.9
27.5°	489.5
30°	470.8
32.5°	450.8
35°	430.5
37.5°	409.3
40°	388.2
42.5°	365.8
45°	342.3
47.5°	318.4
50°	292.8
52.5°	251.7
55°	186.7
57.5°	116.1
60°	60.6
62.5°	29.5
65°	13.6
67.5°	11.2
70°	10.8
72.5°	10.0
75°	8.8
77.5°	7.6
80°	6.4
82.5°	4.8
85°	3.2
87.5°	1.6
90°	0.0



TEST NUMBER: P865969
 CATALOG NUMBER: PRLX-2001-M-930-15L-L-U-S-X-X-BRSS-X

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	12.57	13.97	12.93	14.28	14.59	12.57	13.97	12.93	14.28	14.59
	3H	12.51	13.74	12.89	14.07	14.43	12.51	13.74	12.89	14.07	14.43
	4H	12.49	13.63	12.89	13.98	14.36	12.49	13.63	12.89	13.98	14.36
	6H	12.48	13.52	12.89	13.89	14.29	12.48	13.52	12.89	13.89	14.29
	8H	12.47	13.46	12.90	13.85	14.25	12.47	13.46	12.90	13.85	14.25
	12H	12.45	13.40	12.88	13.78	14.21	12.45	13.40	12.88	13.78	14.21
4H	2H	12.41	13.55	12.81	13.90	14.28	12.41	13.55	12.81	13.90	14.28
	3H	12.38	13.30	12.79	13.70	14.11	12.38	13.30	12.79	13.70	14.11
	4H	12.38	13.20	12.81	13.62	14.06	12.38	13.20	12.81	13.62	14.06
	6H	12.40	13.11	12.87	13.56	14.02	12.40	13.11	12.87	13.56	14.02
	8H	12.40	13.06	12.87	13.51	13.98	12.40	13.06	12.87	13.51	13.98
	12H	12.40	12.98	12.88	13.47	13.94	12.40	12.98	12.88	13.47	13.94
8H	4H	12.29	12.95	12.76	13.40	13.87	12.29	12.95	12.76	13.40	13.87
	6H	12.33	12.88	12.83	13.37	13.85	12.33	12.88	12.83	13.37	13.85
	8H	12.34	12.84	12.86	13.35	13.84	12.34	12.84	12.86	13.35	13.84
	12H	12.37	12.81	12.88	13.31	13.88	12.37	12.81	12.88	13.31	13.88
12H	4H	12.26	12.84	12.74	13.32	13.80	12.26	12.84	12.74	13.32	13.80
	6H	12.29	12.78	12.81	13.30	13.79	12.29	12.78	12.81	13.30	13.79
	8H	12.33	12.77	12.84	13.27	13.84	12.33	12.77	12.84	13.27	13.84