

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P866144

Luminaire Tested: PRLX-2001-M-940-75L-L-U-S-X-X-BLAK-X

Issue Date: 8/20/2024

Test Information

Test Method: LM-79-2019
Report Number: P866144
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2304-993-49)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 8/20/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: Prenalux
Catalog Number: PRLX-2001-M-940-75L-L-U-S-X-X-BLAK-X
Description: PRENTALUX 3D PRINTED PENDANT LED LUMINAIRE, MEDIUM LIGHT ENGINE, FLAT LENS,
TAPERED DRUM WITH BLACK INTERIOR SHADE.
LIGHT LEVEL 8
Light Source: 4000K CCT, 90 CRI LEDS
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 5949.5 lumens
Efficiency: N/A
Efficacy: 85.4 lumens/watt
Spacing Criteria (0/90/45): 1.16 / 1.16 / 1.27
Luminous Opening: Circular (Dia: 1.27' x H: 0')
CIE Type: Direct

Input Watts (W): 69.7
Input Voltage (V): 120
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: 0.5 HR
Operation Time: 3 HR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P866144

CATALOG NUMBER: PRLX-2001-M-940-75L-L-U-S-X-X-BLAK-X

Luminous Intensity Polar Plot





TEST NUMBER: P866144

CATALOG NUMBER: PRLX-2001-M-940-75L-L-U-S-X-X-BLAK-X

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	112	108	105	103	109	106	103	101	102	100	98	98	97	95	95	93	92	90
2	104	98	93	88	102	96	91	87	93	89	86	90	86	84	87	84	82	80
3	97	88	82	77	95	87	81	76	84	79	75	82	77	74	79	76	73	71
4	90	80	73	67	88	79	72	67	76	71	66	74	69	65	72	68	64	63
5	83	73	65	60	82	72	65	59	70	63	59	68	62	58	66	61	58	56
6	78	66	58	53	76	65	58	53	64	57	52	62	56	52	61	55	52	50
7	72	60	53	47	71	60	52	47	58	52	47	57	51	47	56	50	46	45
8	68	56	48	43	66	55	48	43	54	47	42	52	47	42	51	46	42	40
9	63	51	44	39	62	51	44	39	50	43	39	49	43	38	48	42	38	37
10	59	47	40	35	58	47	40	35	46	40	35	45	39	35	44	39	35	33

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	26541
5°	26440
10°	26096
15°	25623
20°	25055
25°	24445
30°	23766
35°	22984
40°	22120
45°	21146
50°	19878
55°	14023
60°	4423
65°	303
70°	213
75°	213
80°	210
85°	214

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 21146 cd/sqm

TEST NUMBER: P866144

CATALOG NUMBER: PRLX-2001-M-940-75L-L-U-S-X-X-BLAK-X

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	293.9	4.9
10°-20°	821.7	13.8
20°-30°	1201.7	20.2
30°-40°	1387.0	23.3
40°-50°	1357.3	22.8
50°-60°	814.2	13.7
60°-70°	63.5	1.1
70°-80°	7.4	0.1
80°-90°	3.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2317.2	38.9
0°-40°	3704.2	62.3
0°-60°	5875.7	98.8
0°-90°	5949.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5949.5	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3128	
5°	3104	294
15°	2916	822
25°	2611	1202
35°	2219	1387
45°	1762	1357
55°	948	814
65°	15	63
75°	6	7
85°	2	3
90°	0	

TEST NUMBER: P866144

CATALOG NUMBER: PRLX-2001-M-940-75L-L-U-S-X-X-BLAK-X

CANDELA DISTRIBUTION (FULL):

	0°
0°	3127.6
2.5°	3123.3
5°	3103.9
7.5°	3071.6
10°	3028.5
12.5°	2979.0
15°	2916.5
17.5°	2849.8
20°	2774.4
22.5°	2694.7
25°	2610.7
27.5°	2520.2
30°	2425.4
32.5°	2324.2
35°	2218.6
37.5°	2110.9
40°	1996.8
42.5°	1886.9
45°	1762.0
47.5°	1637.1
50°	1505.7
52.5°	1292.4
55°	947.8
57.5°	557.9
60°	260.6
62.5°	103.4
65°	15.1
67.5°	8.6
70°	8.6
72.5°	8.6
75°	6.5
77.5°	6.5
80°	4.3
82.5°	4.3
85°	2.2
87.5°	2.2
90°	0.0



TEST NUMBER: P866144
 CATALOG NUMBER: PRLX-2001-M-940-75L-L-U-S-X-X-BLAK-X

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	17.86	19.23	18.22	19.54	19.86	17.86	19.23	18.22	19.54	19.86
	3H	17.74	18.94	18.11	19.27	19.63	17.74	18.94	18.11	19.27	19.63
	4H	17.67	18.79	18.07	19.14	19.52	17.67	18.79	18.07	19.14	19.52
	6H	17.59	18.62	18.01	18.99	19.38	17.59	18.62	18.01	18.99	19.38
	8H	17.55	18.52	17.98	18.91	19.32	17.55	18.52	17.98	18.91	19.32
	12H	17.51	18.44	17.94	18.82	19.25	17.51	18.44	17.94	18.82	19.25
4H	2H	17.67	18.79	18.07	19.14	19.52	17.67	18.79	18.07	19.14	19.52
	3H	17.55	18.44	17.96	18.85	19.25	17.55	18.44	17.96	18.85	19.25
	4H	17.46	18.26	17.90	18.68	19.12	17.46	18.26	17.90	18.68	19.12
	6H	17.39	18.07	17.85	18.52	18.98	17.39	18.07	17.85	18.52	18.98
	8H	17.33	17.97	17.80	18.42	18.89	17.33	17.97	17.80	18.42	18.89
	12H	17.28	17.85	17.77	18.33	18.81	17.28	17.85	17.77	18.33	18.81
8H	4H	17.33	17.97	17.80	18.41	18.88	17.33	17.97	17.80	18.41	18.88
	6H	17.22	17.75	17.72	18.25	18.73	17.22	17.75	17.72	18.25	18.73
	8H	17.15	17.64	17.68	18.15	18.64	17.15	17.64	17.68	18.15	18.64
	12H	17.10	17.54	17.62	18.03	18.60	17.10	17.54	17.62	18.03	18.60
12H	4H	17.28	17.84	17.76	18.33	18.80	17.28	17.84	17.76	18.33	18.80
	6H	17.15	17.63	17.67	18.15	18.64	17.15	17.63	17.67	18.15	18.64
	8H	17.10	17.54	17.62	18.03	18.60	17.10	17.54	17.62	18.03	18.60