

Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269



Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P865470

Luminaire Tested: PRLX-2001-S-930-15L-G-U-S-X-X-GREY-X

Issue Date: 8/20/2024

**Test Information**

Test Method: LM-79-2019  
Report Number: P865470  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2304-993-5)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 8/20/2024  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: Prenalux  
Catalog Number: PRLX-2001-S-930-15L-G-U-S-X-X-GREY-X  
Description: PRENTALUX 3D PRINTED PENDANT LED LUMINAIRE, SMALL LIGHT ENGINE, GLOBE LENS,  
TAPERED DRUM WITH GRAY INTERIOR SHADE.  
LIGHT LEVEL 3  
Light Source: 3000K CCT, 90 CRI LEDS  
Ballast/Driver: -


**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 519.5 lumens  
Efficiency: N/A  
Efficacy: 33.3 lumens/watt  
Spacing Criteria (0/90/45): 1.37 / 1.37 / 1.55  
Luminous Opening: Circular (Dia: 0.92' x H: 0')  
CIE Type: Direct  
  
Input Watts (W): 15.6  
Input Voltage (V): 120  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: 0.5 HR  
Operation Time: 3 HR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P865470

CATALOG NUMBER: PRLX-2001-S-930-15L-G-U-S-X-X-GREY-X

### Luminous Intensity Polar Plot





TEST NUMBER: P865470

CATALOG NUMBER: PRLX-2001-S-930-15L-G-U-S-X-X-GREY-X

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	107	102	97	93	105	100	95	91	95	92	88		91	88	86		88	85	83	81
2	97	88	80	74	94	86	79	73	82	76	71		79	74	70		76	72	68	66
3	88	76	67	60	85	75	66	60	71	64	59		69	63	58		66	61	56	54
4	80	67	57	50	77	65	57	50	63	55	49		60	54	48		58	52	48	45
5	73	59	50	43	71	58	49	42	56	48	42		54	47	41		52	46	41	39
6	67	53	43	37	65	52	43	37	50	42	36		48	41	36		47	40	35	33
7	62	48	39	32	60	47	38	32	45	37	32		44	37	31		42	36	31	29
8	58	43	34	28	56	43	34	28	41	34	28		40	33	28		39	32	28	26
9	54	40	31	25	52	39	31	25	38	30	25		37	30	25		36	29	25	23
10	50	36	28	23	49	36	28	23	35	28	23		34	27	22		33	27	22	21

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	2334
5°	2341
10°	2360
15°	2371
20°	2392
25°	2420
30°	2465
35°	2535
40°	2638
45°	2768
50°	2895
55°	2949
60°	2942
65°	2918
70°	2856
75°	2804
80°	2790
85°	3032

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 87.5°  
 Luminance: 3926 cd/sqm



TEST NUMBER: P865470

CATALOG NUMBER: PRLX-2001-S-930-15L-G-U-S-X-X-GREY-X

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	13.6	2.6
10°-20°	39.7	7.6
20°-30°	62.1	12.0
30°-40°	79.9	15.4
40°-50°	92.6	17.8
50°-60°	92.3	17.8
60°-70°	74.6	14.4
70°-80°	47.1	9.1
80°-90°	17.5	3.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	115.5	22.2
0°-40°	195.4	37.6
0°-60°	380.3	73.2
0°-90°	519.5	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	519.5	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	143	
5°	143	14
15°	140	40
25°	134	62
35°	127	80
45°	120	93
55°	104	92
65°	76	75
75°	44	47
85°	16	17
90°	0	

TEST NUMBER: P865470

CATALOG NUMBER: PRLX-2001-S-930-15L-G-U-S-X-X-GREY-X

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	143.1
2.5°	143.0
5°	143.0
7.5°	142.8
10°	142.5
12.5°	141.5
15°	140.4
17.5°	139.1
20°	137.8
22.5°	136.1
25°	134.5
27.5°	132.9
30°	130.9
32.5°	129.2
35°	127.3
37.5°	125.7
40°	123.9
42.5°	122.1
45°	120.0
47.5°	117.6
50°	114.1
52.5°	109.5
55°	103.7
57.5°	97.2
60°	90.2
62.5°	83.0
65°	75.6
67.5°	67.8
70°	59.9
72.5°	52.2
75°	44.5
77.5°	36.9
80°	29.7
82.5°	22.7
85°	16.2
87.5°	10.5
90°	0.0

TEST NUMBER: P865470  
 CATALOG NUMBER: PRLX-2001-S-930-15L-G-U-S-X-X-GREY-X

**CIE UGR TABLE:**

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	16.24	17.98	16.61	18.29	18.60	16.24	17.98	16.61	18.29	18.60
	3H	18.26	19.84	18.63	20.16	20.52	18.26	19.84	18.63	20.16	20.52
	4H	19.07	20.57	19.47	20.91	21.29	19.07	20.57	19.47	20.91	21.29
	6H	19.75	21.14	20.16	21.50	21.89	19.75	21.14	20.16	21.50	21.89
	8H	20.01	21.34	20.43	21.73	22.13	20.01	21.34	20.43	21.73	22.13
	12H	20.24	21.52	20.67	21.90	22.33	20.24	21.52	20.67	21.90	22.33
4H	2H	16.95	18.44	17.35	18.79	19.16	16.95	18.44	17.35	18.79	19.16
	3H	19.19	20.46	19.60	20.86	21.25	19.19	20.46	19.60	20.86	21.25
	4H	20.15	21.30	20.58	21.72	22.15	20.15	21.30	20.58	21.72	22.15
	6H	20.98	21.99	21.43	22.43	22.88	20.98	21.99	21.43	22.43	22.88
	8H	21.31	22.26	21.77	22.70	23.16	21.31	22.26	21.77	22.70	23.16
	12H	21.61	22.47	22.09	22.94	23.41	21.61	22.47	22.09	22.94	23.41
8H	4H	20.55	21.50	21.00	21.94	22.40	20.55	21.50	21.00	21.94	22.40
	6H	21.53	22.33	22.02	22.82	23.29	21.53	22.33	22.02	22.82	23.29
	8H	21.97	22.69	22.47	23.19	23.67	21.97	22.69	22.47	23.19	23.67
	12H	22.38	23.02	22.89	23.51	24.07	22.38	23.02	22.89	23.51	24.07
12H	4H	20.61	21.47	21.09	21.94	22.41	20.61	21.47	21.09	21.94	22.41
	6H	21.63	22.35	22.14	22.86	23.34	21.63	22.35	22.14	22.86	23.34
	8H	22.15	22.79	22.65	23.27	23.83	22.15	22.79	22.65	23.27	23.83