

Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269



Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P865512

Luminaire Tested: PRLX-2001-S-935-15L-L-U-S-X-X-BLAK-X

Issue Date: 8/20/2024

**Test Information**

Test Method: LM-79-2019  
Report Number: P865512  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2304-993-18)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 8/20/2024  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: Prenalux  
Catalog Number: PRLX-2001-S-935-15L-L-U-S-X-X-BLAK-X  
Description: PRENTALUX 3D PRINTED PENDANT LED LUMINAIRE, SMALL LIGHT ENGINE, FLAT LENS, TAPERED DRUM WITH BLACK INTERIOR SHADE.  
LIGHT LEVEL 3  
Light Source: 3500K CCT, 90 CRI LEDS  
Ballast/Driver: -


**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 1210.0 lumens  
Efficiency: N/A  
Efficacy: 77.6 lumens/watt  
Spacing Criteria (0/90/45): 1.18 / 1.18 / 1.29  
Luminous Opening: Circular (Dia: 0.92' x H: 0')  
CIE Type: Direct  
  
Input Watts (W): 15.6  
Input Voltage (V): 120  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: 0.5 HR  
Operation Time: 3 HR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P865512

CATALOG NUMBER: PRLX-2001-S-935-15L-L-U-S-X-X-BLAK-X

### Luminous Intensity Polar Plot





TEST NUMBER: P865512

CATALOG NUMBER: PRLX-2001-S-935-15L-L-U-S-X-X-BLAK-X

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	111	108	104	102	109	106	103	100	101	99	97	98	96	94	94	93	91	89
2	103	97	91	87	101	95	90	86	91	87	84	88	85	82	85	83	80	78
3	95	87	80	74	93	85	79	74	82	77	72	80	75	71	77	73	70	68
4	88	78	70	64	86	77	70	64	74	68	63	72	67	62	70	65	62	60
5	82	70	62	56	80	69	62	56	67	61	56	65	60	55	64	59	54	53
6	76	64	56	50	74	63	55	50	61	54	49	59	53	49	58	53	48	47
7	70	58	50	44	69	57	50	44	56	49	44	54	48	44	53	48	43	42
8	66	53	45	40	64	52	45	40	51	44	40	50	44	39	49	43	39	37
9	61	49	41	36	60	48	41	36	47	41	36	46	40	36	45	40	36	34
10	58	45	38	33	56	45	38	33	44	37	33	43	37	33	42	36	32	31

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	9408
5°	9399
10°	9328
15°	9167
20°	8998
25°	8816
30°	8537
35°	8269
40°	7976
45°	7669
50°	7336
55°	6793
60°	4782
65°	1571
70°	129
75°	88
80°	131
85°	262

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 45°  
 Luminance: 7669 cd/sqm

TEST NUMBER: P865512

CATALOG NUMBER: PRLX-2001-S-935-15L-L-U-S-X-X-BLAK-X

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	54.5	4.5
10°-20°	152.9	12.6
20°-30°	224.8	18.6
30°-40°	259.5	21.4
40°-50°	256.5	21.2
50°-60°	205.7	17.0
60°-70°	53.3	4.4
70°-80°	1.6	0.1
80°-90°	1.3	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	432.1	35.7
0°-40°	691.6	57.2
0°-60°	1153.8	95.3
0°-90°	1210.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1210.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	577	
5°	574	54
15°	543	153
25°	490	225
35°	415	259
45°	332	256
55°	239	206
65°	41	53
75°	1	2
85°	1	1
90°	0	

TEST NUMBER: P865512

CATALOG NUMBER: PRLX-2001-S-935-15L-L-U-S-X-X-BLAK-X

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	576.8
2.5°	575.4
5°	574.1
7.5°	570.0
10°	563.2
12.5°	552.4
15°	542.9
17.5°	530.6
20°	518.4
22.5°	503.5
25°	489.9
27.5°	470.9
30°	453.3
32.5°	434.3
35°	415.3
37.5°	394.9
40°	374.6
42.5°	354.2
45°	332.5
47.5°	310.8
50°	289.1
52.5°	266.0
55°	238.9
57.5°	199.5
60°	146.6
62.5°	88.2
65°	40.7
67.5°	14.9
70°	2.7
72.5°	1.4
75°	1.4
77.5°	1.4
80°	1.4
82.5°	1.4
85°	1.4
87.5°	1.4
90°	0.0



TEST NUMBER: P865512

CATALOG NUMBER: PRLX-2001-S-935-15L-L-U-S-X-X-BLAK-X

**CIE UGR TABLE:**

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	18.57	20.02	18.93	20.33	20.64	18.57	20.02	18.93	20.33	20.64
	3H	18.46	19.74	18.84	20.07	20.43	18.46	19.74	18.84	20.07	20.43
	4H	18.40	19.59	18.80	19.94	20.32	18.40	19.59	18.80	19.94	20.32
	6H	18.33	19.42	18.74	19.79	20.18	18.33	19.42	18.74	19.79	20.18
	8H	18.29	19.33	18.72	19.72	20.12	18.29	19.33	18.72	19.72	20.12
	12H	18.26	19.24	18.69	19.63	20.06	18.26	19.24	18.69	19.63	20.06
4H	2H	18.47	19.66	18.87	20.01	20.39	18.47	19.66	18.87	20.01	20.39
	3H	18.37	19.33	18.78	19.73	20.14	18.37	19.33	18.78	19.73	20.14
	4H	18.29	19.15	18.73	19.56	20.01	18.29	19.15	18.73	19.56	20.01
	6H	18.22	18.96	18.69	19.40	19.87	18.22	18.96	18.69	19.40	19.87
	8H	18.17	18.86	18.64	19.30	19.77	18.17	18.86	18.64	19.30	19.77
	12H	18.13	18.74	18.62	19.22	19.70	18.13	18.74	18.62	19.22	19.70
8H	4H	18.17	18.86	18.64	19.30	19.77	18.17	18.86	18.64	19.30	19.77
	6H	18.08	18.64	18.58	19.13	19.61	18.08	18.64	18.58	19.13	19.61
	8H	18.01	18.53	18.53	19.04	19.53	18.01	18.53	18.53	19.04	19.53
	12H	17.97	18.43	18.49	18.92	19.49	17.97	18.43	18.49	18.92	19.49
12H	4H	18.13	18.74	18.61	19.22	19.69	18.13	18.74	18.61	19.22	19.69
	6H	18.01	18.52	18.53	19.04	19.53	18.01	18.52	18.53	19.04	19.53
	8H	17.97	18.43	18.48	18.92	19.49	17.97	18.43	18.48	18.92	19.49