

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P867029

Luminaire Tested: PRLX-2002-L-930-67L-L-X-X-BRSS-X

Issue Date: 8/20/2024

Test Information

Test Method: LM-79-2019
Report Number: P867029
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2304-993-81)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 8/20/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: Pentalux
Catalog Number: PRLX-2002-L-930-67L-L-X-X-BRSS-X
Description: PRENTALUX 3D PRINTED PENDANT LED LUMINAIRE, LARGE LIGHT ENGINE, FLAT LENS, TRUNCATED DOME WITH BRASS INTERIOR SHADE.
LIGHT LEVEL 4
Light Source: 3000K CCT, 90 CRI LEDS
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 5368.7 lumens
Efficiency: N/A
Efficacy: 106.5 lumens/watt
Spacing Criteria (0/90/45): 1.17 / 1.17 / 1.27
Luminous Opening: Circular (Dia: 1.67' x H: 0')
CIE Type: Direct

Input Watts (W): 50.4
Input Voltage (V): 120
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: 0.5 HR
Operation Time: 3 HR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P867029

CATALOG NUMBER: PRLX-2002-L-930-67L-L-X-X-BRSS-X

Luminous Intensity Polar Plot





TEST NUMBER: P867029

CATALOG NUMBER: PRLX-2002-L-930-67L-L-X-X-BRSS-X

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	112	108	105	102	109	106	103	100	102	99	97	98	96	94	94	93	92	90
2	104	97	92	88	101	96	91	87	92	88	85	89	86	83	86	83	81	79
3	96	88	81	76	94	86	80	75	83	78	74	81	77	73	78	75	72	70
4	89	79	72	66	87	78	71	66	76	70	65	74	68	64	72	67	64	62
5	83	72	64	59	81	71	64	58	69	63	58	67	62	57	65	60	57	55
6	77	65	58	52	75	65	57	52	63	56	51	61	56	51	60	55	51	49
7	72	60	52	47	70	59	52	47	58	51	46	56	50	46	55	50	46	44
8	67	55	47	42	66	54	47	42	53	46	42	52	46	42	51	45	41	40
9	63	51	43	38	62	50	43	38	49	43	38	48	42	38	47	42	38	36
10	59	47	40	35	58	46	39	35	46	39	35	45	39	35	44	38	34	33

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	13643
5°	13594
10°	13423
15°	13212
20°	12974
25°	12685
30°	12335
35°	11880
40°	11337
45°	10647
50°	9783
55°	7358
60°	3097
65°	1142
70°	525
75°	574
80°	662
85°	770

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 10647 cd/sqm

TEST NUMBER: P867029

CATALOG NUMBER: PRLX-2002-L-930-67L-L-X-X-BRSS-X

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	259.9	4.8
10°-20°	729.1	13.6
20°-30°	1072.5	20.0
30°-40°	1231.8	22.9
40°-50°	1173.4	21.9
50°-60°	734.8	13.7
60°-70°	121.6	2.3
70°-80°	31.8	0.6
80°-90°	13.8	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2061.5	38.4
0°-40°	3293.3	61.3
0°-60°	5201.5	96.9
0°-90°	5368.7	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	5368.7	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2765	
5°	2745	260
15°	2587	729
25°	2330	1072
35°	1972	1232
45°	1526	1173
55°	855	735
65°	98	122
75°	30	32
85°	14	14
90°	0	

TEST NUMBER: P867029

CATALOG NUMBER: PRLX-2002-L-930-67L-L-X-X-BRSS-X

CANDELA DISTRIBUTION (FULL):

0°	
0°	2765.2
2.5°	2762.3
5°	2744.7
7.5°	2716.8
10°	2679.3
12.5°	2636.6
15°	2586.6
17.5°	2532.0
20°	2471.1
22.5°	2403.5
25°	2330.1
27.5°	2252.2
30°	2165.2
32.5°	2070.8
35°	1972.4
37.5°	1868.9
40°	1760.2
42.5°	1644.8
45°	1525.9
47.5°	1399.1
50°	1274.5
52.5°	1113.0
55°	855.4
57.5°	552.8
60°	313.9
62.5°	178.0
65°	97.8
67.5°	46.1
70°	36.4
72.5°	33.6
75°	30.1
77.5°	26.7
80°	23.3
82.5°	18.8
85°	13.6
87.5°	6.8
90°	0.0



TEST NUMBER: P867029

CATALOG NUMBER: PRLX-2002-L-930-67L-L-X-X-BRSS-X

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	16.30	17.69	16.66	18.00	18.32	16.30	17.69	16.66	18.00	18.32
	3H	16.21	17.44	16.59	17.77	18.13	16.21	17.44	16.59	17.77	18.13
	4H	16.17	17.31	16.57	17.66	18.04	16.17	17.31	16.57	17.66	18.04
	6H	16.13	17.17	16.54	17.54	17.94	16.13	17.17	16.54	17.54	17.94
	8H	16.11	17.10	16.54	17.49	17.89	16.11	17.10	16.54	17.49	17.89
	12H	16.09	17.03	16.52	17.41	17.84	16.09	17.03	16.52	17.41	17.84
4H	2H	16.17	17.31	16.57	17.66	18.04	16.17	17.31	16.57	17.66	18.04
	3H	16.10	17.02	16.51	17.42	17.82	16.10	17.02	16.51	17.42	17.82
	4H	16.06	16.87	16.49	17.29	17.74	16.06	16.87	16.49	17.29	17.74
	6H	16.04	16.74	16.50	17.19	17.65	16.04	16.74	16.50	17.19	17.65
	8H	16.02	16.67	16.49	17.12	17.59	16.02	16.67	16.49	17.12	17.59
	12H	16.00	16.59	16.49	17.07	17.54	16.00	16.59	16.49	17.07	17.54
8H	4H	15.95	16.61	16.42	17.05	17.52	15.95	16.61	16.42	17.05	17.52
	6H	15.93	16.47	16.43	16.97	17.45	15.93	16.47	16.43	16.97	17.45
	8H	15.92	16.41	16.44	16.92	17.41	15.92	16.41	16.44	16.92	17.41
	12H	15.92	16.36	16.44	16.86	17.43	15.92	16.36	16.44	16.86	17.43
12H	4H	15.91	16.49	16.39	16.97	17.45	15.91	16.49	16.39	16.97	17.45
	6H	15.88	16.37	16.40	16.88	17.37	15.88	16.37	16.40	16.88	17.37
	8H	15.89	16.33	16.40	16.83	17.39	15.89	16.33	16.40	16.83	17.39