

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P866214

Luminaire Tested: PRLX-2002-M-930-07L-G-U-S-X-X-GREY-X

Issue Date: 8/20/2024

Test Information

Test Method: LM-79-2019
Report Number: P866214
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2304-993-40)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 8/20/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: Prenalux
Catalog Number: PRLX-2002-M-930-07L-G-U-S-X-X-GREY-X
Description: PRENTALUX 3D PRINTED PENDANT LED LUMINAIRE, MEDIUM LIGHT ENGINE, GLOBE LENS, TRUNCATED DOME WITH GRAY INTERIOR SHADE.
LIGHT LEVEL 1
Light Source: 3000K CCT, 90 CRI LEDS
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 264.6 lumens
Efficiency: N/A
Efficacy: 32.3 lumens/watt
Spacing Criteria (0/90/45): 1.36 / 1.36 / 1.53
Luminous Opening: Circular (Dia: 1.31' x H: 0')
CIE Type: Direct

Input Watts (W): 8.2
Input Voltage (V): 120
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: 0.5 HR
Operation Time: 3 HR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P866214

CATALOG NUMBER: PRLX-2002-M-930-07L-G-U-S-X-X-GREY-X

Luminous Intensity Polar Plot





TEST NUMBER: P866214

CATALOG NUMBER: PRLX-2002-M-930-07L-G-U-S-X-X-GREY-X

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	108	103	99	95	105	101	97	93	97	93	90		93	90	87		89	87	85	83
2	98	89	82	76	95	87	81	75	84	78	73		80	76	72		77	73	70	68
3	89	78	69	62	86	76	68	62	73	66	61		70	64	59		68	63	58	56
4	81	68	59	52	78	67	58	52	64	57	51		62	55	50		60	54	49	47
5	74	61	51	44	72	59	51	44	57	49	44		55	48	43		53	47	43	40
6	68	54	45	38	66	53	44	38	51	44	38		50	43	37		48	42	37	35
7	63	49	40	33	61	48	39	33	47	39	33		45	38	33		44	37	33	31
8	58	44	36	30	57	44	35	30	42	35	29		41	34	29		40	34	29	27
9	55	41	32	26	53	40	32	26	39	31	26		38	31	26		37	31	26	24
10	51	37	29	24	50	37	29	24	36	29	24		35	28	24		34	28	23	22

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	618
5°	621
10°	624
15°	625
20°	628
25°	635
30°	645
35°	663
40°	689
45°	718
50°	736
55°	742
60°	726
65°	700
70°	656
75°	599
80°	527
85°	429

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 55°
 Luminance: 742 cd/sqm

TEST NUMBER: P866214

CATALOG NUMBER: PRLX-2002-M-930-07L-G-U-S-X-X-GREY-X

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	7.4	2.8
10°-20°	21.5	8.1
20°-30°	33.4	12.6
30°-40°	42.9	16.2
40°-50°	49.0	18.5
50°-60°	47.5	18.0
60°-70°	36.7	13.9
70°-80°	20.7	7.8
80°-90°	5.6	2.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	62.3	23.5
0°-40°	105.1	39.7
0°-60°	201.7	76.2
0°-90°	264.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	264.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	78	
5°	78	7
15°	76	21
25°	72	33
35°	68	43
45°	64	49
55°	54	48
65°	37	37
75°	20	21
85°	5	6
90°	0	

TEST NUMBER: P866214

CATALOG NUMBER: PRLX-2002-M-930-07L-G-U-S-X-X-GREY-X

CANDELA DISTRIBUTION (FULL):

	0°
0°	77.7
2.5°	77.7
5°	77.7
7.5°	77.5
10°	77.2
12.5°	76.6
15°	75.9
17.5°	75.1
20°	74.2
22.5°	73.2
25°	72.3
27.5°	71.4
30°	70.2
32.5°	69.3
35°	68.3
37.5°	67.4
40°	66.3
42.5°	65.2
45°	63.8
47.5°	61.8
50°	59.5
52.5°	56.7
55°	53.5
57.5°	49.6
60°	45.6
62.5°	41.5
65°	37.2
67.5°	32.7
70°	28.2
72.5°	23.8
75°	19.5
77.5°	15.2
80°	11.5
82.5°	7.9
85°	4.7
87.5°	2.1
90°	0.0



TEST NUMBER: P866214
 CATALOG NUMBER: PRLX-2002-M-930-07L-G-U-S-X-X-GREY-X

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	11.45	13.16	11.82	13.47	13.78	11.45	13.16	11.82	13.47	13.78
	3H	13.27	14.82	13.65	15.14	15.50	13.27	14.82	13.65	15.14	15.50
	4H	13.93	15.39	14.33	15.74	16.11	13.93	15.39	14.33	15.74	16.11
	6H	14.40	15.75	14.81	16.11	16.50	14.40	15.75	14.81	16.11	16.50
	8H	14.54	15.84	14.97	16.23	16.62	14.54	15.84	14.97	16.23	16.62
	12H	14.64	15.88	15.07	16.26	16.69	14.64	15.88	15.07	16.26	16.69
4H	2H	12.11	13.57	12.51	13.92	14.29	12.11	13.57	12.51	13.92	14.29
	3H	14.14	15.37	14.55	15.76	16.16	14.14	15.37	14.55	15.76	16.16
	4H	14.93	16.04	15.36	16.45	16.88	14.93	16.04	15.36	16.45	16.88
	6H	15.51	16.49	15.97	16.93	17.38	15.51	16.49	15.97	16.93	17.38
	8H	15.71	16.62	16.17	17.06	17.52	15.71	16.62	16.17	17.06	17.52
	12H	15.84	16.67	16.32	17.14	17.61	15.84	16.67	16.32	17.14	17.61
8H	4H	15.24	16.15	15.69	16.59	17.05	15.24	16.15	15.69	16.59	17.05
	6H	15.94	16.70	16.43	17.19	17.66	15.94	16.70	16.43	17.19	17.66
	8H	16.20	16.89	16.71	17.39	17.87	16.20	16.89	16.71	17.39	17.87
	12H	16.41	17.01	16.91	17.50	18.06	16.41	17.01	16.91	17.50	18.06
12H	4H	15.27	16.09	15.75	16.57	17.04	15.27	16.09	15.75	16.57	17.04
	6H	16.00	16.68	16.50	17.18	17.67	16.00	16.68	16.50	17.18	17.67
	8H	16.31	16.92	16.82	17.41	17.96	16.31	16.92	16.82	17.41	17.96