

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P866288

Luminaire Tested: PRLX-2002-M-935-15L-L-U-S-X-X-BLAK-X

Issue Date: 8/20/2024

Test Information

Test Method: LM-79-2019
Report Number: P866288
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2304-993-53)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 8/20/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: Prenalux
Catalog Number: PRLX-2002-M-935-15L-L-U-S-X-X-BLAK-X
Description: PRENATALUX 3D PRINTED PENDANT LED LUMINAIRE, MEDIUM LIGHT ENGINE, FLAT LENS, TRUNCATED DOME WITH BLACK INTERIOR SHADE.
LIGHT LEVEL 2
Light Source: 3500K CCT, 90 CRI LEDS
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1174.3 lumens
Efficiency: N/A
Efficacy: 83.9 lumens/watt
Spacing Criteria (0/90/45): 1.16 / 1.16 / 1.27
Luminous Opening: Circular (Dia: 1.31' x H: 0')
CIE Type: Direct

Input Watts (W): 14
Input Voltage (V): 120
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: 0.5 HR
Operation Time: 3 HR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P866288

CATALOG NUMBER: PRLX-2002-M-935-15L-L-U-S-X-X-BLAK-X

Luminous Intensity Polar Plot





TEST NUMBER: P866288

CATALOG NUMBER: PRLX-2002-M-935-15L-L-U-S-X-X-BLAK-X

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	112	108	105	102	109	106	103	100	102	99	97	98	96	94	95	93	92	90
2	104	97	92	88	101	96	91	87	92	88	85	89	86	83	86	83	81	79
3	96	88	81	76	94	86	80	75	83	78	74	81	76	73	78	75	71	69
4	89	79	72	66	87	78	71	66	75	69	65	73	68	64	71	67	63	61
5	83	71	64	58	81	70	63	58	68	62	57	67	61	57	65	60	56	54
6	77	65	57	51	75	64	57	51	62	56	51	61	55	50	59	54	50	48
7	71	59	51	46	70	58	51	46	57	50	45	56	50	45	54	49	45	43
8	67	54	47	41	65	54	46	41	52	46	41	51	45	41	50	45	41	39
9	62	50	43	37	61	49	42	37	48	42	37	47	41	37	46	41	37	35
10	59	46	39	34	57	46	39	34	45	38	34	44	38	34	43	38	34	32

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	4695
5°	4677
10°	4620
15°	4539
20°	4439
25°	4334
30°	4218
35°	4084
40°	3927
45°	3765
50°	3567
55°	3088
60°	1580
65°	307
70°	28
75°	37
80°	37
85°	37

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 3765 cd/sqm

TEST NUMBER: P866288

CATALOG NUMBER: PRLX-2002-M-935-15L-L-U-S-X-X-BLAK-X

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	55.5	4.7
10°-20°	155.2	13.2
20°-30°	227.2	19.3
30°-40°	262.2	22.3
40°-50°	257.1	21.9
50°-60°	186.8	15.9
60°-70°	28.6	2.4
70°-80°	1.1	0.1
80°-90°	0.5	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	437.9	37.3
0°-40°	700.1	59.6
0°-60°	1144.0	97.4
0°-90°	1174.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1174.3	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	590	
5°	586	55
15°	551	155
25°	494	227
35°	420	262
45°	335	257
55°	223	187
65°	16	29
75°	1	1
85°	0	1
90°	0	

TEST NUMBER: P866288

CATALOG NUMBER: PRLX-2002-M-935-15L-L-U-S-X-X-BLAK-X

CANDELA DISTRIBUTION (FULL):

	0°
0°	590.2
2.5°	589.4
5°	585.7
7.5°	579.6
10°	571.9
12.5°	562.1
15°	551.1
17.5°	538.1
20°	524.3
22.5°	509.2
25°	493.7
27.5°	476.6
30°	459.1
32.5°	438.8
35°	420.5
37.5°	398.1
40°	378.1
42.5°	355.3
45°	334.6
47.5°	309.8
50°	288.2
52.5°	259.3
55°	222.6
57.5°	164.4
60°	99.3
62.5°	47.2
65°	16.3
67.5°	4.1
70°	1.2
72.5°	1.2
75°	1.2
77.5°	0.8
80°	0.8
82.5°	0.8
85°	0.4
87.5°	0.4
90°	0.0



TEST NUMBER: P866288
 CATALOG NUMBER: PRLX-2002-M-935-15L-L-U-S-X-X-BLAK-X

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	14.81	16.22	15.17	16.53	16.85	14.81	16.22	15.17	16.53	16.85
	3H	14.69	15.93	15.07	16.26	16.62	14.69	15.93	15.07	16.26	16.62
	4H	14.62	15.78	15.02	16.13	16.51	14.62	15.78	15.02	16.13	16.51
	6H	14.55	15.61	14.96	15.98	16.37	14.55	15.61	14.96	15.98	16.37
	8H	14.51	15.51	14.94	15.90	16.31	14.51	15.51	14.94	15.90	16.31
	12H	14.47	15.43	14.90	15.81	16.24	14.47	15.43	14.90	15.81	16.24
4H	2H	14.64	15.80	15.05	16.15	16.53	14.64	15.80	15.05	16.15	16.53
	3H	14.53	15.46	14.94	15.86	16.26	14.53	15.46	14.94	15.86	16.26
	4H	14.45	15.27	14.88	15.69	16.13	14.45	15.27	14.88	15.69	16.13
	6H	14.37	15.08	14.83	15.53	15.99	14.37	15.08	14.83	15.53	15.99
	8H	14.32	14.98	14.79	15.43	15.90	14.32	14.98	14.79	15.43	15.90
	12H	14.27	14.86	14.76	15.34	15.81	14.27	14.86	14.76	15.34	15.81
8H	4H	14.32	14.98	14.79	15.42	15.90	14.32	14.98	14.79	15.42	15.90
	6H	14.21	14.76	14.72	15.25	15.74	14.21	14.76	14.72	15.25	15.74
	8H	14.15	14.64	14.67	15.16	15.65	14.15	14.64	14.67	15.16	15.65
	12H	14.10	14.54	14.61	15.04	15.61	14.10	14.54	14.61	15.04	15.61
12H	4H	14.27	14.86	14.76	15.34	15.81	14.27	14.86	14.76	15.34	15.81
	6H	14.15	14.64	14.67	15.16	15.65	14.15	14.64	14.67	15.16	15.65
	8H	14.10	14.54	14.61	15.04	15.61	14.10	14.54	14.61	15.04	15.61