

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P866298

Luminaire Tested: PRLX-2002-M-935-25L-L-U-S-X-X-GREY-X

Issue Date: 8/20/2024

Test Information

Test Method: LM-79-2019
Report Number: P866298
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2304-993-52)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 8/20/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: Pentalux
Catalog Number: PRLX-2002-M-935-25L-L-U-S-X-X-GREY-X
Description: PRENTALUX 3D PRINTED PENDANT LED LUMINAIRE, MEDIUM LIGHT ENGINE, FLAT LENS, TRUNCATED DOME WITH GRAY INTERIOR SHADE.
LIGHT LEVEL 3
Light Source: 3500K CCT, 90 CRI LEDS
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2081.4 lumens
Efficiency: N/A
Efficacy: 95.9 lumens/watt
Spacing Criteria (0/90/45): 1.15 / 1.15 / 1.27
Luminous Opening: Circular (Dia: 1.31' x H: 0')
CIE Type: Direct

Input Watts (W): 21.7
Input Voltage (V): 120
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: 0.5 HR
Operation Time: 3 HR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P866298

CATALOG NUMBER: PRLX-2002-M-935-25L-L-U-S-X-X-GREY-X

Luminous Intensity Polar Plot





TEST NUMBER: P866298

CATALOG NUMBER: PRLX-2002-M-935-25L-L-U-S-X-X-GREY-X

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	111	108	105	102	109	106	103	100	101	99	97	98	96	94	94	93	91	89
2	103	97	91	87	101	95	90	86	92	88	84	89	85	82	86	83	80	78
3	96	87	80	75	93	86	79	74	83	77	73	80	76	72	78	74	71	69
4	89	78	71	65	86	77	70	65	75	69	64	73	67	63	71	66	62	60
5	82	71	63	57	80	70	63	57	68	61	56	66	60	56	64	59	55	53
6	76	64	56	51	74	64	56	51	62	55	50	60	54	50	59	53	49	48
7	71	59	51	45	69	58	51	45	57	50	45	55	49	45	54	48	44	43
8	66	54	46	41	65	53	46	41	52	45	41	51	45	40	50	44	40	38
9	62	50	42	37	61	49	42	37	48	41	37	47	41	37	46	40	36	35
10	58	46	39	34	57	45	38	34	45	38	34	44	38	33	43	37	33	32

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	8268
5°	8235
10°	8122
15°	7956
20°	7771
25°	7563
30°	7341
35°	7096
40°	6827
45°	6549
50°	6205
55°	5466
60°	2915
65°	766
70°	316
75°	353
80°	403
85°	493

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 6549 cd/sqm

TEST NUMBER: P866298

CATALOG NUMBER: PRLX-2002-M-935-25L-L-U-S-X-X-GREY-X

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	97.6	4.7
10°-20°	272.1	13.1
20°-30°	396.7	19.1
30°-40°	456.5	21.9
40°-50°	448.0	21.5
50°-60°	331.8	15.9
60°-70°	61.2	2.9
70°-80°	12.1	0.6
80°-90°	5.4	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	766.3	36.8
0°-40°	1222.9	58.8
0°-60°	2002.6	96.2
0°-90°	2081.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2081.4	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1039	
5°	1031	98
15°	966	272
25°	862	397
35°	731	457
45°	582	448
55°	394	332
65°	41	61
75°	12	12
85°	5	5
90°	0	

TEST NUMBER: P866298

CATALOG NUMBER: PRLX-2002-M-935-25L-L-U-S-X-X-GREY-X

CANDELA DISTRIBUTION (FULL):

	0°
0°	1039.3
2.5°	1037.9
5°	1031.2
7.5°	1020.3
10°	1005.4
12.5°	987.1
15°	966.0
17.5°	942.3
20°	917.9
22.5°	890.7
25°	861.6
27.5°	831.0
30°	799.1
32.5°	765.2
35°	730.6
37.5°	694.0
40°	657.4
42.5°	619.4
45°	582.1
47.5°	541.4
50°	501.3
52.5°	457.2
55°	394.1
57.5°	297.8
60°	183.2
62.5°	94.3
65°	40.7
67.5°	17.6
70°	13.6
72.5°	12.9
75°	11.5
77.5°	10.2
80°	8.8
82.5°	7.5
85°	5.4
87.5°	2.7
90°	0.0



TEST NUMBER: P866298
 CATALOG NUMBER: PRLX-2002-M-935-25L-L-U-S-X-X-GREY-X

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	16.93	18.36	17.30	18.67	18.99	16.93	18.36	17.30	18.67	18.99
	3H	16.83	18.09	17.21	18.42	18.78	16.83	18.09	17.21	18.42	18.78
	4H	16.78	17.95	17.18	18.30	18.68	16.78	17.95	17.18	18.30	18.68
	6H	16.73	17.80	17.14	18.17	18.56	16.73	17.80	17.14	18.17	18.56
	8H	16.70	17.71	17.12	18.10	18.51	16.70	17.71	17.12	18.10	18.51
	12H	16.67	17.64	17.10	18.02	18.45	16.67	17.64	17.10	18.02	18.45
4H	2H	16.79	17.96	17.19	18.31	18.69	16.79	17.96	17.19	18.31	18.69
	3H	16.70	17.64	17.11	18.04	18.45	16.70	17.64	17.11	18.04	18.45
	4H	16.64	17.48	17.07	17.90	18.34	16.64	17.48	17.07	17.90	18.34
	6H	16.59	17.32	17.06	17.76	18.23	16.59	17.32	17.06	17.76	18.23
	8H	16.56	17.23	17.03	17.68	18.15	16.56	17.23	17.03	17.68	18.15
	12H	16.53	17.13	17.02	17.61	18.09	16.53	17.13	17.02	17.61	18.09
8H	4H	16.52	17.20	16.99	17.64	18.11	16.52	17.20	16.99	17.64	18.11
	6H	16.46	17.02	16.96	17.52	18.00	16.46	17.02	16.96	17.52	18.00
	8H	16.43	16.93	16.95	17.45	17.94	16.43	16.93	16.95	17.45	17.94
	12H	16.41	16.87	16.92	17.36	17.93	16.41	16.87	16.92	17.36	17.93
12H	4H	16.48	17.08	16.97	17.56	18.04	16.48	17.08	16.97	17.56	18.04
	6H	16.41	16.91	16.92	17.43	17.92	16.41	16.91	16.92	17.43	17.92
	8H	16.39	16.85	16.90	17.34	17.91	16.39	16.85	16.90	17.34	17.91