

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P866345

Luminaire Tested: PRLX-2002-M-940-07L-L-U-S-X-X-BRSS-X

Issue Date: 8/20/2024

Test Information

Test Method: LM-79-2019
Report Number: P866345
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2304-993-51)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 8/20/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: Prenalux
Catalog Number: PRLX-2002-M-940-07L-L-U-S-X-X-BRSS-X
Description: PRENTALUX 3D PRINTED PENDANT LED LUMINAIRE, MEDIUM LIGHT ENGINE, FLAT LENS, TRUNCATED DOME WITH BRASS INTERIOR SHADE.
LIGHT LEVEL 1
Light Source: 4000K CCT, 90 CRI LEDS
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 622.1 lumens
Efficiency: N/A
Efficacy: 75.9 lumens/watt
Spacing Criteria (0/90/45): 1.16 / 1.16 / 1.27
Luminous Opening: Circular (Dia: 1.31' x H: 0')
CIE Type: Direct

Input Watts (W): 8.2
Input Voltage (V): 120
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: 0.5 HR
Operation Time: 3 HR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P866345

CATALOG NUMBER: PRLX-2002-M-940-07L-L-U-S-X-X-BRSS-X

Luminous Intensity Polar Plot





TEST NUMBER: P866345

CATALOG NUMBER: PRLX-2002-M-940-07L-L-U-S-X-X-BRSS-X

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	111	108	105	102	109	106	103	100	101	99	97	98	96	94	94	93	91	89
2	103	97	91	87	101	95	90	86	92	88	84	89	85	82	86	83	80	78
3	96	87	80	75	93	86	79	74	83	77	73	80	76	72	78	74	71	69
4	89	78	71	65	86	77	70	65	75	69	64	73	67	63	71	66	62	60
5	82	71	63	57	80	70	62	57	68	61	56	66	60	56	64	59	55	53
6	76	64	56	51	74	63	56	51	62	55	50	60	54	50	59	53	49	48
7	71	59	51	45	69	58	51	45	57	50	45	55	49	45	54	48	44	43
8	66	54	46	41	65	53	46	41	52	45	40	51	45	40	50	44	40	38
9	62	50	42	37	61	49	42	37	48	41	37	47	41	37	46	40	36	35
10	58	46	39	34	57	45	38	34	44	38	34	44	38	33	43	37	33	32

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	2465
5°	2455
10°	2421
15°	2375
20°	2319
25°	2259
30°	2195
35°	2121
40°	2043
45°	1955
50°	1854
55°	1598
60°	881
65°	248
70°	100
75°	105
80°	119
85°	146

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 1955 cd/sqm

TEST NUMBER: P866345

CATALOG NUMBER: PRLX-2002-M-940-07L-L-U-S-X-X-BRSS-X

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	29.1	4.7
10°-20°	81.2	13.1
20°-30°	118.5	19.0
30°-40°	136.5	21.9
40°-50°	134.0	21.5
50°-60°	98.3	15.8
60°-70°	19.3	3.1
70°-80°	3.6	0.6
80°-90°	1.6	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	228.7	36.8
0°-40°	365.3	58.7
0°-60°	597.6	96.1
0°-90°	622.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	622.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	310	
5°	307	29
15°	288	81
25°	257	118
35°	218	137
45°	174	134
55°	115	98
65°	13	19
75°	3	4
85°	2	2
90°	0	

TEST NUMBER: P866345

CATALOG NUMBER: PRLX-2002-M-940-07L-L-U-S-X-X-BRSS-X

CANDELA DISTRIBUTION (FULL):

0°	
0°	309.8
2.5°	309.4
5°	307.4
7.5°	303.9
10°	299.7
12.5°	294.6
15°	288.3
17.5°	281.2
20°	273.9
22.5°	265.8
25°	257.3
27.5°	248.4
30°	238.9
32.5°	228.7
35°	218.4
37.5°	207.6
40°	196.7
42.5°	185.5
45°	173.8
47.5°	162.2
50°	149.8
52.5°	135.9
55°	115.2
57.5°	88.2
60°	55.4
62.5°	29.8
65°	13.2
67.5°	6.1
70°	4.3
72.5°	3.9
75°	3.4
77.5°	3.0
80°	2.6
82.5°	2.2
85°	1.6
87.5°	0.8
90°	0.0



TEST NUMBER: P866345
 CATALOG NUMBER: PRLX-2002-M-940-07L-L-U-S-X-X-BRSS-X

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	12.68	14.11	13.04	14.42	14.74	12.68	14.11	13.04	14.42	14.74
	3H	12.59	13.84	12.96	14.17	14.54	12.59	13.84	12.96	14.17	14.54
	4H	12.53	13.70	12.93	14.05	14.43	12.53	13.70	12.93	14.05	14.43
	6H	12.48	13.55	12.89	13.92	14.31	12.48	13.55	12.89	13.92	14.31
	8H	12.45	13.46	12.88	13.86	14.26	12.45	13.46	12.88	13.86	14.26
	12H	12.42	13.39	12.85	13.77	14.20	12.42	13.39	12.85	13.77	14.20
4H	2H	12.54	13.71	12.94	14.06	14.44	12.54	13.71	12.94	14.06	14.44
	3H	12.46	13.40	12.87	13.81	14.21	12.46	13.40	12.87	13.81	14.21
	4H	12.40	13.24	12.83	13.66	14.10	12.40	13.24	12.83	13.66	14.10
	6H	12.35	13.08	12.82	13.52	13.99	12.35	13.08	12.82	13.52	13.99
	8H	12.32	12.99	12.79	13.44	13.91	12.32	12.99	12.79	13.44	13.91
	12H	12.29	12.89	12.78	13.37	13.85	12.29	12.89	12.78	13.37	13.85
8H	4H	12.28	12.96	12.75	13.41	13.88	12.28	12.96	12.75	13.41	13.88
	6H	12.22	12.78	12.72	13.28	13.76	12.22	12.78	12.72	13.28	13.76
	8H	12.19	12.69	12.71	13.21	13.70	12.19	12.69	12.71	13.21	13.70
	12H	12.17	12.63	12.68	13.12	13.69	12.17	12.63	12.68	13.12	13.69
12H	4H	12.24	12.84	12.73	13.32	13.80	12.24	12.84	12.73	13.32	13.80
	6H	12.17	12.67	12.69	13.19	13.68	12.17	12.67	12.69	13.19	13.68
	8H	12.15	12.61	12.66	13.10	13.67	12.15	12.61	12.66	13.10	13.67