

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P866379

Luminaire Tested: PRLX-2002-M-940-45L-L-U-S-X-X-WHHR-X

Issue Date: 8/20/2024

Test Information

Test Method: LM-79-2019
Report Number: P866379
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2304-993-50)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 8/20/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: Prenalux
Catalog Number: PRLX-2002-M-940-45L-L-U-S-X-X-WHHR-X
Description: PRENATALUX 3D PRINTED PENDANT LED LUMINAIRE, MEDIUM LIGHT ENGINE, FLAT LENS, TRUNCATED DOME WITH WHITE INTERIOR SHADE.
LIGHT LEVEL 5
Light Source: 4000K CCT, 90 CRI LEDS
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 4820.6 lumens
Efficiency: N/A
Efficacy: 124.2 lumens/watt
Spacing Criteria (0/90/45): 1.19 / 1.19 / 1.3
Luminous Opening: Circular (Dia: 1.31' x H: 0')
CIE Type: Direct

Input Watts (W): 38.8
Input Voltage (V): 120
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: 0.333 HR
Operation Time: 3 HR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P866379

CATALOG NUMBER: PRLX-2002-M-940-45L-L-U-S-X-X-WHHR-X

Luminous Intensity Polar Plot





TEST NUMBER: P866379

CATALOG NUMBER: PRLX-2002-M-940-45L-L-U-S-X-X-WHHR-X

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	111	107	103	100	108	104	101	98	100	98	95	96	94	92	93	91	89	87
2	102	95	89	84	100	93	88	83	90	85	81	86	83	79	84	80	78	76
3	94	85	77	72	92	83	76	71	80	75	70	78	73	69	75	71	68	66
4	87	76	68	62	84	75	67	62	72	66	61	70	64	60	68	63	59	57
5	80	68	60	54	78	67	60	54	65	58	53	63	57	53	62	56	52	50
6	74	62	54	48	72	61	53	48	59	52	47	58	51	47	56	51	46	44
7	69	56	48	42	67	56	48	42	54	47	42	53	46	42	51	46	41	40
8	64	52	44	38	63	51	43	38	50	43	38	48	42	38	47	42	37	36
9	60	47	40	34	59	47	39	34	46	39	34	45	38	34	44	38	34	32
10	56	44	36	31	55	43	36	31	42	36	31	41	35	31	41	35	31	29

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	17171
5°	17113
10°	16945
15°	16702
20°	16413
25°	16098
30°	15755
35°	15364
40°	14952
45°	14497
50°	13965
55°	13015
60°	8740
65°	4136
70°	3036
75°	3258
80°	3610
85°	4007

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 14497 cd/sqm

TEST NUMBER: P866379

CATALOG NUMBER: PRLX-2002-M-940-45L-L-U-S-X-X-WHHR-X

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	203.1	4.2
10°-20°	571.3	11.9
20°-30°	844.6	17.5
30°-40°	989.5	20.5
40°-50°	993.2	20.6
50°-60°	801.7	16.6
60°-70°	259.1	5.4
70°-80°	111.9	2.3
80°-90°	46.2	1.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1618.9	33.6
0°-40°	2608.4	54.1
0°-60°	4403.3	91.3
0°-90°	4820.6	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	4820.6	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2158	
5°	2143	203
15°	2028	571
25°	1834	845
35°	1582	989
45°	1288	993
55°	938	802
65°	220	259
75°	106	112
85°	44	46
90°	0	

TEST NUMBER: P866379

CATALOG NUMBER: PRLX-2002-M-940-45L-L-U-S-X-X-WHHR-X

CANDELA DISTRIBUTION (FULL):

	0°
0°	2158.3
2.5°	2155.7
5°	2142.8
7.5°	2123.4
10°	2097.6
12.5°	2064.0
15°	2027.8
17.5°	1983.9
20°	1938.6
22.5°	1888.2
25°	1833.9
27.5°	1775.8
30°	1715.0
32.5°	1650.4
35°	1581.9
37.5°	1512.1
40°	1439.7
42.5°	1364.8
45°	1288.5
47.5°	1209.7
50°	1128.3
52.5°	1044.3
55°	938.3
57.5°	774.2
60°	549.3
62.5°	343.8
65°	219.7
67.5°	151.2
70°	130.5
72.5°	120.2
75°	106.0
77.5°	93.1
80°	78.8
82.5°	63.3
85°	43.9
87.5°	23.3
90°	0.0



TEST NUMBER: P866379
 CATALOG NUMBER: PRLX-2002-M-940-45L-L-U-S-X-X-WHHR-X

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	20.61	22.11	20.98	22.43	22.74	20.61	22.11	20.98	22.43	22.74
	3H	20.72	22.05	21.10	22.38	22.74	20.72	22.05	21.10	22.38	22.74
	4H	20.81	22.05	21.21	22.40	22.78	20.81	22.05	21.21	22.40	22.78
	6H	20.92	22.07	21.34	22.44	22.83	20.92	22.07	21.34	22.44	22.83
	8H	20.98	22.07	21.41	22.46	22.86	20.98	22.07	21.41	22.46	22.86
	12H	21.03	22.07	21.46	22.45	22.88	21.03	22.07	21.46	22.45	22.88
4H	2H	20.58	21.82	20.98	22.17	22.55	20.58	21.82	20.98	22.17	22.55
	3H	20.78	21.80	21.19	22.20	22.60	20.78	21.80	21.19	22.20	22.60
	4H	20.94	21.85	21.37	22.27	22.70	20.94	21.85	21.37	22.27	22.70
	6H	21.16	21.95	21.62	22.39	22.85	21.16	21.95	21.62	22.39	22.85
	8H	21.26	22.00	21.73	22.45	22.91	21.26	22.00	21.73	22.45	22.91
	12H	21.36	22.02	21.85	22.50	22.97	21.36	22.02	21.85	22.50	22.97
8H	4H	20.95	21.69	21.42	22.14	22.61	20.95	21.69	21.42	22.14	22.61
	6H	21.25	21.87	21.75	22.36	22.84	21.25	21.87	21.75	22.36	22.84
	8H	21.42	21.98	21.94	22.49	22.98	21.42	21.98	21.94	22.49	22.98
	12H	21.60	22.09	22.11	22.59	23.15	21.60	22.09	22.11	22.59	23.15
12H	4H	20.95	21.60	21.43	22.08	22.56	20.95	21.60	21.43	22.08	22.56
	6H	21.26	21.81	21.77	22.32	22.81	21.26	21.81	21.77	22.32	22.81
	8H	21.47	21.97	21.99	22.46	23.03	21.47	21.97	21.99	22.46	23.03