

Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269



Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P866402

Luminaire Tested: PRLX-2002-M-940-75L-L-U-S-X-X-GREY-X

Issue Date: 8/20/2024

**Test Information**

Test Method: LM-79-2019  
Report Number: P866402  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2304-993-52)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 8/20/2024  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: Pentalux  
Catalog Number: PRLX-2002-M-940-75L-L-U-S-X-X-GREY-X  
Description: PRENTALUX 3D PRINTED PENDANT LED LUMINAIRE, MEDIUM LIGHT ENGINE, FLAT LENS, TRUNCATED DOME WITH GRAY INTERIOR SHADE.  
LIGHT LEVEL 8  
Light Source: 4000K CCT, 90 CRI LEDS  
Ballast/Driver: -


**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 6608.8 lumens  
Efficiency: N/A  
Efficacy: 94.8 lumens/watt  
Spacing Criteria (0/90/45): 1.15 / 1.15 / 1.27  
Luminous Opening: Circular (Dia: 1.31' x H: 0')  
CIE Type: Direct  
  
Input Watts (W): 69.7  
Input Voltage (V): 120  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: 0.5 HR  
Operation Time: 3 HR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P866402

CATALOG NUMBER: PRLX-2002-M-940-75L-L-U-S-X-X-GREY-X

### Luminous Intensity Polar Plot





TEST NUMBER: P866402

CATALOG NUMBER: PRLX-2002-M-940-75L-L-U-S-X-X-GREY-X

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	111	108	105	102	109	106	103	100	101	99	97	98	96	94	94	93	91	89
2	103	97	91	87	101	95	90	86	92	88	84	89	85	82	86	83	80	78
3	96	87	80	75	93	86	79	74	83	77	73	80	76	72	78	74	71	69
4	89	78	71	65	86	77	70	65	75	69	64	73	67	63	71	66	62	60
5	82	71	63	57	80	70	63	57	68	61	56	66	60	56	64	59	55	53
6	76	64	56	51	74	64	56	51	62	55	50	60	54	50	59	53	49	48
7	71	59	51	45	69	58	51	45	57	50	45	55	49	45	54	48	44	43
8	66	54	46	41	65	53	46	41	52	45	41	51	45	40	50	44	40	38
9	62	50	42	37	61	49	42	37	48	41	37	47	41	37	46	40	36	35
10	58	46	39	34	57	45	38	34	45	38	34	44	38	33	43	37	33	32

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	26254
5°	26147
10°	25789
15°	25264
20°	24674
25°	24014
30°	23310
35°	22531
40°	21677
45°	20794
50°	19702
55°	17359
60°	9254
65°	2432
70°	1003
75°	1125
80°	1283
85°	1570

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 45°  
 Luminance: 20794 cd/sqm

TEST NUMBER: P866402

CATALOG NUMBER: PRLX-2002-M-940-75L-L-U-S-X-X-GREY-X

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	309.9	4.7
10°-20°	863.8	13.1
20°-30°	1259.5	19.1
30°-40°	1449.6	21.9
40°-50°	1422.3	21.5
50°-60°	1053.5	15.9
60°-70°	194.5	2.9
70°-80°	38.4	0.6
80°-90°	17.3	0.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2433.2	36.8
0°-40°	3882.9	58.8
0°-60°	6358.7	96.2
0°-90°	6608.8	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6608.8	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	3300	
5°	3274	310
15°	3067	864
25°	2736	1259
35°	2320	1450
45°	1848	1422
55°	1252	1054
65°	129	194
75°	37	38
85°	17	17
90°	0	

TEST NUMBER: P866402

CATALOG NUMBER: PRLX-2002-M-940-75L-L-U-S-X-X-GREY-X

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	3300.0
2.5°	3295.7
5°	3274.1
7.5°	3239.6
10°	3192.3
12.5°	3134.1
15°	3067.3
17.5°	2991.9
20°	2914.4
22.5°	2828.2
25°	2735.6
27.5°	2638.7
30°	2537.4
32.5°	2429.7
35°	2319.9
37.5°	2203.6
40°	2087.2
42.5°	1966.6
45°	1848.2
47.5°	1718.9
50°	1591.8
52.5°	1451.8
55°	1251.5
57.5°	945.6
60°	581.6
62.5°	299.4
65°	129.2
67.5°	56.0
70°	43.1
72.5°	40.9
75°	36.6
77.5°	32.3
80°	28.0
82.5°	23.7
85°	17.2
87.5°	8.6
90°	0.0



TEST NUMBER: P866402  
 CATALOG NUMBER: PRLX-2002-M-940-75L-L-U-S-X-X-GREY-X

**CIE UGR TABLE:**

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	20.95	22.38	21.31	22.69	23.00	20.95	22.38	21.31	22.69	23.00
	3H	20.85	22.11	21.23	22.43	22.80	20.85	22.11	21.23	22.43	22.80
	4H	20.79	21.96	21.20	22.31	22.69	20.79	21.96	21.20	22.31	22.69
	6H	20.74	21.81	21.15	22.18	22.57	20.74	21.81	21.15	22.18	22.57
	8H	20.71	21.73	21.14	22.12	22.52	20.71	21.73	21.14	22.12	22.52
	12H	20.68	21.65	21.11	22.04	22.47	20.68	21.65	21.11	22.04	22.47
4H	2H	20.80	21.97	21.20	22.32	22.70	20.80	21.97	21.20	22.32	22.70
	3H	20.71	21.66	21.12	22.06	22.46	20.71	21.66	21.12	22.06	22.46
	4H	20.65	21.49	21.09	21.91	22.35	20.65	21.49	21.09	21.91	22.35
	6H	20.61	21.33	21.07	21.78	22.24	20.61	21.33	21.07	21.78	22.24
	8H	20.57	21.25	21.04	21.69	22.16	20.57	21.25	21.04	21.69	22.16
	12H	20.55	21.15	21.03	21.63	22.10	20.55	21.15	21.03	21.63	22.10
8H	4H	20.54	21.21	21.00	21.66	22.13	20.54	21.21	21.00	21.66	22.13
	6H	20.48	21.04	20.98	21.53	22.01	20.48	21.04	20.98	21.53	22.01
	8H	20.44	20.95	20.96	21.46	21.95	20.44	20.95	20.96	21.46	21.95
	12H	20.43	20.88	20.94	21.37	21.94	20.43	20.88	20.94	21.37	21.94
12H	4H	20.50	21.10	20.98	21.58	22.05	20.50	21.10	20.98	21.58	22.05
	6H	20.42	20.93	20.94	21.44	21.93	20.42	20.93	20.94	21.44	21.93
	8H	20.41	20.86	20.92	21.36	21.92	20.41	20.86	20.92	21.36	21.92