

Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269



Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P865661

Luminaire Tested: PRLX-2002-S-935-10L-G-U-S-X-X-BRSS-X

Issue Date: 8/20/2024

**Test Information**

Test Method: LM-79-2019  
Report Number: P865661  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2304-993-8)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 8/20/2024  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: Prenalux  
Catalog Number: PRLX-2002-S-935-10L-G-U-S-X-X-BRSS-X  
Description: PRENTALUX 3D PRINTED PENDANT LED LUMINAIRE, SMALL LIGHT ENGINE, GLOBE LENS, TRUNCATED DOME WITH BRASS INTERIOR SHADE.  
LIGHT LEVEL 2  
Light Source: 3500K CCT, 90 CRI LEDS  
Ballast/Driver: -


**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 344.9 lumens  
Efficiency: N/A  
Efficacy: 32.8 lumens/watt  
Spacing Criteria (0/90/45): 1.36 / 1.36 / 1.52  
Luminous Opening: Circular (Dia: 0.85' x H: 0')  
CIE Type: Direct  
  
Input Watts (W): 10.5  
Input Voltage (V): 120  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: 0.333 HR  
Operation Time: 3 HR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P865661

CATALOG NUMBER: PRLX-2002-S-935-10L-G-U-S-X-X-BRSS-X

### Luminous Intensity Polar Plot





TEST NUMBER: P865661

CATALOG NUMBER: PRLX-2002-S-935-10L-G-U-S-X-X-BRSS-X

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	108	103	99	95	105	101	97	93	97	93	90		93	90	87		89	87	85	83
2	98	89	82	76	95	87	81	75	84	78	73		80	76	72		77	74	70	68
3	89	78	69	63	86	76	68	62	73	66	61		70	65	60		68	63	59	56
4	81	69	59	52	79	67	59	52	65	57	51		62	56	51		60	54	50	48
5	74	61	52	45	72	60	51	44	58	50	44		56	49	43		54	48	43	41
6	68	55	45	39	66	54	45	38	52	44	38		50	43	38		48	42	37	35
7	63	49	40	34	61	48	40	34	47	39	33		45	38	33		44	38	33	31
8	59	45	36	30	57	44	36	30	43	35	30		41	35	29		40	34	29	27
9	55	41	33	27	53	40	32	27	39	32	27		38	31	26		37	31	26	24
10	51	38	30	24	50	37	29	24	36	29	24		35	29	24		34	28	24	22

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	1927
5°	1933
10°	1947
15°	1956
20°	1969
25°	1992
30°	2024
35°	2073
40°	2143
45°	2223
50°	2259
55°	2234
60°	2168
65°	2071
70°	1955
75°	1814
80°	1633
85°	1466

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 50°  
 Luminance: 2259 cd/sqm

TEST NUMBER: P865661

CATALOG NUMBER: PRLX-2002-S-935-10L-G-U-S-X-X-BRSS-X

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	9.8	2.8
10°-20°	28.4	8.2
20°-30°	44.4	12.9
30°-40°	56.7	16.4
40°-50°	64.3	18.7
50°-60°	60.7	17.6
60°-70°	46.2	13.4
70°-80°	26.5	7.7
80°-90°	7.8	2.3
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	82.6	23.9
0°-40°	139.3	40.4
0°-60°	264.4	76.7
0°-90°	344.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	344.9	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	103	
5°	102	10
15°	101	28
25°	96	44
35°	90	57
45°	84	64
55°	68	61
65°	47	46
75°	25	27
85°	7	8
90°	0	

TEST NUMBER: P865661

CATALOG NUMBER: PRLX-2002-S-935-10L-G-U-S-X-X-BRSS-X

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	102.6
2.5°	102.6
5°	102.5
7.5°	102.4
10°	102.1
12.5°	101.4
15°	100.6
17.5°	99.6
20°	98.5
22.5°	97.4
25°	96.1
27.5°	94.6
30°	93.3
32.5°	91.9
35°	90.4
37.5°	88.9
40°	87.4
42.5°	85.8
45°	83.7
47.5°	81.0
50°	77.3
52.5°	72.9
55°	68.2
57.5°	63.0
60°	57.7
62.5°	52.2
65°	46.6
67.5°	41.2
70°	35.6
72.5°	30.3
75°	25.0
77.5°	20.0
80°	15.1
82.5°	10.8
85°	6.8
87.5°	3.5
90°	0.0



TEST NUMBER: P865661  
 CATALOG NUMBER: PRLX-2002-S-935-10L-G-U-S-X-X-BRSS-X

**CIE UGR TABLE:**

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	15.19	16.88	15.55	17.20	17.51	15.19	16.88	15.55	17.20	17.51
	3H	16.99	18.52	17.36	18.85	19.21	16.99	18.52	17.36	18.85	19.21
	4H	17.66	19.11	18.06	19.45	19.83	17.66	19.11	18.06	19.45	19.83
	6H	18.16	19.51	18.57	19.87	20.26	18.16	19.51	18.57	19.87	20.26
	8H	18.33	19.61	18.75	20.00	20.40	18.33	19.61	18.75	20.00	20.40
	12H	18.44	19.68	18.87	20.06	20.49	18.44	19.68	18.87	20.06	20.49
4H	2H	15.83	17.28	16.22	17.62	18.00	15.83	17.28	16.22	17.62	18.00
	3H	17.84	19.07	18.25	19.46	19.86	17.84	19.07	18.25	19.46	19.86
	4H	18.65	19.75	19.08	20.17	20.60	18.65	19.75	19.08	20.17	20.60
	6H	19.28	20.25	19.73	20.69	21.14	19.28	20.25	19.73	20.69	21.14
	8H	19.50	20.40	19.95	20.85	21.31	19.50	20.40	19.95	20.85	21.31
	12H	19.66	20.48	20.14	20.96	21.42	19.66	20.48	20.14	20.96	21.42
8H	4H	18.97	19.88	19.43	20.32	20.78	18.97	19.88	19.43	20.32	20.78
	6H	19.72	20.48	20.22	20.97	21.44	19.72	20.48	20.22	20.97	21.44
	8H	20.02	20.70	20.52	21.20	21.69	20.02	20.70	20.52	21.20	21.69
	12H	20.26	20.87	20.77	21.36	21.91	20.26	20.87	20.77	21.36	21.91
12H	4H	19.01	19.83	19.49	20.30	20.77	19.01	19.83	19.49	20.30	20.77
	6H	19.79	20.47	20.29	20.97	21.46	19.79	20.47	20.29	20.97	21.46
	8H	20.14	20.74	20.64	21.23	21.79	20.14	20.74	20.64	21.23	21.79