

Cooper Lighting Solutions Photometric Lab  
1121 Highway 74 South  
Peachtree City, GA 30269



Scaled data based on original data using  
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-  
State Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P865675

Luminaire Tested: PRLX-2002-S-935-15L-L-U-S-X-X-WHHR-X

Issue Date: 8/20/2024

**Test Information**

Test Method: LM-79-2019  
Report Number: P865675  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2304-993-19)  
Test Lab: COOPER LIGHTING SOLUTIONS  
Issue Date: 8/20/2024  
Manufacturer: COOPER LIGHTING SOLUTIONS  
Product Line: Prenalux  
Catalog Number: PRLX-2002-S-935-15L-L-U-S-X-X-WHHR-X  
Description: PRENTALUX 3D PRINTED PENDANT LED LUMINAIRE, SMALL LIGHT ENGINE, FLAT LENS, TRUNCATED DOME WITH WHITE INTERIOR SHADE.  
LIGHT LEVEL 3  
Light Source: 3500K CCT, 90 CRI LEDS  
Ballast/Driver: -


**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 1497.3 lumens  
Efficiency: N/A  
Efficacy: 96.0 lumens/watt  
Spacing Criteria (0/90/45): 1.2 / 1.2 / 1.31  
Luminous Opening: Circular (Dia: 0.85' x H: 0')  
CIE Type: Direct  
  
Input Watts (W): 15.6  
Input Voltage (V): 120  
Input Current (A<sub>in</sub>): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: 0.333 HR  
Operation Time: 3 HR  
Ambient Temperature (°C): NR  
Test Distance: 24 FT

TEST NUMBER: P865675

CATALOG NUMBER: PRLX-2002-S-935-15L-L-U-S-X-X-WHHR-X

### Luminous Intensity Polar Plot





TEST NUMBER: P865675

CATALOG NUMBER: PRLX-2002-S-935-15L-L-U-S-X-X-WHHR-X

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	111	107	103	100	108	104	101	98	100	98	95	96	94	92	93	91	90	88
2	102	95	89	84	100	93	88	83	90	85	81	87	83	80	84	81	78	76
3	94	85	78	72	92	83	77	71	80	75	70	78	73	69	75	71	68	66
4	87	76	68	62	85	75	68	62	72	66	61	70	65	60	68	63	60	58
5	80	69	60	54	78	68	60	54	66	59	54	64	58	53	62	57	53	51
6	74	62	54	48	73	61	54	48	60	53	47	58	52	47	56	51	47	45
7	69	57	49	43	68	56	48	43	54	47	42	53	47	42	52	46	42	40
8	65	52	44	38	63	51	44	38	50	43	38	49	42	38	48	42	38	36
9	60	48	40	35	59	47	40	35	46	39	35	45	39	34	44	38	34	32
10	57	44	37	32	55	44	36	32	43	36	31	42	36	31	41	35	31	30

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	12670
5°	12641
10°	12503
15°	12351
20°	12154
25°	11955
30°	11745
35°	11452
40°	11182
45°	10889
50°	10471
55°	8888
60°	5301
65°	2956
70°	2460
75°	2562
80°	2791
85°	2931

**MAXIMUM LUMINANCE 45°-90°:**

Horizontal Angle: 0°  
 Vertical Angle: 45°  
 Luminance: 10889 cd/sqm

TEST NUMBER: P865675

CATALOG NUMBER: PRLX-2002-S-935-15L-L-U-S-X-X-WHHR-X

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	63.5	4.2
10°-20°	179.1	12.0
20°-30°	265.7	17.7
30°-40°	312.8	20.9
40°-50°	315.3	21.1
50°-60°	233.7	15.6
60°-70°	75.0	5.0
70°-80°	37.6	2.5
80°-90°	14.6	1.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	508.3	33.9
0°-40°	821.1	54.8
0°-60°	1370.1	91.5
0°-90°	1497.3	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1497.3	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	674	
5°	670	64
15°	635	179
25°	577	266
35°	499	313
45°	410	315
55°	271	234
65°	66	75
75°	35	38
85°	14	15
90°	0	

TEST NUMBER: P865675

CATALOG NUMBER: PRLX-2002-S-935-15L-L-U-S-X-X-WHHR-X

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	674.5
2.5°	674.5
5°	670.4
7.5°	663.6
10°	655.5
12.5°	647.4
15°	635.1
17.5°	622.9
20°	608.0
22.5°	593.1
25°	576.8
27.5°	559.1
30°	541.5
32.5°	521.1
35°	499.4
37.5°	479.1
40°	456.0
42.5°	432.9
45°	409.9
47.5°	384.1
50°	358.3
52.5°	321.6
55°	271.4
57.5°	207.6
60°	141.1
62.5°	93.6
65°	66.5
67.5°	51.6
70°	44.8
72.5°	40.7
75°	35.3
77.5°	31.2
80°	25.8
82.5°	20.4
85°	13.6
87.5°	6.8
90°	0.0



TEST NUMBER: P865675  
 CATALOG NUMBER: PRLX-2002-S-935-15L-L-U-S-X-X-WHHR-X

**CIE UGR TABLE:**

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	18.51	20.00	18.88	20.31	20.63	18.51	20.00	18.88	20.31	20.63
	3H	18.76	20.08	19.13	20.41	20.77	18.76	20.08	19.13	20.41	20.77
	4H	18.92	20.15	19.32	20.50	20.88	18.92	20.15	19.32	20.50	20.88
	6H	19.11	20.25	19.52	20.61	21.01	19.11	20.25	19.52	20.61	21.01
	8H	19.20	20.28	19.62	20.67	21.07	19.20	20.28	19.62	20.67	21.07
	12H	19.27	20.30	19.70	20.68	21.11	19.27	20.30	19.70	20.68	21.11
4H	2H	18.51	19.74	18.91	20.09	20.47	18.51	19.74	18.91	20.09	20.47
	3H	18.89	19.90	19.30	20.30	20.71	18.89	19.90	19.30	20.30	20.71
	4H	19.15	20.06	19.59	20.47	20.91	19.15	20.06	19.59	20.47	20.91
	6H	19.48	20.27	19.94	20.71	21.17	19.48	20.27	19.94	20.71	21.17
	8H	19.63	20.36	20.09	20.81	21.28	19.63	20.36	20.09	20.81	21.28
	12H	19.76	20.41	20.24	20.89	21.36	19.76	20.41	20.24	20.89	21.36
8H	4H	19.22	19.96	19.69	20.40	20.87	19.22	19.96	19.69	20.40	20.87
	6H	19.65	20.26	20.15	20.76	21.24	19.65	20.26	20.15	20.76	21.24
	8H	19.88	20.43	20.39	20.94	21.43	19.88	20.43	20.39	20.94	21.43
	12H	20.09	20.58	20.60	21.08	21.64	20.09	20.58	20.60	21.08	21.64
12H	4H	19.22	19.88	19.71	20.36	20.83	19.22	19.88	19.71	20.36	20.83
	6H	19.67	20.23	20.19	20.74	21.23	19.67	20.23	20.19	20.74	21.23
	8H	19.95	20.45	20.46	20.94	21.51	19.95	20.45	20.46	20.94	21.51