

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P867206

Luminaire Tested: PRLX-2004-L-927-32L-L-X-X-GREY-X

Issue Date: 8/20/2024

Test Information

Test Method: LM-79-2019
Report Number: P867206
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2304-993-86)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 8/20/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: Prenalux
Catalog Number: PRLX-2004-L-927-32L-L-X-X-GREY-X
Description: PRENTALUX 3D PRINTED PENDANT LED LUMINAIRE, LARGE LIGHT ENGINE, FLAT LENS,
BELL WITH GRAY INTERIOR SHADE.
LIGHT LEVEL 2
Light Source: 2700K CCT, 90 CRI LEDS
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1517.9 lumens
Efficiency: N/A
Efficacy: 58.2 lumens/watt
Spacing Criteria (0/90/45): 1.02 / 1.02 / 0.98
Luminous Opening: Circular (Dia: 1.67' x H: 0')
CIE Type: Direct

Input Watts (W): 26.1
Input Voltage (V): 120
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: 0.333 HR
Operation Time: 3 HR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P867206

CATALOG NUMBER: PRLX-2004-L-927-32L-L-X-X-GREY-X

Luminous Intensity Polar Plot





TEST NUMBER: P867206

CATALOG NUMBER: PRLX-2004-L-927-32L-L-X-X-GREY-X

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	113	110	107	104	110	108	105	103	103	101	100		100	98	97		96	95	94	92
2	107	101	97	93	104	99	95	92	96	93	90		93	90	88		90	88	86	84
3	101	94	88	84	99	92	87	83	89	85	82		87	83	80		85	82	79	77
4	95	87	81	76	93	86	80	76	83	79	75		81	77	74		79	76	73	71
5	90	81	74	70	88	80	74	69	78	73	69		76	72	68		75	71	68	66
6	85	75	69	64	83	74	68	64	73	68	64		71	67	63		70	66	63	61
7	80	70	64	59	79	70	64	59	68	63	59		67	62	59		66	62	58	57
8	76	66	60	55	75	65	59	55	64	59	55		63	58	55		62	58	54	53
9	72	62	56	51	71	62	55	51	61	55	51		60	55	51		59	54	51	49
10	69	58	52	48	68	58	52	48	57	52	48		56	51	48		56	51	48	46

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	7182
5°	6949
10°	6585
15°	6299
20°	6049
25°	5813
30°	5550
35°	3888
40°	1223
45°	593
50°	442
55°	427
60°	398
65°	368
70°	343
75°	320
80°	301
85°	277

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 593 cd/sqm

TEST NUMBER: P867206

CATALOG NUMBER: PRLX-2004-L-927-32L-L-X-X-GREY-X

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	131.0	8.6
10°-20°	347.4	22.9
20°-30°	491.3	32.4
30°-40°	374.1	24.6
40°-50°	75.2	5.0
50°-60°	44.1	2.9
60°-70°	31.4	2.1
70°-80°	17.9	1.2
80°-90°	5.5	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	969.7	63.9
0°-40°	1343.8	88.5
0°-60°	1463.1	96.4
0°-90°	1517.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1517.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1456	
5°	1403	131
15°	1233	347
25°	1068	491
35°	646	374
45°	85	75
55°	50	44
65°	32	31
75°	17	18
85°	5	6
90°	0	

TEST NUMBER: P867206

CATALOG NUMBER: PRLX-2004-L-927-32L-L-X-X-GREY-X

CANDELA DISTRIBUTION (FULL):

0°	
0°	1455.7
2.5°	1444.8
5°	1403.0
7.5°	1355.9
10°	1314.3
12.5°	1274.3
15°	1233.2
17.5°	1193.9
20°	1152.0
22.5°	1109.6
25°	1067.8
27.5°	1025.4
30°	974.2
32.5°	866.0
35°	645.5
37.5°	356.9
40°	189.9
42.5°	125.6
45°	85.0
47.5°	61.2
50°	57.6
52.5°	54.0
55°	49.6
57.5°	44.7
60°	40.3
62.5°	35.7
65°	31.5
67.5°	27.7
70°	23.8
72.5°	20.2
75°	16.8
77.5°	13.7
80°	10.6
82.5°	7.8
85°	4.9
87.5°	2.3
90°	0.0

TEST NUMBER: P867206
 CATALOG NUMBER: PRLX-2004-L-927-32L-L-X-X-GREY-X

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	3.82	4.87	4.19	5.18	5.50	3.82	4.87	4.19	5.18	5.50
	3H	5.39	6.32	5.77	6.65	7.02	5.39	6.32	5.77	6.65	7.02
	4H	5.98	6.84	6.39	7.20	7.58	5.98	6.84	6.39	7.20	7.58
	6H	6.44	7.23	6.85	7.60	8.00	6.44	7.23	6.85	7.60	8.00
	8H	6.59	7.34	7.03	7.73	8.14	6.59	7.34	7.03	7.73	8.14
	12H	6.69	7.40	7.13	7.79	8.22	6.69	7.40	7.13	7.79	8.22
4H	2H	4.28	5.15	4.69	5.50	5.89	4.28	5.15	4.69	5.50	5.89
	3H	6.06	6.77	6.48	7.18	7.58	6.06	6.77	6.48	7.18	7.58
	4H	6.78	7.41	7.22	7.83	8.28	6.78	7.41	7.22	7.83	8.28
	6H	7.37	7.91	7.83	8.36	8.83	7.37	7.91	7.83	8.36	8.83
	8H	7.57	8.07	8.04	8.52	9.00	7.57	8.07	8.04	8.52	9.00
	12H	7.71	8.15	8.21	8.64	9.12	7.71	8.15	8.21	8.64	9.12
8H	4H	7.00	7.50	7.47	7.95	8.43	7.00	7.50	7.47	7.95	8.43
	6H	7.73	8.13	8.23	8.63	9.11	7.73	8.13	8.23	8.63	9.11
	8H	8.02	8.37	8.55	8.90	9.39	8.02	8.37	8.55	8.90	9.39
	12H	8.25	8.56	8.78	9.06	9.64	8.25	8.56	8.78	9.06	9.64
12H	4H	7.00	7.44	7.49	7.93	8.40	7.00	7.44	7.49	7.93	8.40
	6H	7.76	8.12	8.29	8.64	9.14	7.76	8.12	8.29	8.64	9.14
	8H	8.12	8.43	8.64	8.92	9.50	8.12	8.43	8.64	8.92	9.50