

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P867284

Luminaire Tested: PRLX-2004-L-930-67L-L-X-X-BLAK-X

Issue Date: 8/20/2024

Test Information

Test Method: LM-79-2019
Report Number: P867284
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2304-993-87)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 8/20/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: Pentalux
Catalog Number: PRLX-2004-L-930-67L-L-X-X-BLAK-X
Description: PRENTALUX 3D PRINTED PENDANT LED LUMINAIRE, LARGE LIGHT ENGINE, FLAT LENS,
BELL WITH BLACK INTERIOR SHADE.
LIGHT LEVEL 4
Light Source: 3000K CCT, 90 CRI LEDS
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2809.1 lumens
Efficiency: N/A
Efficacy: 55.7 lumens/watt
Spacing Criteria (0/90/45): 1.05 / 1.05 / 0.98
Luminous Opening: Circular (Dia: 1.67' x H: 0')
CIE Type: Direct

Input Watts (W): 50.4
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: 0.333 HR
Operation Time: 3 HR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P867284

CATALOG NUMBER: PRLX-2004-L-930-67L-L-X-X-BLAK-X

Luminous Intensity Polar Plot





TEST NUMBER: P867284

CATALOG NUMBER: PRLX-2004-L-930-67L-L-X-X-BLAK-X

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	113	111	108	106	111	108	106	104	104	103	101		101	99	98		97	96	95	93
2	108	103	99	95	106	101	97	94	98	95	92		95	92	90		92	90	88	87
3	102	96	91	87	100	94	90	86	92	88	85		89	86	83		87	84	82	81
4	97	89	84	80	95	88	83	79	86	82	78		84	80	77		82	79	76	75
5	92	84	78	73	90	83	77	73	81	76	72		79	75	72		78	74	71	70
6	87	78	72	68	86	78	72	68	76	71	67		75	70	67		73	69	66	65
7	83	74	68	63	82	73	67	63	72	66	63		70	66	62		69	65	62	61
8	79	69	63	59	78	69	63	59	68	62	59		66	62	58		65	61	58	57
9	75	65	59	55	74	65	59	55	64	59	55		63	58	55		62	58	54	53
10	71	61	56	52	70	61	55	52	60	55	51		59	55	51		59	54	51	50

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	14269
5°	13889
10°	13244
15°	12735
20°	12282
25°	11852
30°	11343
35°	7652
40°	1846
45°	472
50°	166
55°	157
60°	146
65°	133
70°	123
75°	120
80°	114
85°	96

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 472 cd/sqm

TEST NUMBER: P867284

CATALOG NUMBER: PRLX-2004-L-930-67L-L-X-X-BLAK-X

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	262.5	9.3
10°-20°	702.2	25.0
20°-30°	1001.2	35.6
30°-40°	732.6	26.1
40°-50°	74.2	2.6
50°-60°	16.3	0.6
60°-70°	11.3	0.4
70°-80°	6.6	0.2
80°-90°	2.1	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1966.0	70.0
0°-40°	2698.6	96.1
0°-60°	2789.1	99.3
0°-90°	2809.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2809.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	2892	
5°	2804	262
15°	2493	702
25°	2177	1001
35°	1270	733
45°	68	74
55°	18	16
65°	11	11
75°	6	7
85°	2	2
90°	0	

TEST NUMBER: P867284

CATALOG NUMBER: PRLX-2004-L-930-67L-L-X-X-BLAK-X

CANDELA DISTRIBUTION (FULL):

	0°
0°	2892.0
2.5°	2872.1
5°	2804.4
7.5°	2722.5
10°	2643.5
12.5°	2568.4
15°	2493.3
17.5°	2417.7
20°	2339.2
22.5°	2257.9
25°	2177.1
27.5°	2092.4
30°	1991.1
32.5°	1758.5
35°	1270.5
37.5°	646.1
40°	286.6
42.5°	151.9
45°	67.7
47.5°	23.9
50°	21.6
52.5°	19.9
55°	18.2
57.5°	16.5
60°	14.8
62.5°	13.1
65°	11.4
67.5°	9.7
70°	8.5
72.5°	7.4
75°	6.3
77.5°	5.1
80°	4.0
82.5°	2.8
85°	1.7
87.5°	1.1
90°	0.0



TEST NUMBER: P867284
 CATALOG NUMBER: PRLX-2004-L-930-67L-L-X-X-BLAK-X

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	6H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	8H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	12H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
4H	2H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	6H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	8H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	12H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
8H	4H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	6H	0.00	0.00	0.00	0.00	0.03	0.00	0.00	0.00	0.00	0.03
	8H	0.00	0.00	0.00	0.00	0.30	0.00	0.00	0.00	0.00	0.30
	12H	0.00	0.00	0.00	0.00	0.53	0.00	0.00	0.00	0.00	0.53
12H	4H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	6H	0.00	0.00	0.00	0.00	0.06	0.00	0.00	0.00	0.00	0.06
	8H	0.00	0.00	0.00	0.00	0.41	0.00	0.00	0.00	0.00	0.41