

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P867362

Luminaire Tested: PRLX-2004-L-935-83L-G-X-X-GREY-X

Issue Date: 8/20/2024

Test Information

Test Method: LM-79-2019
Report Number: P867362
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2304-993-74)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 8/20/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: Prenalux
Catalog Number: PRLX-2004-L-935-83L-G-X-X-GREY-X
Description: PRENATALUX 3D PRINTED PENDANT LED LUMINAIRE, LARGE LIGHT ENGINE, GLOBE LENS,
BELL WITH GRAY INTERIOR SHADE.
LIGHT LEVEL 5
Light Source: 3500K CCT, 90 CRI LEDS
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 1629.2 lumens
Efficiency: N/A
Efficacy: 25.3 lumens/watt
Spacing Criteria (0/90/45): 1.16 / 1.16 / 1.15
Luminous Opening: Circular (Dia: 1.67' x H: 0')
CIE Type: Direct

Input Watts (W): 64.5
Input Voltage (V): 120
Input Current (A_{in}): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: 0.333 HR
Operation Time: 3 HR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P867362

CATALOG NUMBER: PRLX-2004-L-935-83L-G-X-X-GREY-X

Luminous Intensity Polar Plot





TEST NUMBER: P867362

CATALOG NUMBER: PRLX-2004-L-935-83L-G-X-X-GREY-X

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	112	108	105	102	109	106	103	101	102	100	98		98	96	95		95	93	92	90
2	104	98	93	89	102	96	92	88	93	89	86		90	87	84		87	85	82	80
3	97	89	83	78	95	88	82	77	85	80	76		82	78	75		80	77	74	72
4	91	81	74	69	89	80	74	69	78	72	68		76	71	67		74	70	66	64
5	85	75	67	62	83	73	67	62	72	66	61		70	64	60		68	63	60	58
6	79	68	61	56	78	68	61	56	66	60	55		64	59	55		63	58	54	53
7	74	63	56	51	73	62	55	50	61	55	50		60	54	50		58	53	49	48
8	70	58	51	46	68	58	51	46	56	50	46		55	50	45		54	49	45	44
9	66	54	47	42	64	54	47	42	53	46	42		52	46	42		51	45	42	40
10	62	50	43	39	61	50	43	39	49	43	39		48	42	39		47	42	38	37

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	4872
5°	4876
10°	4859
15°	4795
20°	4712
25°	4600
30°	4368
35°	3888
40°	3282
45°	2582
50°	1820
55°	1061
60°	641
65°	552
70°	490
75°	437
80°	398
85°	374

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 2582 cd/sqm

TEST NUMBER: P867362

CATALOG NUMBER: PRLX-2004-L-935-83L-G-X-X-GREY-X

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	93.5	5.7
10°-20°	264.5	16.2
20°-30°	387.5	23.8
30°-40°	400.8	24.6
40°-50°	284.6	17.5
50°-60°	118.5	7.3
60°-70°	47.8	2.9
70°-80°	24.7	1.5
80°-90°	7.3	0.4
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	745.5	45.8
0°-40°	1146.4	70.4
0°-60°	1549.4	95.1
0°-90°	1629.2	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1629.2	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	988	
5°	985	94
15°	939	265
25°	845	387
35°	646	401
45°	370	285
55°	123	118
65°	47	48
75°	23	25
85°	7	7
90°	0	

TEST NUMBER: P867362

CATALOG NUMBER: PRLX-2004-L-935-83L-G-X-X-GREY-X

CANDELA DISTRIBUTION (FULL):

0°	
0°	987.5
2.5°	986.8
5°	984.6
7.5°	979.4
10°	969.8
12.5°	955.8
15°	938.8
17.5°	919.6
20°	897.4
22.5°	873.0
25°	845.0
27.5°	813.2
30°	766.7
32.5°	710.5
35°	645.5
37.5°	578.3
40°	509.6
42.5°	439.5
45°	370.0
47.5°	302.1
50°	237.1
52.5°	178.7
55°	123.3
57.5°	82.0
60°	65.0
62.5°	56.1
65°	47.3
67.5°	40.6
70°	34.0
72.5°	28.1
75°	22.9
77.5°	18.5
80°	14.0
82.5°	10.3
85°	6.6
87.5°	3.0
90°	0.0

TEST NUMBER: P867362

CATALOG NUMBER: PRLX-2004-L-935-83L-G-X-X-GREY-X

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	7.44	8.72	7.80	9.04	9.35	7.44	8.72	7.80	9.04	9.35
	3H	8.51	9.64	8.89	9.97	10.34	8.51	9.64	8.89	9.97	10.34
	4H	8.90	9.96	9.30	10.31	10.69	8.90	9.96	9.30	10.31	10.69
	6H	9.20	10.17	9.62	10.55	10.94	9.20	10.17	9.62	10.55	10.94
	8H	9.31	10.22	9.74	10.62	11.02	9.31	10.22	9.74	10.62	11.02
	12H	9.37	10.25	9.81	10.63	11.07	9.37	10.25	9.81	10.63	11.07
4H	2H	7.74	8.80	8.15	9.15	9.54	7.74	8.80	8.15	9.15	9.54
	3H	9.03	9.89	9.44	10.30	10.70	9.03	9.89	9.44	10.30	10.70
	4H	9.54	10.31	9.98	10.73	11.17	9.54	10.31	9.98	10.73	11.17
	6H	9.97	10.63	10.43	11.08	11.54	9.97	10.63	10.43	11.08	11.54
	8H	10.11	10.73	10.58	11.18	11.65	10.11	10.73	10.58	11.18	11.65
	12H	10.22	10.77	10.71	11.25	11.72	10.22	10.77	10.71	11.25	11.72
8H	4H	9.70	10.32	10.17	10.76	11.23	9.70	10.32	10.17	10.76	11.23
	6H	10.23	10.74	10.73	11.23	11.71	10.23	10.74	10.73	11.23	11.71
	8H	10.44	10.90	10.97	11.41	11.91	10.44	10.90	10.97	11.41	11.91
	12H	10.63	11.03	11.14	11.53	12.10	10.63	11.03	11.14	11.53	12.10
12H	4H	9.69	10.24	10.18	10.72	11.20	9.69	10.24	10.18	10.72	11.20
	6H	10.25	10.70	10.77	11.22	11.71	10.25	10.70	10.77	11.22	11.71
	8H	10.52	10.92	11.03	11.41	11.99	10.52	10.92	11.03	11.41	11.99