

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P867356

Luminaire Tested: PRLX-2004-L-935-83L-L-X-X-BLAK-X

Issue Date: 8/20/2024

Test Information

Test Method: LM-79-2019
Report Number: P867356
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2304-993-87)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 8/20/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: Prenalux
Catalog Number: PRLX-2004-L-935-83L-L-X-X-BLAK-X
Description: PRENTALUX 3D PRINTED PENDANT LED LUMINAIRE, LARGE LIGHT ENGINE, FLAT LENS,
BELL WITH BLACK INTERIOR SHADE.
LIGHT LEVEL 5
Light Source: 3500K CCT, 90 CRI LEDS
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 3648.1 lumens
Efficiency: N/A
Efficacy: 56.6 lumens/watt
Spacing Criteria (0/90/45): 1.05 / 1.05 / 0.98
Luminous Opening: Circular (Dia: 1.67' x H: 0')
CIE Type: Direct

Input Watts (W): 64.5
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: 0.333 HR
Operation Time: 3 HR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P867356

CATALOG NUMBER: PRLX-2004-L-935-83L-L-X-X-BLAK-X

Luminous Intensity Polar Plot



TEST NUMBER: P867356

CATALOG NUMBER: PRLX-2004-L-935-83L-L-X-X-BLAK-X

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	113	111	108	106	111	108	106	104	104	103	101	101	99	98	97	96	95	93
2	108	103	99	95	106	101	97	94	98	95	92	95	92	90	92	90	88	87
3	102	96	91	87	100	94	90	86	92	88	85	89	86	83	87	84	82	81
4	97	89	84	80	95	88	83	79	86	82	78	84	80	77	82	79	76	75
5	92	84	78	73	90	83	77	73	81	76	72	79	75	72	78	74	71	70
6	87	78	72	68	86	78	72	68	76	71	67	75	70	67	73	69	66	65
7	83	74	68	63	82	73	67	63	72	66	63	70	66	62	69	65	62	61
8	79	69	63	59	78	69	63	59	68	62	59	66	62	58	65	61	58	57
9	75	65	59	55	74	65	59	55	64	59	55	63	58	55	62	58	54	53
10	71	61	56	52	70	61	55	52	60	55	51	59	55	51	59	54	51	50

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	18530
5°	18038
10°	17199
15°	16540
20°	15950
25°	15392
30°	14732
35°	9938
40°	2398
45°	613
50°	216
55°	203
60°	189
65°	173
70°	160
75°	154
80°	148
85°	125

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 613 cd/sqm

TEST NUMBER: P867356

CATALOG NUMBER: PRLX-2004-L-935-83L-L-X-X-BLAK-X

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	340.9	9.3
10°-20°	912.0	25.0
20°-30°	1300.3	35.6
30°-40°	951.5	26.1
40°-50°	96.4	2.6
50°-60°	21.1	0.6
60°-70°	14.7	0.4
70°-80°	8.6	0.2
80°-90°	2.7	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	2553.2	70.0
0°-40°	3504.7	96.1
0°-60°	3622.1	99.3
0°-90°	3648.1	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	3648.1	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	3756	
5°	3642	341
15°	3238	912
25°	2827	1300
35°	1650	951
45°	88	96
55°	24	21
65°	15	15
75°	8	9
85°	2	3
90°	0	

TEST NUMBER: P867356

CATALOG NUMBER: PRLX-2004-L-935-83L-L-X-X-BLAK-X

CANDELA DISTRIBUTION (FULL):

	0°
0°	3755.8
2.5°	3730.0
5°	3642.1
7.5°	3535.7
10°	3433.0
12.5°	3335.5
15°	3238.1
17.5°	3139.8
20°	3037.9
22.5°	2932.3
25°	2827.4
27.5°	2717.3
30°	2585.9
32.5°	2283.8
35°	1650.0
37.5°	839.1
40°	372.3
42.5°	197.2
45°	87.9
47.5°	31.0
50°	28.1
52.5°	25.9
55°	23.6
57.5°	21.4
60°	19.2
62.5°	17.0
65°	14.8
67.5°	12.6
70°	11.1
72.5°	9.6
75°	8.1
77.5°	6.6
80°	5.2
82.5°	3.7
85°	2.2
87.5°	1.5
90°	0.0



TEST NUMBER: P867356
 CATALOG NUMBER: PRLX-2004-L-935-83L-L-X-X-BLAK-X

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	6H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	8H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	12H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
4H	2H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	4H	0.00	0.00	0.00	0.00	0.05	0.00	0.00	0.00	0.00	0.05
	6H	0.00	0.00	0.00	0.15	0.63	0.00	0.00	0.00	0.15	0.63
	8H	0.00	0.00	0.00	0.32	0.80	0.00	0.00	0.00	0.32	0.80
	12H	0.00	0.00	0.05	0.43	0.90	0.00	0.00	0.05	0.43	0.90
8H	4H	0.00	0.00	0.00	0.00	0.20	0.00	0.00	0.00	0.00	0.20
	6H	0.00	0.00	0.11	0.44	0.93	0.00	0.00	0.11	0.44	0.93
	8H	0.00	0.19	0.42	0.71	1.21	0.00	0.19	0.42	0.71	1.21
	12H	0.10	0.36	0.62	0.86	1.44	0.10	0.36	0.62	0.86	1.44
12H	4H	0.00	0.00	0.00	0.00	0.18	0.00	0.00	0.00	0.00	0.18
	6H	0.00	0.00	0.17	0.46	0.96	0.00	0.00	0.17	0.46	0.96
	8H	0.00	0.24	0.50	0.74	1.32	0.00	0.24	0.50	0.74	1.32