

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P867385

Luminaire Tested: PRLX-2004-L-940-133L-G-X-X-BRSS-X

Issue Date: 8/20/2024

Test Information

Test Method: LM-79-2019
Report Number: P867385
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2304-993-73)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 8/20/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: Pentalux
Catalog Number: PRLX-2004-L-940-133L-G-X-X-BRSS-X
Description: PRENTALUX 3D PRINTED PENDANT LED LUMINAIRE, LARGE LIGHT ENGINE, GLOBE LENS,
BELL WITH BRASS INTERIOR SHADE.
LIGHT LEVEL 8
Light Source: 4000K CCT, 90 CRI LEDS
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 2799.0 lumens
Efficiency: N/A
Efficacy: 25.0 lumens/watt
Spacing Criteria (0/90/45): 1.17 / 1.17 / 1.17
Luminous Opening: Circular (Dia: 1.67' x H: 0')
CIE Type: Direct

Input Watts (W): 111.8
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: 0.5 HR
Operation Time: 3 HR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P867385

CATALOG NUMBER: PRLX-2004-L-940-133L-G-X-X-BRSS-X

Luminous Intensity Polar Plot





TEST NUMBER: P867385

CATALOG NUMBER: PRLX-2004-L-940-133L-G-X-X-BRSS-X

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20			
RC	80				70				50				30				10	0		
RW	70	50	30	10	70	50	30	10	50	30	10		50	30	10		50	30	10	0
RCR																				
0	119	119	119	119	116	116	116	116	111	111	111		106	106	106		102	102	102	100
1	112	108	105	102	109	106	103	101	102	100	97		98	96	95		95	93	92	90
2	104	98	93	89	102	96	92	88	93	89	86		90	87	84		87	84	82	80
3	97	89	83	78	95	88	82	77	85	80	76		82	78	74		80	76	73	71
4	91	81	74	69	89	80	73	68	78	72	67		75	70	67		73	69	66	64
5	85	74	67	61	83	73	66	61	71	65	60		69	64	60		68	63	59	57
6	79	68	61	55	77	67	60	55	65	59	55		64	58	54		62	58	54	52
7	74	63	55	50	72	62	55	50	60	54	49		59	53	49		58	53	49	47
8	69	58	50	45	68	57	50	45	56	50	45		55	49	45		54	49	45	43
9	65	54	46	42	64	53	46	42	52	46	41		51	45	41		50	45	41	39
10	62	50	43	38	60	49	43	38	48	42	38		48	42	38		47	42	38	36

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	8132
5°	8145
10°	8120
15°	8038
20°	7916
25°	7747
30°	7391
35°	6646
40°	5680
45°	4540
50°	3294
55°	2022
60°	1142
65°	972
70°	861
75°	782
80°	707
85°	634

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 4540 cd/sqm

TEST NUMBER: P867385

CATALOG NUMBER: PRLX-2004-L-940-133L-G-X-X-BRSS-X

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	156.2	5.6
10°-20°	443.5	15.8
20°-30°	652.8	23.3
30°-40°	685.3	24.5
40°-50°	500.2	17.9
50°-60°	220.4	7.9
60°-70°	84.1	3.0
70°-80°	43.6	1.6
80°-90°	12.9	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	1252.5	44.7
0°-40°	1937.8	69.2
0°-60°	2658.4	95.0
0°-90°	2799.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	2799.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	1648	
5°	1644	156
15°	1574	444
25°	1423	653
35°	1103	685
45°	651	500
55°	235	220
65°	83	84
75°	41	44
85°	11	13
90°	0	

TEST NUMBER: P867385

CATALOG NUMBER: PRLX-2004-L-940-133L-G-X-X-BRSS-X

CANDELA DISTRIBUTION (FULL):

	0°
0°	1648.2
2.5°	1646.9
5°	1644.5
7.5°	1635.8
10°	1620.8
12.5°	1599.7
15°	1573.6
17.5°	1543.7
20°	1507.6
22.5°	1469.1
25°	1423.0
27.5°	1370.8
30°	1297.4
32.5°	1207.8
35°	1103.4
37.5°	995.1
40°	881.9
42.5°	766.3
45°	650.6
47.5°	536.1
50°	429.2
52.5°	328.4
55°	235.1
57.5°	159.2
60°	115.7
62.5°	98.3
65°	83.3
67.5°	70.9
70°	59.7
72.5°	49.8
75°	41.0
77.5°	32.3
80°	24.9
82.5°	18.7
85°	11.2
87.5°	5.0
90°	0.0



TEST NUMBER: P867385
 CATALOG NUMBER: PRLX-2004-L-940-133L-G-X-X-BRSS-X

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	10.11	11.42	10.48	11.73	12.04	10.11	11.42	10.48	11.73	12.04
	3H	10.99	12.14	11.37	12.48	12.84	10.99	12.14	11.37	12.48	12.84
	4H	11.35	12.42	11.75	12.77	13.15	11.35	12.42	11.75	12.77	13.15
	6H	11.61	12.59	12.02	12.96	13.36	11.61	12.59	12.02	12.96	13.36
	8H	11.70	12.63	12.13	13.02	13.43	11.70	12.63	12.13	13.02	13.43
	12H	11.76	12.65	12.19	13.03	13.46	11.76	12.65	12.19	13.03	13.46
4H	2H	10.34	11.41	10.74	11.76	12.14	10.34	11.41	10.74	11.76	12.14
	3H	11.44	12.31	11.85	12.71	13.12	11.44	12.31	11.85	12.71	13.12
	4H	11.91	12.69	12.34	13.11	13.55	11.91	12.69	12.34	13.11	13.55
	6H	12.29	12.96	12.76	13.41	13.88	12.29	12.96	12.76	13.41	13.88
	8H	12.43	13.06	12.90	13.50	13.97	12.43	13.06	12.90	13.50	13.97
	12H	12.53	13.08	13.01	13.56	14.04	12.53	13.08	13.01	13.56	14.04
8H	4H	12.04	12.67	12.51	13.12	13.59	12.04	12.67	12.51	13.12	13.59
	6H	12.53	13.04	13.03	13.54	14.02	12.53	13.04	13.03	13.54	14.02
	8H	12.74	13.20	13.26	13.71	14.21	12.74	13.20	13.26	13.71	14.21
	12H	12.90	13.31	13.42	13.81	14.38	12.90	13.31	13.42	13.81	14.38
12H	4H	12.04	12.59	12.52	13.07	13.55	12.04	12.59	12.52	13.07	13.55
	6H	12.54	13.01	13.07	13.52	14.01	12.54	13.01	13.07	13.52	14.01
	8H	12.80	13.21	13.32	13.71	14.28	12.80	13.21	13.32	13.71	14.28