

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P867380

Luminaire Tested: PRLX-2004-L-940-133L-L-X-X-BLAK-X

Issue Date: 8/20/2024

Test Information

Test Method: LM-79-2019
Report Number: P867380
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2304-993-87)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 8/20/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: Prenalux
Catalog Number: PRLX-2004-L-940-133L-L-X-X-BLAK-X
Description: PRENATALUX 3D PRINTED PENDANT LED LUMINAIRE, LARGE LIGHT ENGINE, FLAT LENS,
BELL WITH BLACK INTERIOR SHADE.
LIGHT LEVEL 8
Light Source: 4000K CCT, 90 CRI LEDS
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 6143.9 lumens
Efficiency: N/A
Efficacy: 55.0 lumens/watt
Spacing Criteria (0/90/45): 1.05 / 1.05 / 0.98
Luminous Opening: Circular (Dia: 1.67' x H: 0')
CIE Type: Direct

Input Watts (W): 111.8
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: 0.333 HR
Operation Time: 3 HR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P867380

CATALOG NUMBER: PRLX-2004-L-940-133L-L-X-X-BLAK-X

Luminous Intensity Polar Plot





TEST NUMBER: P867380

CATALOG NUMBER: PRLX-2004-L-940-133L-L-X-X-BLAK-X

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	113	111	108	106	111	108	106	104	104	103	101	101	99	98	97	96	95	93
2	108	103	99	95	106	101	97	94	98	95	92	95	92	90	92	90	88	87
3	102	96	91	87	100	94	90	86	92	88	85	89	86	83	87	84	82	81
4	97	89	84	80	95	88	83	79	86	82	78	84	80	77	82	79	76	75
5	92	84	78	73	90	83	77	73	81	76	72	79	75	72	78	74	71	70
6	87	78	72	68	86	78	72	68	76	71	67	75	70	67	73	69	66	65
7	83	74	68	63	82	73	67	63	72	66	63	70	66	62	69	65	62	61
8	79	69	63	59	78	69	63	59	68	62	59	66	62	58	65	61	58	57
9	75	65	59	55	74	65	59	55	64	59	55	63	58	55	62	58	54	53
10	71	61	56	52	70	61	55	52	60	55	51	59	55	51	59	54	51	50

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	31208
5°	30379
10°	28966
15°	27855
20°	26862
25°	25922
30°	24811
35°	16738
40°	4038
45°	1033
50°	363
55°	342
60°	319
65°	291
70°	270
75°	261
80°	247
85°	209

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 1033 cd/sqm

TEST NUMBER: P867380

CATALOG NUMBER: PRLX-2004-L-940-133L-L-X-X-BLAK-X

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	574.1	9.3
10°-20°	1535.9	25.0
20°-30°	2189.9	35.6
30°-40°	1602.4	26.1
40°-50°	162.3	2.6
50°-60°	35.6	0.6
60°-70°	24.8	0.4
70°-80°	14.5	0.2
80°-90°	4.6	0.1
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	4299.9	70.0
0°-40°	5902.3	96.1
0°-60°	6100.1	99.3
0°-90°	6143.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	6143.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	6325	
5°	6134	574
15°	5453	1536
25°	4762	2190
35°	2779	1602
45°	148	162
55°	40	36
65°	25	25
75°	14	14
85°	4	5
90°	0	

TEST NUMBER: P867380

CATALOG NUMBER: PRLX-2004-L-940-133L-L-X-X-BLAK-X

CANDELA DISTRIBUTION (FULL):

0°	
0°	6325.3
2.5°	6281.8
5°	6133.8
7.5°	5954.6
10°	5781.7
12.5°	5617.5
15°	5453.3
17.5°	5287.9
20°	5116.2
22.5°	4938.4
25°	4761.7
27.5°	4576.4
30°	4355.0
32.5°	3846.2
35°	2778.9
37.5°	1413.1
40°	626.9
42.5°	332.1
45°	148.0
47.5°	52.2
50°	47.3
52.5°	43.5
55°	39.8
57.5°	36.1
60°	32.3
62.5°	28.6
65°	24.9
67.5°	21.1
70°	18.7
72.5°	16.2
75°	13.7
77.5°	11.2
80°	8.7
82.5°	6.2
85°	3.7
87.5°	2.5
90°	0.0



TEST NUMBER: P867380
 CATALOG NUMBER: PRLX-2004-L-940-133L-L-X-X-BLAK-X

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3H	0.00	0.00	0.00	0.21	0.57	0.00	0.00	0.00	0.21	0.57
	4H	0.00	0.42	0.07	0.78	1.17	0.00	0.42	0.07	0.78	1.17
	6H	0.14	0.83	0.56	1.21	1.60	0.14	0.83	0.56	1.21	1.60
	8H	0.29	0.94	0.73	1.33	1.75	0.29	0.94	0.73	1.33	1.75
	12H	0.38	1.00	0.81	1.38	1.81	0.38	1.00	0.81	1.38	1.81
4H	2H	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
	3H	0.00	0.31	0.11	0.72	1.13	0.00	0.31	0.11	0.72	1.13
	4H	0.44	0.99	0.88	1.41	1.86	0.44	0.99	0.88	1.41	1.86
	6H	1.05	1.52	1.52	1.97	2.45	1.05	1.52	1.52	1.97	2.45
	8H	1.25	1.69	1.73	2.14	2.61	1.25	1.69	1.73	2.14	2.61
	12H	1.37	1.75	1.87	2.24	2.72	1.37	1.75	1.87	2.24	2.72
8H	4H	0.66	1.09	1.14	1.54	2.02	0.66	1.09	1.14	1.54	2.02
	6H	1.41	1.75	1.92	2.26	2.74	1.41	1.75	1.92	2.26	2.74
	8H	1.70	2.00	2.23	2.52	3.02	1.70	2.00	2.23	2.52	3.02
	12H	1.91	2.17	2.43	2.67	3.25	1.91	2.17	2.43	2.67	3.25
12H	4H	0.65	1.03	1.15	1.52	2.00	0.65	1.03	1.15	1.52	2.00
	6H	1.45	1.75	1.98	2.27	2.77	1.45	1.75	1.98	2.27	2.77
	8H	1.79	2.05	2.31	2.55	3.13	1.79	2.05	2.31	2.55	3.13