

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P866557

Luminaire Tested: PRLX-2004-M-935-35L-G-U-S-X-X-BRSS-X

Issue Date: 8/20/2024

Test Information

Test Method: LM-79-2019
Report Number: P866557
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2304-993-43)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 8/20/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: Prenalux
Catalog Number: PRLX-2004-M-935-35L-G-U-S-X-X-BRSS-X
Description: PRENTALUX 3D PRINTED PENDANT LED LUMINAIRE, MEDIUM LIGHT ENGINE, GLOBE LENS,
BELL WITH BRASS INTERIOR SHADE.
LIGHT LEVEL 4
Light Source: 3500K CCT, 90 CRI LEDS
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 708.0 lumens
Efficiency: N/A
Efficacy: 23.6 lumens/watt
Spacing Criteria (0/90/45): 1.17 / 1.17 / 1.14
Luminous Opening: Circular (Dia: 1.31' x H: 0')
CIE Type: Direct

Input Watts (W): 30
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: 0.5 HR
Operation Time: 3 HR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P866557

CATALOG NUMBER: PRLX-2004-M-935-35L-G-U-S-X-X-BRSS-X

Luminous Intensity Polar Plot





TEST NUMBER: P866557

CATALOG NUMBER: PRLX-2004-M-935-35L-G-U-S-X-X-BRSS-X

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	112	108	105	103	109	106	103	101	102	100	98	98	97	95	95	93	92	90
2	105	99	94	89	102	97	92	88	93	90	86	90	87	84	88	85	83	81
3	98	90	84	79	96	88	83	78	86	81	77	83	79	75	81	77	74	72
4	91	82	75	70	89	81	74	70	79	73	69	76	72	68	74	70	67	65
5	85	75	68	63	84	74	67	62	72	66	62	70	65	61	69	64	61	59
6	80	69	62	57	78	68	61	56	67	61	56	65	60	56	64	59	55	53
7	75	64	57	52	74	63	56	51	62	56	51	60	55	51	59	54	50	49
8	71	59	52	47	69	59	52	47	57	51	47	56	51	46	55	50	46	45
9	66	55	48	43	65	54	48	43	53	47	43	52	47	43	51	46	43	41
10	63	51	44	40	62	51	44	40	50	44	40	49	43	39	48	43	39	38

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	3528
5°	3527
10°	3514
15°	3489
20°	3425
25°	3343
30°	3185
35°	2795
40°	2288
45°	1699
50°	1093
55°	592
60°	438
65°	375
70°	330
75°	292
80°	261
85°	256

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 1699 cd/sqm

TEST NUMBER: P866557

CATALOG NUMBER: PRLX-2004-M-935-35L-G-U-S-X-X-BRSS-X

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	41.9	5.9
10°-20°	119.2	16.8
20°-30°	174.7	24.7
30°-40°	178.4	25.2
40°-50°	116.5	16.5
50°-60°	43.3	6.1
60°-70°	20.2	2.8
70°-80°	10.4	1.5
80°-90°	3.3	0.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	335.9	47.4
0°-40°	514.3	72.6
0°-60°	674.1	95.2
0°-90°	708.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	708.0	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	444	
5°	442	42
15°	424	119
25°	381	175
35°	288	178
45°	151	117
55°	43	43
65°	20	20
75°	10	10
85°	3	3
90°	0	

TEST NUMBER: P866557

CATALOG NUMBER: PRLX-2004-M-935-35L-G-U-S-X-X-BRSS-X

CANDELA DISTRIBUTION (FULL):

0°	
0°	443.5
2.5°	442.6
5°	441.6
7.5°	438.8
10°	435.0
12.5°	430.2
15°	423.6
17.5°	415.0
20°	404.6
22.5°	393.2
25°	380.8
27.5°	366.6
30°	346.7
32.5°	320.1
35°	287.8
37.5°	254.5
40°	220.3
42.5°	185.2
45°	151.0
47.5°	118.7
50°	88.3
52.5°	62.7
55°	42.7
57.5°	32.3
60°	27.5
62.5°	23.7
65°	19.9
67.5°	17.1
70°	14.2
72.5°	12.3
75°	9.5
77.5°	7.6
80°	5.7
82.5°	4.7
85°	2.8
87.5°	1.9
90°	0.0



TEST NUMBER: P866557
 CATALOG NUMBER: PRLX-2004-M-935-35L-G-U-S-X-X-BRSS-X

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	5.59	6.85	5.95	7.16	7.47	5.59	6.85	5.95	7.16	7.47
	3H	6.78	7.89	7.16	8.22	8.58	6.78	7.89	7.16	8.22	8.58
	4H	7.22	8.25	7.62	8.60	8.98	7.22	8.25	7.62	8.60	8.98
	6H	7.52	8.47	7.94	8.84	9.24	7.52	8.47	7.94	8.84	9.24
	8H	7.65	8.55	8.08	8.94	9.34	7.65	8.55	8.08	8.94	9.34
	12H	7.73	8.59	8.17	8.97	9.40	7.73	8.59	8.17	8.97	9.40
4H	2H	5.95	6.98	6.36	7.34	7.72	5.95	6.98	6.36	7.34	7.72
	3H	7.36	8.20	7.78	8.61	9.01	7.36	8.20	7.78	8.61	9.01
	4H	7.91	8.66	8.34	9.08	9.52	7.91	8.66	8.34	9.08	9.52
	6H	8.33	8.98	8.80	9.42	9.89	8.33	8.98	8.80	9.42	9.89
	8H	8.50	9.11	8.98	9.56	10.03	8.50	9.11	8.98	9.56	10.03
	12H	8.64	9.17	9.12	9.65	10.13	8.64	9.17	9.12	9.65	10.13
8H	4H	8.07	8.67	8.54	9.12	9.59	8.07	8.67	8.54	9.12	9.59
	6H	8.60	9.10	9.11	9.59	10.08	8.60	9.10	9.11	9.59	10.08
	8H	8.86	9.31	9.39	9.82	10.32	8.86	9.31	9.39	9.82	10.32
	12H	9.08	9.47	9.59	9.96	10.54	9.08	9.47	9.59	9.96	10.54
12H	4H	8.07	8.60	8.55	9.08	9.56	8.07	8.60	8.55	9.08	9.56
	6H	8.63	9.07	9.15	9.59	10.08	8.63	9.07	9.15	9.59	10.08
	8H	8.95	9.34	9.46	9.83	10.41	8.95	9.34	9.46	9.83	10.41