

Cooper Lighting Solutions Photometric Lab
1121 Highway 74 South
Peachtree City, GA 30269



Scaled data based on original data using
LM-79-2019 Approved Method: Electrical and Photometric Measurements of Solid-
State Lighting Products

Test Report Prepared for
Cooper Lighting Solutions

Brand: PrentaLux

Report Number: P865863

Luminaire Tested: PRLX-2004-S-940-10L-G-U-S-X-X-WHHR-X

Issue Date: 8/20/2024

Test Information

Test Method: LM-79-2019
Report Number: P865863
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (G3-2304-993-11)
Test Lab: COOPER LIGHTING SOLUTIONS
Issue Date: 8/20/2024
Manufacturer: COOPER LIGHTING SOLUTIONS
Product Line: Prenalux
Catalog Number: PRLX-2004-S-940-10L-G-U-S-X-X-WHHR-X
Description: PRENTALUX 3D PRINTED PENDANT LED LUMINAIRE, SMALL LIGHT ENGINE, GLOBE LENS,
BELL WITH WHITE INTERIOR SHADE.
LIGHT LEVEL 2
Light Source: 4000K CCT, 90 CRI LEDS
Ballast/Driver: -

Summary


Lumens per Lamp: N/A
Luminaire Lumens: 559.9 lumens
Efficiency: N/A
Efficacy: 53.3 lumens/watt
Spacing Criteria (0/90/45): 1.18 / 1.18 / 1.21
Luminous Opening: Circular (Dia: 0.92' x H: 0')
CIE Type: Direct

Input Watts (W): 10.5
Input Voltage (V): 120
Input Current (Ain): NR
Voltage Rise (V): NR
Power Factor: NR
Total Harmonic Distortion (THDi): NR
Frequency (hertz): 60
Stabilization Time: 0.5 HR
Operation Time: 3 HR
Ambient Temperature (°C): NR
Test Distance: 24 FT

TEST NUMBER: P865863

CATALOG NUMBER: PRLX-2004-S-940-10L-G-U-S-X-X-WHHR-X

Luminous Intensity Polar Plot





TEST NUMBER: P865863

CATALOG NUMBER: PRLX-2004-S-940-10L-G-U-S-X-X-WHHR-X

COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	110	106	102	98	107	103	100	97	99	96	94	95	93	91	92	90	88	86
2	101	94	88	83	99	92	86	82	88	84	80	85	81	78	82	79	76	74
3	93	84	76	70	91	82	75	70	79	73	69	77	72	67	74	70	66	64
4	86	75	67	61	84	74	66	61	71	65	60	69	64	59	67	62	58	56
5	80	68	60	54	78	67	59	53	65	58	53	63	57	52	61	56	52	50
6	74	62	54	48	72	61	53	47	59	52	47	58	51	47	56	50	46	44
7	69	56	48	43	67	56	48	42	54	47	42	53	47	42	52	46	42	40
8	65	52	44	38	63	51	44	38	50	43	38	49	43	38	48	42	38	36
9	61	48	40	35	59	47	40	35	46	39	35	45	39	35	44	39	34	33
10	57	44	37	32	56	44	37	32	43	36	32	42	36	32	41	36	32	30

AVERAGE LUMINANCE (cd/sqm):

	0°
0°	4288
5°	4290
10°	4278
15°	4267
20°	4239
25°	4127
30°	3931
35°	3614
40°	3247
45°	2892
50°	2517
55°	2181
60°	1892
65°	1733
70°	1650
75°	1531
80°	1493
85°	1404

MAXIMUM LUMINANCE 45°-90°:

Horizontal Angle: 0°
 Vertical Angle: 45°
 Luminance: 2892 cd/sqm

TEST NUMBER: P865863

CATALOG NUMBER: PRLX-2004-S-940-10L-G-U-S-X-X-WHHR-X

ZONAL LUMENS:

Zone	Lumens	% Fixture
0°-10°	24.9	4.4
10°-20°	71.2	12.7
20°-30°	105.2	18.8
30°-40°	113.1	20.2
40°-50°	96.8	17.3
50°-60°	69.1	12.3
60°-70°	45.0	8.0
70°-80°	26.4	4.7
80°-90°	8.3	1.5
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	201.3	36.0
0°-40°	314.4	56.1
0°-60°	480.3	85.8
0°-90°	559.9	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	559.9	100.0

CANDELA DISTRIBUTION:

	0°	Flux
0°	263	
5°	262	25
15°	253	71
25°	229	105
35°	182	113
45°	125	97
55°	77	69
65°	45	45
75°	24	26
85°	8	8
90°	0	

TEST NUMBER: P865863

CATALOG NUMBER: PRLX-2004-S-940-10L-G-U-S-X-X-WHHR-X

CANDELA DISTRIBUTION (FULL):

	0°
0°	262.9
2.5°	262.9
5°	262.0
7.5°	261.1
10°	258.3
12.5°	255.5
15°	252.7
17.5°	248.0
20°	244.2
22.5°	237.7
25°	229.3
27.5°	219.9
30°	208.7
32.5°	195.6
35°	181.5
37.5°	166.6
40°	152.5
42.5°	139.4
45°	125.4
47.5°	112.3
50°	99.2
52.5°	88.0
55°	76.7
57.5°	66.4
60°	58.0
62.5°	51.5
65°	44.9
67.5°	39.3
70°	34.6
72.5°	29.9
75°	24.3
77.5°	20.6
80°	15.9
82.5°	11.2
85°	7.5
87.5°	3.7
90°	0.0



TEST NUMBER: P865863
 CATALOG NUMBER: PRLX-2004-S-940-10L-G-U-S-X-X-WHHR-X

CIE UGR TABLE:

Reflectances:											
Ceiling		0.7	0.7	0.5	0.5	0.3	0.7	0.7	0.5	0.5	0.3
Wall		0.5	0.3	0.5	0.3	0.3	0.5	0.3	0.5	0.3	0.3
Reference plane		0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2	0.2
Room dimensions		Viewed crosswise					Viewed endwise				
X=2H	Y=2H	13.62	15.11	13.98	15.42	15.74	13.62	15.11	13.98	15.42	15.74
	3H	15.15	16.49	15.53	16.82	17.18	15.15	16.49	15.53	16.82	17.18
	4H	15.77	17.02	16.17	17.37	17.75	15.77	17.02	16.17	17.37	17.75
	6H	16.29	17.45	16.70	17.81	18.21	16.29	17.45	16.70	17.81	18.21
	8H	16.46	17.56	16.88	17.95	18.35	16.46	17.56	16.88	17.95	18.35
	12H	16.58	17.64	17.01	18.02	18.45	16.58	17.64	17.01	18.02	18.45
4H	2H	14.12	15.37	14.52	15.72	16.10	14.12	15.37	14.52	15.72	16.10
	3H	15.91	16.95	16.32	17.35	17.75	15.91	16.95	16.32	17.35	17.75
	4H	16.65	17.59	17.09	18.01	18.45	16.65	17.59	17.09	18.01	18.45
	6H	17.32	18.14	17.78	18.58	19.04	17.32	18.14	17.78	18.58	19.04
	8H	17.54	18.31	18.01	18.75	19.22	17.54	18.31	18.01	18.75	19.22
	12H	17.72	18.40	18.20	18.88	19.35	17.72	18.40	18.20	18.88	19.35
8H	4H	16.95	17.71	17.41	18.16	18.62	16.95	17.71	17.41	18.16	18.62
	6H	17.75	18.38	18.24	18.87	19.35	17.75	18.38	18.24	18.87	19.35
	8H	18.05	18.62	18.56	19.13	19.62	18.05	18.62	18.56	19.13	19.62
	12H	18.31	18.82	18.82	19.31	19.88	18.31	18.82	18.82	19.31	19.88
12H	4H	16.98	17.66	17.46	18.14	18.61	16.98	17.66	17.46	18.14	18.61
	6H	17.80	18.37	18.32	18.88	19.37	17.80	18.37	18.32	18.88	19.37
	8H	18.17	18.67	18.68	19.16	19.73	18.17	18.67	18.68	19.16	19.73