

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: RSA

Report Number: P226104

Luminaire Tested: **MRZ-1-REC-X-1-L27-97-FL-UNV-X-STD-HEX**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P226104  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P14876)  
Test Lab: INNOVATION CENTER (G1)  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: RSA  
Catalog Number: MRZ-1-REC-X-1-L27-97-FL-UNV-X-STD-HEX  
Description: MRZ INTEGRAL LED DOWNLIGHT  
40 DEGREE FLOOD OPTIC WITH HEX LOUVER, LIGHT LEVEL 1  
Light Source: (1) 2700K CCT, 97 CRI LEDS  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 245.0 lumens  
Efficiency: N/A  
Efficacy: 45.4 lumens/watt  
Spacing Criteria (0/90/45): 0.56 / 0.56 / 0.55  
Luminous Opening: Circular (Dia: 0.17' x H: 0')  
CIE Type: Direct


Input Watts (W): 5.4  
Input Voltage (V): 120  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P226104

CATALOG NUMBER: MRZ-1-REC-X-1-L27-97-FL-UNV-X-STD-HEX

### Luminous Intensity Polar Plot





TEST NUMBER: P226104

CATALOG NUMBER: MRZ-1-REC-X-1-L27-97-FL-UNV-X-STD-HEX

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	115	112	110	108	112	110	108	107	106	105	103	103	101	100	99	98	98	96
2	110	106	103	100	108	105	102	99	102	99	97	99	97	95	96	95	93	92
3	106	101	97	94	104	100	96	93	97	94	92	95	93	91	93	91	89	88
4	102	97	92	89	101	95	91	88	93	90	87	92	89	86	90	87	85	84
5	99	92	88	84	97	91	87	84	90	86	83	88	85	83	87	84	82	81
6	95	88	84	80	94	88	83	80	86	83	80	85	82	79	84	81	79	78
7	92	85	80	77	91	84	80	77	83	79	76	82	79	76	81	78	76	75
8	89	82	77	74	88	81	77	74	80	76	73	79	76	73	78	75	73	72
9	86	79	74	71	85	78	74	71	77	73	71	77	73	70	76	73	70	69
10	83	76	71	68	83	76	71	68	75	71	68	74	71	68	73	70	68	67

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	334906
5°	318207
10°	275194
15°	206408
20°	128636
25°	67613
30°	30479
35°	11745
40°	4573
45°	2303
50°	1075
55°	860
60°	395
65°	467
70°	0
75°	0
80°	0
85°	0



TEST NUMBER: P226104

CATALOG NUMBER: MRZ-1-REC-X-1-L27-97-FL-UNV-X-STD-HEX

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	58.5	23.9
10°-20°	109.2	44.6
20°-30°	59.2	24.2
30°-40°	14.3	5.8
40°-50°	2.7	1.1
50°-60°	0.7	0.3
60°-70°	0.2	0.1
70°-80°	0.0	0.0
80°-90°	0.0	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	227.0	92.7
0°-40°	241.3	98.5
0°-60°	244.7	99.9
0°-90°	245.0	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	245.0	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	679	
5°	642	58
15°	404	109
25°	124	59
35°	20	14
45°	3	3
55°	1	1
65°	0	0
75°	0	0
85°	0	0
90°	0	



TEST NUMBER: P226104

CATALOG NUMBER: MRZ-1-REC-X-1-L27-97-FL-UNV-X-STD-HEX

**CANDELA DISTRIBUTION (FULL):**

	0°
0°	678.8
2.5°	666.3
5°	642.5
7.5°	606.7
10°	549.3
12.5°	481.5
15°	404.1
17.5°	321.5
20°	245.0
22.5°	177.2
25°	124.2
27.5°	83.6
30°	53.5
32.5°	32.9
35°	19.5
37.5°	12.0
40°	7.1
42.5°	4.8
45°	3.3
47.5°	1.9
50°	1.4
52.5°	1.0
55°	1.0
57.5°	0.4
60°	0.4
62.5°	0.4
65°	0.4
67.5°	0.0
70°	0.0
72.5°	0.0
75°	0.0
77.5°	0.0
80°	0.0
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)