

Scaled data based on original data using  
LM-79-08 Approved Method: Electrical and Photometric Measurements of Solid-State  
Lighting Products

Test Report Prepared for  
Cooper Lighting Solutions  
(formerly Eaton)

Brand: RSA

Report Number: P219662

Luminaire Tested: **MRZ-1-REC-X-4-L27-97-NFL-UNV-X-STD-SFL**

Issue Date: 3/3/2020

**Test Information**

Test Method: LM-79-08  
Report Number: P219662  
TEST IS SCALED FROM IESNA LM-79-08 TEST DATA (P14873)  
Test Lab: INNOVATION CENTER (G1)  
Issue Date: 3/3/2020  
Manufacturer: COOPER LIGHTING SOLUTIONS (FORMERLY EATON)  
Product Line: RSA  
Catalog Number: MRZ-1-REC-X-4-L27-97-NFL-UNV-X-STD-SFL  
Description: MRZ INTEGRAL LED DOWNLIGHT  
25 DEGREE NARROW FLOOD OPTIC WITH SOFT FOCUS LENS, LIGHT LEVEL 4  
Light Source: (1) 2700K CCT, 97 CRI LEDS  
Ballast/Driver: ELECTRONIC DRIVER

**Summary**

Lumens per Lamp: N/A  
Luminaire Lumens: 1073.4 lumens  
Efficiency: N/A  
Efficacy: 67.9 lumens/watt  
Spacing Criteria (0/90/45): 0.41 / 0.41 / 0.4  
Luminous Opening: Circular (Dia: 0.17' x H: 0')  
CIE Type: Direct


Input Watts (W): 15.8  
Input Voltage (V): 120  
Input Current (Ain): NR  
Voltage Rise (V): NR  
Power Factor: NR  
Total Harmonic Distortion (THDi): NR  
Frequency (hertz): 60  
Stabilization Time: NR  
Operation Time: NR  
Ambient Temperature (°C): NR  
Test Distance: 25 FT



TEST NUMBER: P219662

CATALOG NUMBER: MRZ-1-REC-X-4-L27-97-NFL-UNV-X-STD-SFL

### Luminous Intensity Polar Plot





TEST NUMBER: P219662

CATALOG NUMBER: MRZ-1-REC-X-4-L27-97-NFL-UNV-X-STD-SFL

**COEFFICIENT OF UTILIZATION - ZONAL CAVITY METHOD:**

RF	20				20				20				20				20	
RC	80				70				50				30				10	0
RW	70	50	30	10	70	50	30	10	50	30	10	50	30	10	50	30	10	0
RCR																		
0	119	119	119	119	116	116	116	116	111	111	111	106	106	106	102	102	102	100
1	115	113	111	109	112	110	109	107	106	105	104	103	102	101	99	99	98	96
2	111	107	104	101	109	105	102	100	102	100	98	99	97	96	97	95	94	92
3	107	102	98	95	105	101	97	95	98	95	93	96	94	92	94	92	90	89
4	103	98	94	91	102	97	93	90	95	92	89	93	90	88	91	89	87	86
5	100	94	90	87	99	93	89	86	92	88	85	90	87	85	89	86	84	83
6	97	91	86	83	96	90	86	83	89	85	82	87	84	82	86	83	81	80
7	94	88	83	80	93	87	83	80	86	82	80	85	82	79	84	81	79	78
8	92	85	80	77	91	84	80	77	83	80	77	82	79	77	82	79	76	75
9	89	82	78	75	88	82	78	75	81	77	75	80	77	74	79	76	74	73
10	87	80	76	73	86	79	75	73	79	75	73	78	75	72	77	74	72	71

**AVERAGE LUMINANCE (cd/sqm):**

	0°
0°	2406508
5°	2195308
10°	1579323
15°	784513
20°	319594
25°	165003
30°	96907
35°	56255
40°	35423
45°	24072
50°	15735
55°	9892
60°	6315
65°	5954
70°	3751
75°	2478
80°	3694
85°	0



TEST NUMBER: P219662

CATALOG NUMBER: MRZ-1-REC-X-4-L27-97-NFL-UNV-X-STD-SFL

**ZONAL LUMENS:**

Zone	Lumens	% Fixture
0°-10°	382.0	35.6
10°-20°	436.5	40.7
20°-30°	148.5	13.8
30°-40°	61.9	5.8
40°-50°	27.0	2.5
50°-60°	10.9	1.0
60°-70°	4.6	0.4
70°-80°	1.9	0.2
80°-90°	0.2	0.0
90°-100°	0.0	0.0
100°-110°	0.0	0.0
110°-120°	0.0	0.0
120°-130°	0.0	0.0
130°-140°	0.0	0.0
140°-150°	0.0	0.0
150°-160°	0.0	0.0
160°-170°	0.0	0.0
170°-180°	0.0	0.0
0°-30°	967.0	90.1
0°-40°	1028.9	95.8
0°-60°	1066.8	99.4
0°-90°	1073.4	100.0
90°-120°	0.0	0.0
90°-150°	0.0	0.0
90°-180°	0.0	0.0
0°-180°	1073.4	100.0

**CANDELA DISTRIBUTION:**

	0°	Flux
0°	4878	
5°	4433	382
15°	1536	436
25°	303	149
35°	93	62
45°	34	27
55°	12	11
65°	5	5
75°	1	2
85°	0	0
90°	0	



TEST NUMBER: P219662

CATALOG NUMBER: MRZ-1-REC-X-4-L27-97-NFL-UNV-X-STD-SFL

**CANDELA DISTRIBUTION (FULL):**

0°	
0°	4877.6
2.5°	4770.2
5°	4432.6
7.5°	3878.8
10°	3152.4
12.5°	2330.1
15°	1535.9
17.5°	948.9
20°	608.7
22.5°	413.1
25°	303.1
27.5°	226.4
30°	170.1
32.5°	126.6
35°	93.4
37.5°	70.3
40°	55.0
42.5°	42.2
45°	34.5
47.5°	26.9
50°	20.5
52.5°	15.3
55°	11.5
57.5°	9.0
60°	6.4
62.5°	5.1
65°	5.1
67.5°	3.8
70°	2.6
72.5°	2.6
75°	1.3
77.5°	1.3
80°	1.3
82.5°	0.0
85°	0.0
87.5°	0.0
90°	0.0

(END OF REPORT)